

538

AD-A208

US Army Corps of Engineers

Southwestern Division

**Reservoir Control Center** 

# Annual Report 1988


January 1989



THE PACESETTER DIVISION

This document has been approved to public release and salet im

89 6 02 027



REPORT DOCUMENTATION	READ INSTRUCTIONS BEFORE COMPLETING FORM				
I. REPORT HUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG	HUMBER JUNE		
(HONE)	<u> </u>				
4. TITLE (and Subilife)		FINAL REPORT	EMOD COVERED .		
ANNUAL REPORT		FY-88 (1 Oct 87	- 31 Sen 88		
1988		4. PERFORMING ONG. RE			
January 1989		1	Ohr no-con Mar		
7. AUTHOR(*)	<del></del>	B. CONTRACT OR GRANT	HUMBER(+)		
Reservoir Control Center	•		: "		
Southwestern Division (Albuquerque					
Galveston, Little Rock, and Tuls					
J. PERFORMING ORGANIZATION HAME AND ADDRESS U.S. Army Corps of Engineers		16. PROGRAM ELEMENT, P	UMBERS		
Southwestern Division (CESWD-ED-WR	)				
1114 Commerce Street, Room 301		]	•.		
11. CONTROLLING OFFICE HARE AND ADDRESS		12. REPORT DATE			
		January 1989			
Office, Chief of Engineers, U.S. A	rmy	13. NUMBER OF PAGES	182		
Washington, DC 20314-1000					
U.S. Army Corps of Engineers	it men Controlling Office)	IL BECURITY GLASS (M	mie report)		
Southwestern Division (CESWD-ED-WR	)	Unclassified			
1114 Commerce Street, Room 301	,	THE DECLASHFICATION	DOWNGRADING		
Dallas, Texas 75242-0216		PCHEDULE			

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

#### 18. SUPPLEMENTARY NOTES

Available from:

Administrator, Defense Technical Information Center, ATTN: DTIC/DDA-2 Bldg. #5 Cameron Station, Alexandria, VA 22814

19. KEY WORDS (Cantinue on severee side if necessary and identify by block member)

Lake Regulation activities

Regulation plans:

Water control manuals Water quality activities

Sediment activities

Data collection and management; Water control automated data system

It. ABSTRACT (Continue on reverse side it reservents and identify by block tember)

This report presents activities and accomplishments of the Southwestern Division (SWD) as related to reservoir regulation and water management activities for fiscal year 1988. Also presents detailed summaries of the reservoir conditions, water quality activities, and coordinating activities with other Federal and non-Federal basin interests groups.

exi No Perior

DO 1 JAN 73 1473 EDITION OF ! HOV SE IS OBSOLETE

Unclassified

SECURITY CLASSIFK: ATION OF THIS PAGE (

Acces	ssion For	
NTIS	GRA&I	H
DTIC	TAB	T
Unan	nounced	
Just	ification	
By	ribution/	
Dist	ribution/	
Dist		Codes

### ANNUAL REPORT RESERVOIR CONTROL CENTER SOUTHWESTERN DIVISION

1988

#### **PLATE**

Dams and Reservoirs in the Southwestern Division Inside Front Cover

TABLE OF CONTENTS

SECTION	I -	INTRODUCTION	PAGE
1.	Pur	pose of Report	I-1
2.	Ref	erence	I-1
3.	Obje	ectives of the Reservoir Control Center	I-1
SECTION	II ·	- WATER CONTROL ACTIVITIES IN SWD	
1.	Res	ervoir Regulation	I I ~ 1
	a.	Lake Regulation During FY 88	11-1
	b.	System Studies	II-1
	c.	Water Control Manuals	11-1
	<b>d</b> .	Drought Contingency Plans	11-2
	e.	Section 7 Project Regulation	11-2
2.	SWD	Water Quality Program and Activities	11-3
	a.	Responsibilities	I1-3
	b.	Organization	11-3
	c.	Special Activities in FY 88	I1-4
	d.	Long-Term Goals	II-5
	e.	Immediate Goals	II-5
3.	SWD	Sediment Program and Activities	11-5
4.	Dat	a Collection and Management	11-5
	a.	Stream Gaging Program	11-5
	b.	Cooperative Reporting Networks	II-6
	c.	Water Control Data System	II-6
	a	Cooperative Data Bank and Worsessting Activity	11-7

# TABLE OF CONTENTS (CONTINUED)

5.	Coordination with Water Management Interests	II-8
	a. General	II-8
	b. Agency Coordination	11-8
SECTION	III - FACILITIES AND PERSONNEL	
1.	Facilities	III-1
	a. Office Space	III-1
	b. Display Facilities	III-1
	c. Communications Equipment	III-1
2.	Personnel	III-1
	a. Staff	111-1
	b. Training	III-1
SECTION	IV - STATUS OF RESERVOIR WATER CONTROL MANUALS AND DROUGHT CONTINGENCY PLANS	
SECTION	V - REGULATION OF MULTI-PURPOSE PROJECTS WITH HYD	ROPOWER
SECTION	VI - DISTRICT WATER CONTROL ACTIVITIES	
1.	Project Visitation by Water Management Personnel	<b>V</b> I-1
2.	Special Reservoir Operations	VI-3
3.	Water Quality Program and Activities	VI - 14
4.	Sediment Program and Activities	<b>V</b> I-20
5.	Navigation Activities	VI-22
6.	Cooperative Programs	VI-24
7.	Annual Flood Damages, Per River Basin, Prevented by Both Corps and Section 7 Projects	<b>V</b> I-26
8.	Annual Flood Damages, By State, Prevented by Corps Projects	<b>V</b> I-30

# TABLE OF CONTENTS (CONTINUED)

	9.	Annual Flood Damages, By State, Prevented by Corps Supported Emergency Operations	<b>V</b> I-31
	10.	Hydropower Production	<b>V</b> I-32
	11.	Lake Attendance	<b>V</b> I-33
	12.	Water Supply Storage	<b>V</b> I-35
S <b>E</b> C	TION	VII - RESERVOIR DATA SUMMARY	
	1.	SWD Map	
	2.	Index by Basins	

4. Data Tables

SECTION VIII - MINUTES OF THE ARKANSAS RIVER BASIN COORDINATING COMMITTEE MEETING AND THE ANNUAL RESERVOIR CONTROL CENTER MEETING

1. Reservoir Control Center

3. Index in Alphabetical Order

2. Arkansas River Basin

RESERVOIR CONTROL CENTER
1988 ANNUAL REPORT

SECTION I - INTRODUCTION

#### SECTION I - INTRODUCTION

1. <u>PURPOSE OF REPORT</u>. This report presents activities and accomplishments of the Southwestern Division (SWD) as related to reservoir regulation and water management activities throughout FY 1988. Detailed summaries of reservoir conditions, water quality activities, minutes of coordinating committee meetings and minutes of the 1988 Annual Reservoir Control Center meeting are also included.

This report is prepared in conformance with ER 1110-2-1400. 24 April 1970, Reservoir Control Centers, paragraph 12c.

- 2. <u>REFERENCE</u>. Reservoir Control Center (RCC) SWD Guidance Memorandum, dated June 1971, approved by the Chief of Engineers as a general basis for the RCC's activities.
- 3. OBJECTIVES OF THE RESERVOIR CONTROL CENTER. The SWD RCC was established in 1967 by the Chief of Engineers to improve capabilities of the Corps of Engineers to perform its civil works mission as related to operation of reservoirs. The SWD RCC carries out its responsibilities by:
- a. Organizing coordinating committees and/or participating in committees to accomplish mutual understanding among water interests regarding use and regulation of water resources.
- b. Providing interbasin coordination of day-to-day regulation needs for river systems for all purposes.
- c. Surveillance of daily operations and continuous analysis of Project needs.
- d. Furnishing technical assistance to personnel of District offices in related efforts to improve the reliability of regulations and hydrologic determinations.
- e. Provide management and technical guidance for the development and operation of the Division-wide dedicated water control data system. This system includes the equipment and software used for the acquisition, transmission and processing of real-time hydrologic and meteorological data for the purpose of regulating projects for which the Corps of Engineers has responsibility.

SECTION II - WATER CONTROL ACTIVITIES IN SWD

#### SECTION II - WATER CONTROL ACTIVITIES IN SWD

#### 1. RESERVOIR REGULATION

a. <u>Lake Regulation During FY 88.</u> Lake regulation activities for Division lakes and Section 7 lakes during FY 88 are summarized in Section VI of this report. Operational data summaries for all of the SWD projects, including Section 7, are shown in tabular form, Section VII An index, by basin, to these tables is included which also lists pertinent data for each project. Also included is a listing in alphabetical order giving names of both the lake and dam where different.

#### b. System Studies - FY 88

- (1) Brazos River Super Model Fort Worth District Completed the final development of the Brazes River hydrology and system model. The period or record is January 1940 through December 1986. Simulations for natural and existing conditions were run to verify the hydrology and model.
- (2) White River Super Model Little Rock District Reservoir Regulation Thirteen additional simulations were made for the Little Rock Reservoir Regulation section in their attempt to develop a regulation plan to enhance farming along the White River.
- (3) White River Super Model Little Rock District Planning The White River hydrology was updated through 1986 and the natural and existing conditions were run to verify the hydrology. The Planning study is a navigation study on the White River system.
- (4) Red River Super Model Tulsa Data for the Red River update was collected and verified during the latter months of this FY. This model wil be used in the Texoma restudy.
- (5) Trinity River Super Model Fort Worth District Data for the Trinity River update was collected and verified during the latter months of this FY. This model will be used for the Trinity river Regulation study.
- (6) Arkansas River Feasibility Study Tulsa and Little Rock Districts The hydrology and Modified SUPER (computer) model for the Arkansas River Planning Model (contains eleven proposed reservoir sites) was completed in FY 88. The period of record is January 1940 through December 1986. Natural and existing condition runs were made to verify the hydrology and computer model. The economic portion of the model was also updated.
- c. <u>Water Control Manuals</u>. A summary entitled "Status of Water Control Manuals in SWI" is included in Section IV of this report. The summary shows the status and completion schedule through FY 1991 for manuals and plans on 118 lakes and 17 river

systems and subsystems. Also shown in Section IV is a schedule for completion of high priority water control manuals for FY 89 thru FY 94. At the end of FY 1988, there were 97 Corps of Engineers projects (80 lakes and 17 locks and dams) and 19 Section 7 lakes in operation in SWD.

During FY 1988, the SWD Reservoir Control Center received and reviewed five water control manuals that were submitted by the Districts. The schedule for FY 1989 includes the development of four new manuals and the revision of four old manuals.

- DROUGHT CONTINGENCY PLANS. A letter dated 8 June 1988 "Drought Contingency Plans (DCP)" renewed efforts Subject: within the Southwestern Division for the development of DCP's and provided additional guidance to supplement that contained in ER-This letter requested that DCP's be developed 1110-2-1941. all Corps projects with controlled reservoir storage and that the plans should only address temporary project modifications to satisfy short-term needs that can be implemented within existing During FY 88 several meetings were held in the SWD authorities. office with District personnel to develop a framework for DCP's, submittal schedules. review procedures, funding, etc. It was agreed that the DCP's would address individual projects. However, they would be developed on a river basin or sub-basin concept to include like projects. Each of the documented DCP's will become an appendix to the respective river basin Master Water Control Manual. A total of 23 DCP's will be developed for the river basins within the SWD. These plans were prioritized scheduled for completion by FY 91. Table IV showing the river basin and projects within each basin is included in Section IV of this report. The table also shows a schedule for completion of the 23 DCP'S. During FY 88 initial drafts of the six first priority basin plans were submitted for review. In FY 89 initial drafts are scheduled for review and six in FY 90.
- <u>Section 7 Project Regulation.</u> Within SWD there are existing Section 7 reservoirs owned and operated by other The Bureau of Reclamation's Brantley Dam located on agencies. Pecos River began deliberate impoundment on 28 August 1988. The flood control storage contained in these projects are regulated by the Corps in accordance with Section 7 of the Flood Control Act of The Districts are continuing their efforts to bring the manuals and regulation plans into compliance with requirements contained in paragraph 208.11, Part 208 Flood Control Regulations, Chapter 11, Title 33 of the Code of Federal Regulations (41 FR 20401, May 18. 1976). Due to the varied approaches between the Districts on real time regulation for Section 7 projects, SWDO issued a policy letter on 21 March 1983. The purpose of the letter was to supersede previous SWDO guidance and to provide current policies on Section 7 projects. This letter and subsequent letters have been issued to the Districts requiring that policy on Section 7 projects be coordinated with project owners and that finalizing of water control manuals for existing projects should be expedited.

#### 2. SOUTHWESTERN DIVISION WATER QUALITY PROGRAM AND ACTIVITIES.

- a. <u>Responsibilities</u>. The Water Management Branch is assigned the responsibilities to coordinate and direct activities in SWD in the water quality field. This provides for water quality objectives being included as an effective part of our total water management program. Specific activities in the water quality program are as follows:
- (1) Conduct technical studies and provide guidance on water quality control.
- (2) Review and provide technical assistance in programs for predicting the natural and modified water quality in impoundments, rivers, coastal areas, and estuaries for project planning, design, and regulation activities.
- (3) Review and provide technical assistance on project design and reservoir regulation studies in connection with water quality control performed within the Division, including multiple level outlet facilities, reservoir simulation studies, reregulation structures, and release reoxygenation systems.
- (4) Provide coordination support in interagency liaison as related to water quality control through reservoir regulation, including formulation of operating plans and cooperative data collection programs.
- (5) Coordinate with Planning and Construction-Operations Divisions, and the Districts on SWD water quality investigation programs.
- (6) In coordination with the Geotechnical and Materials Branch, manage the water quality investigation activities of the Division laboratory.
- (7) Responsible for technical engineering solutions to water quality problems in existing projects: reviewing, coordinating, and acting as consultants to other engineering and planning elements in the Division office and District offices.
- (8) Coordination of Division actions required by ER 1130-2-334 for reporting of water quality management of Corps projects.

#### b. ORGANIZATION.

- (1) <u>Division.</u> Water quality activities in SWD are coordinated within the Water Management Branch. These duties require the part-time efforts of two engineers in Water Management Branch, one biologist in Construction-Operations and a fisheries biologist in Planning Division. Mr. Charles Sullivan, Chief. RCC, is the SWD member on the HQUSACE Committee on Water Quality.
- (2) <u>Districts.</u> The organizations for water quality management vary within the Districts. Water quality associated

with planning and design of the projects is coordinated by organizational elements within the Engineering or Planning Divisions in all of the districts. Monitoring and reporting specifically required by ER 1130-2-334 and that required for dredging and other construction activities are done by the Construction, Operations, Engineering or Planning Divisions in the various districts depending on their capabilities.

(3) <u>Laboratory</u>. The Division laboratory is staffed and equipped to conduct water quality testing required by the Districts for use in planning, design, construction, and operation of the projects. However, because of location, costs and other factors most water quality testing is contracted with private laboratories by the Districts.

#### c. Special Activities in FY 88.

- (1) <u>Specific Project Problems</u>. Water Quality related problems and activities at individual projects are discussed in the District reports. Other items in this section are highlights of activities.
- (2) <u>Water Quality Management Reports.</u> Water quality management reports were completed for one additional projects in FY 88. Water quality management reports are now available on 18 SWD projects. Most of these reports are for Fort Worth District projects.
- (3) <u>Baseline Data.</u> Baseline data acquisition was initiated at one additional SWD reservoir project in FY 88. As of the end of the year base line data has been obtained at over 40 reservoirs. Our goal in this program is to develop a water quality data base for all SWD reservoir projects.
- (4) <u>Canyon Lake Non-Federal Hydropower Development.</u> The Waterways Experiment Station (WES) selected Canyon Lake as a research field site for developing techniques to evaluate the impacts associated with installation of hydropower at Corps dams. An intensive water quality data collection program was initiated in the summer of 1988 to determine base (prior to power-on-line) conditions. The study will continue through the summer of 1989 to determine post (after power-on-line) conditions.
- (5) <u>Table Rock Dissolved Oxygen.</u> WES physical and mathematical model studies have determined that retrofitting the structure with selective withdrawal facilities will not solve the dissolved oxygen problem. Little Rock District is awaiting the WES report before proceeding. Model results were discussed with Missouri State representatives in Sept. 1988.
- (6) Abiquiu Lake Waste Material Problems. Several problems were encountered as the result of construction activities last year. Sediment and turbidity increased due to placement of spoil material downstream from Abiquiu Dam next to the Rio Chama channel. The spoil area is being cut back and vegetated to reduce

the erosion. Construction and office trash was found on the same spoil site. Albuquerque District removed the material and took two series of soil and water samples to alleviate concerns.

- d. <u>Long-Term Goals</u>. The following are presently considered as long-term continuous goals of this Division, and consequently the Water Management Branch, in the water quality field.
- (1) To obtain sufficient water quality information from all of our projects to determine whether all state standards and environmental objectives can be met without adverse impact on authorized uses.
- (2) To promote the organization of effective water quality elements in the Division and Districts to obtain the maximum coordination for handling all water quality matters in the Division.
- (3) To provide helpful and thorough guidance to the Districts on water quality matters.
- e. <u>Immediate Goals</u>. The following actions have been scheduled for accomplishment in the near future:
- (1) Continue the present intensive monitoring program for SWD reservoirs. This ongoing program will be continued until base line data are available for all SWD reservoirs.
  - (2) Review the basic water quality, monitoring program.
- 3. <u>SWD SEDIMENT PROGRAM AND ACTIVITIES</u>. Sediment activities for the year included a field survey for one reservoir sedimentation resurvey. None of the sediment ranges along the McClellan-Kerr Arkansas River Navigation Project were resurveyed in FY88. Due to the funding priorities assigned to reservoir sedimentation resurveys, it's almost impossible to receive funding. Several water contracting entities have expressed an interest in obtaining resurveys to determine the depletion rates on their resource but we have been unable to obtain the necessary funding.

#### 4. DATA COLLECTION AND MANAGEMENT.

a. Stream Gaging Program. The reporting and measurement of flow, water quality and sediment data are required for regulation, investigation and design of water resources projects. Most of these data are obtained through a Cooperative Steam Gaging program between the Corps and the U.S. Geological Survey (USGS). During FY 1988 the SWD-USGS cooperative program contained 445 surface water stations, 46 water quality stations, and 57 suspended sediment stations. An additional 66 stations were operated independently by the District Corps offices. In FY 88, the total cost of the SWD program was \$3.0 million with \$2.4 million being transferred to the USGS. The following tabulation shows a breakdown of the program by class of funds used to finance the program.

Class of Funds	C of E Cost \$1,000)
Survey Investigation General Coverage Planning Operation & Maintenance New Work & Construction	20 56 0 2, <b>4</b> 03 <u>88</u>
TOTAL:	2,487

Cooperative Reporting Networks. The National Weather (NWS) and the Corps of Engineers began their 51st year of Service cooperation in establishing and operating networks of river and/or rainfall reporting stations. Reports from these supplement those stations that are maintained by the NWS which are made available to the Corps of Engineers for flood control operations and flood forecasting. Data from these networks are transmitted to the Corps of Engineers District and Division offices via telephone and computer interface from the NWS collection office. A direct interface between the NWS computers located in the Fort Worth, Texas and Tulsa, Oklahoma NWS River Forecast Centers and the Corps Water Control Data System (WCDS) Harris carries hydrological reports, and other data to our water control management functions. essential These data include detailed precipitation reports, river stage information, descriptions of severe storms and floods, and river warnings. forecasts developed by the NWS. SWDO has obtained a small computer which dial NWS radar sites for current radar images which can be stored for later viewing.

The estimated FY 1988 cost for SWD responsibilities in supporting 482 rainfall stations in the NWS Cooperative Reporting Networks was \$246,939.

- c. <u>Water Control Data System</u>. The "Water Control Data System Master Plan" for SWD, dated April 1979 was approved by the Office, Chief of Engineers in June 1979 for funding and detailed design. A "Water Control Data System Software Manual," dated February 1983 was developed as the system software design document.
- (1) <u>Communication.</u> The Data Collection Platforms DCP's transmit the remote gaging station data over the Geostationary Orbiting Environmental Satellite (GOES) System. Communication between the District and Division data processing units is via the Division wide data communications network. A ground Receive Station (GRS) is located at Fort Worth, Texas, for receipt of the transmission. The SWD system was installed at the Federal Center in Fort Worth, Texas, in September 1983. This Synergetics Model 10C direct Readout Ground Receive Station equipped with 2 antennas (one for GOES east and one for GOES Both dial-up and direct line access is provided between west). the GRS and the WCDS computers. Transfer of National Weather

Service (NWS) Automated Field Office Service (AFOS) data between the Corps and National Weather Service River Forecast Center computers is on a continuous basis via direct lines.

- (2) Data Acquisition and Analysis. In June 1982, the RCC began using the Water Control Data System (Harris Computer) located in the Southwestern Division office, for computations that are necessary in the RCC's daily water control activities. Harris minicomputers were installed in the SWDO, Tulsa District, Fort Worth District, and Little Rock District offices as a part of the division wide Water Control Data System. The Albuquerque and Galveston Districts operate remotely from the computer located in SWDO. During FY 85 (as part of a Corps wide procurement contract) the original H-100 and H-500 computers were replaced by Harris 1000 computers at each of the four sites. The hardware at each site is compatible in order to allow the use of common software and data exchange between offices. A division wide data base is maintained on the SWDO machine and the other sites maintain a data base applicable to the site. The data bases at each District office are available to the Division office. The current base uses the "TOTAL" data base management system and the code for data exchange with the National Weather Service. During 88 work continued on software development for analysis and display of the data.
- (3) <u>Data Display and Distribution</u>. Data is displayed in individual offices with color graphic CRT's, PC's, plotters, and printers. Graphic applications programs utilize "TEMPLATE" Software which is licensed by Megatek Corporation. Provisions are made to exchange data with other water management cooperators. Examples of cooperative data exchange requirements are the Office of Chief Engineers, Lower Mississippi Valley Division (LMVD). National Weather Service, Southwestern Power Administration (SWPA), state and local river authorities or agencies. During the past year several routines were developed for the display of information in a graphical format. There also have been several routines developed for display of current project data and reports.
- Cooperative Data Base and Forecasting Activity. The RCC continues to participate in and encourage the advancement of programs for automated data collection and interagency cooperation in forecasting activity and data base utilization. Currently, SWD maintains a data base on the WCDS for Daily Generation reports. and daily River Reports. These data bases are updated daily and the data are maintained until the end of the month then used for These data, with several District auxiliary monthly summaries. programs and data bases, have been used to make forecasts and reports available for exchange as needed between the Districts and In addition, the data are made available to other users which have a need to be aware of the water control activities. Several users have participated in using the USGS WATSTORE data bank for storing and retrieving data.
  - e. <u>Continuity of Operations Plan (COOP)</u>. During the past

year a draft COOP for the Southwestern Division Water Control Data System has been developed. This plan outlines procedures for providing back up capability in the event of a equipment failure at any one site in the SWD WCDS. Plans are to test and finalize the COOP during FY 89.

#### 5. COORDINATION WITH WATER MANAGEMENT INTERESTS.

- a. <u>General</u>. The benefits deriving from personal contact with other persons associated with water management activities are well recognized by the RCC. For this reason, special emphasis has been placed on maintaining this personal contact through meetings and workshops sponsored by the Districts and the RCC with the marketing agency, project personnel, river basin authorities, other Divisions, the Chief's office and others.
- (1) The Hydrologic Engineering Section and the Hydraulics Section (other sections in the Water Management Branch) furnish support to the RCC. The Hydrologic Engineering Section conducts systems studies of Reservoir Regulation and the Hydraulics Section reviews studies on sediment and water quality activities.
- (2) A meeting of lake regulation personnel of each of the Districts and the RCC is held annually at the Division Reservoir Control Center for the purpose of discussing timely topics and exchanging information. Periodically the Hydrologic Engineering and the Hydraulics Sections will hold joint meetings with the RCC. The minutes of the 16 and 17 November 1988 meeting are included in Section VIII.

#### b. Agency Coordination.

(1) Arkansas River Basin Coordinating Committee. After being inactive since the 30 April 1982 meeting in Little Rock, Arkansas the committee was reestablished in connection with the notification of adoption of the "1986 Arkansas River Water Control System Operation Plan." The notification for the plan was issued on 17 June 1986 with the plan becoming effective on 1 July 1986. The second meeting of the reestablished committee was held in Dallas on 6 June 1988. At this meeting it was agreed to hold another meeting in the Spring of 1989. The minutes of the meeting are included in section VIII.

# MEETINGS OF THE REESTABLISHED ARKANSAS COORDINATING COMMITTEE

Meeting	Date
1 2	28 Jan 1987 6 Jun 1988

(2) <u>Cooperation with Lower Mississippi Valley Division.</u>
The SWD RCC continues its cooperation with LMVD and provides

observed, as well as forecasted data, that are significant to the water management activities in LMVD.

- Cooperation with Southwestern Power Administration. SWPA is an agency of the United States, established in the The Department of Energy, to execute the purposes of the Flood Control Act of 1944 with respect to the disposition of the electric power and energy made available from the reservoir projects under control of the Department of the Army in the area comprising all of Arkansas and Louisiana and portions of Missouri, Kansas, Texas, and Oklahoma. The scheduling of releases for hydropower production from the 17 Corps of Engineers projects within SWD has a significant effect on the overall water management activities in close cooperation and continuous Therefore, the Division. communication between the Corps and SWPA are mandatory. Memorandum of Understanding was signed by the SWPA and the Corps Engineers in 1980. SWPA and SWD have proceeded to develop a draft detail Operating Arrangement to assist in the operations of hydropower projects within SWD. SWD has formally informed the SWPA that the draft document would be its policy for coordinating operations with them until such time that both agencies have signed the arrangement. Specific activities included in the Operating Arrangement for cooperation between SWPA and RCC monthly scheduling of power production, preparation of data for reports to the Federal Energy Regulatory Commission (FERC), daily coordination of routine data on current conditions, inflow forecasts, and release schedules. The RCC has taken every opportunity to improve and strengthen relations with SWPA through correspondence, regularly scheduled and special meetings, providing access to our time-share systems, and by special studies aimed at improving energy production and scheduling at SWD power projects.
- (4) <u>National Weather Service</u>. A NWS Interagency Support Agreement was signed by General Lee on 17 July 1988 for hydrometeorological services for the Southwestern Division. agreement provides that a full time NWS employee will be assigned to the Reservoir Control Center, NWS expects to fill this position by January 1989. Also, during the past year, meetings between the Corps and NWS were held to refine procedures for computer to computer exchange of hydrometeorological data. Meetings were also held to improve coordinated snow runoff forecasts. AFOS products are being furnished from the NWS S/140 computers to the CE H-1000 computers on a continuous basis via direct line between The Ft. Worth NWS in cooperation with SWD and machines. developed software which allows the transmission of the Graphics products to the Corps through the VUENWS Program. Efforts are continuing to develop the software required to allow the direct transmission of CE products to the NWS AFOS system. This would also be by the direct line link between the NWS and CE computers.
- (5) <u>General Accounting Office (GAO)</u>. The SWD RCC has continued to cooperate with GAO in their investigation of the

forecasting and regulation activities which were associated with the October 1986 flood in Oklahoma. This review was initiated during the latter stages of the flood event and has continued through the current FY. We have furnished GAO documentation on project plans of regulations, weather data, stream flow data. lake data, etc., which was available during the flood. The assembly of this information has involved numerous man-hours of effort during 1987-88. GAO completed an interim report in 1987 and a final report was made in 1988. In general, the reports supported SWD operation of the Arkansas River Basin Project during the Oct 1986 flood. However, a legal opinion provided by GAO Counsel, questioned the Corps' authority to operate those projects in the Arkansas Basin for the benefit of navigation if the project had not specifically been authorized for navigation. Corps Counsel reviewed this finding by GAO, and supported SWD authority to use projects in the Arkansas Basin to support navigation.

Section III - FACILITIES AND PERSONNEL

#### SECTION III - FACILITIES AND PERSONNEL

#### 1. Facilities.

- a. Office Space. SWDO personnel occupies quarters on the third floor in the Sante Fe Building, 1114 Commerce Street, Dallas. Texas. Space occupied by the RCC includes an open-space working area, and an equipment room.
- b. <u>Display Facilities</u>. All of the display equipment used for conferences and for briefings of higher authorities are located in the Engineering Division conference room. This room has limited space and equipment; but, it does include chalkboards, white metal panel adequate for use of markers, portable projection equipment, a projection screen, and a large screen display unit driven by an IBM-XT.
- c. <u>Communications Equipment.</u> The equipment room contains a multiplexor, two dot-matrix hard-copy TTY terminals, one letter quality terminal, a tektronix color graphics terminal with plotter, printer and digitizing tablet, IBM-AT and printer, IBM-XT which is used to drive the large screen display, Sony color monitor with VTR and an Alden Color Radar system. The Sony color monitor is used to monitor and record weather and news events on the Cable News Network, Weather Channel, and local TV stations. The Alden Color Radar system is used to monitor and record radar images from National Weather Service radars within SWD and along the Gulf Coast.

#### 2. Personnel.

- a. <u>Staff</u>. The authorized staff of the RCC consists of one supervisory hydraulic engineer, two hydraulic engineers and one hydrologic technician. The RCC is supported in technical studies by the Hydrologic Engineering and the Hydraulics Sections. The current organization chart for the SWD Water Management Branch is shown in figure 1.
- b. <u>Training</u>. The RCC periodically assesses the training needs of its personnel and schedules that training which is required and possible. Training for the past year included a System Analyst course for the Harris H-1000 Water-Mini.

				SECTION	CHIEF GM-14	GS-13		
				HYDRAULICS SEC	T. SCHMIDGALL Hydraulic Engr	D.R. BROWN Hydraulic Engr		
RANCH	CHIEF GM-15	GS-05		G SECTION	CHIEF GM-14	GS-13	GS-13	
WATER MANAGEMENT BRANCH	H. E. WALKER Supv Hydraulic Engr	BETTE MacOUEEN Secretary		HYDROLOGIC ENGINEERING SECTION	R.L. HULA Supv Hydraulic Engr	S.L. BATES Hydraulic Engr	J.L. CURTIS Hydraulic Engr	
				ENTER	CHIEF GM-14	GS-13	GS-13	GS-11
GURE 1		•	III-Z	RESERVOIR CONTROL CENTER	C.H. SULLIVAN Supv Hydraulic Engr	R.E. GARLAND Hydraulic Engr	J.R. PARKS Hydraulic Engr	C.H. VICTRY Hydrologic Tech

FIG

# SECTION IV STATUS OF RESERVOIR WATER CONTROL MANUALS AND DROUGHT CONTINGENCY PLANS

#### STATUS DE WATER CONTROL MANUALS IN SWI-(Report Control Symbol DAEN-CWE-16) Revised: January 1989

PESERGOIF	STREAM						THRU FY RI
WHITE PIV MASTER		εE	LAD	DEC 55			85° 90 - U
BEAVER	WHITE RIV BASIN	£Ε	LRD	JAN 67			-
TABLE POCK	WHITE RIV BASIN WHITE RIVER BASIN	<b>EE</b>	LPD	JAN 57	<b>005</b>	F	
BULL SHOALS	WHITE RIVER BASIN	EE	LRD	JAN 57	DOE	۴	
NORFORE	WHITE RIVER BASIN	23	LRD	JAN 67		ŗ	
CLEARWATER	BLACK RIVER	33	LRD	FEB 73	รพร	£+	
GREERS FERRY	LITTLE RED RIVER	CE	LRE	JUN 66	DDE	F	
APKANEAS MASTER		ſF	£ħ.	JUN 70	OFF	F	
PUTSLO (1)	AFRANEAE PINEF						
	FURGHTORIE FILEF						
	ARI ANEAS RIVES						
APKANSAS MAZTEF		CE	TD	007 80	SWE	F	
CHENET (1)	N.F.NINNESCAH	BR	TD	MAR 65			
EL TORADO				FEB 83			
ž.Aw	AFFANSAS PIVER	C E	TD	JAN 78			
SREAT SALT FLAINS	SALT FORK AFK	CE	70				
KERETONE .	ARKANEAS RIVER	CE	10	AUG 71 AFR 65	OFF	£	
HETBURN	FOLECAT CREEK	CE	15	DEC 84	5k[	F	
VERDIGETS SISTEM	t						
TORONTO	MERCIGRIS FIVER	ſ E	I F	AUG 66	ULE	ţ	NSV 88 - U
	FALL RIVES			AUG 65			7127 CC C
ELP CITY	ELE RIVER			AUG 55			
PEARSON-SI UEITI-BIS HILL				APR 83			
00L05AH	VEFDIGRIS RIVER			JUL 76			
COPAN	CANEY RIVER			MAR 83			
	CAMEY RIVER			JUN 69			
	BIRD CREEK						
	HOMINA CREEK						
GRAND SYSTEM							
COUNCIL SEGVE	NEOSHO RIVER	CE	TD	MAY 74	SWD	£	
MARION	COTTONWOOD RIVER	33	TG	AUG 74	SND		
JOHN REDMOND	NEOSHE RIVER	CE	TD	77	UND		
PENSACOLA (1)	NEOSHO RIVER	GRDA	TE	MAR 65	DCE	ΔP	
MAREHAM FERRY (1)	NEOSHO RIVER	GRDA	TD	MAR 65	OCE		
FORT GIBSON	NEOSHO RIVER	CE	TO	MAR 65	300		
TENKILLER FERRY	ILLINGIS RIVER	CE	10	MAR 77	SMD	F	

#### STATUS OF MATER CONTROL MANUALS IN SWD (Report Control Symbol DAEN-CWE-16) Revised: Candany 1989

RESERVOJS	STREAM	OWNER	PIST	APPROVEE			
C LABIAN SYSTEM CONCHAS SANFORD (1) NORMAN (1) OFTIMA FORT SUPPLY CANTON ARCADIA EUFAULA	••••••••••						••••••••••••
CONCHAS	CANADIAN RIVER	CE	AD	JAN 68	999	F	
SANFORD (1)	CANACIAN RIVER	BR	75	FEE 66			
NORMAN (1)	LITTLE RIVER	EF:	10	DEC 65			
OFT1M-	N. CANADIAN PINER	CE	TD	JAN 72			
FORT SUPPLY	WOLF EREEL	CE	TD	JAN 72			
CANTON	M. CANADIAN FINER	CE	TO	JAN 72			
ARCADIA	DEER FORK RIVER	CE	10	JUN SE			
EUFAJLA	CANADIAN PIVER	CE	TD	NDV 63			
NEWY GRAHAM RT 93. LED 18	AFRANSAS PIVER	CE	ŢŢ.	AUS 72	ter.	F	
CHOUTEAU PT V. LGC 17	ARMANBAB BILER	E F		AUS 72			
CHOUTEAS PT V. 185 17 MESSESS FALLS PT TOULSD 15	AERANSAS ELVES	55	77,	308 75	t at.	r	
R.S. PERS ST 111, LNT 15	ARIANSAS PINES	LE.	Tr.	00N 72	CHU	r E	
W.D. MAY2 FT 11, 155 14	ARKANSAS RIMER	CE	10	FEB 73	SHI	F	
WISTER	PETEAU RIVER	רנ	Ťr.	10N: 74	tur	•	
BLUE MOGNTAIN	PRINT TRAN	L.C.	10	HAD ID	540	} ~	
NIMESI	FOURTHE LA FAVE	CE CE	LPD	MAR 68			
150) 1 564 T	ATTIONED DE MES					_	
LOCK & DAM IT	FREENDAD REVER	::	LPD	SEP 4	581		MAY PO F
GIARK-CETA TANICE DARDANELLE BOSK & DAM F	AFIANSAS PINES	LE	LF.i	SEF 74	5#.E	F	
ERCH E ROW I	ARTHNOAS HIVER	i.E	LPD	APS 75	SWI	F	
EDON & DAM 9 TOAT SUIN FERRY	ASTRIBLE RIVER	CE.	LEI	APR 75	SND	F	
FORE COMMIT MEETING	ARTHROPS RIVER	CE	LFD	AUS 74	SME	Ĺ	
LOCK & DAM T MURRAY	APPANONS KIVER	CE	LRD	AUS 74	SWE	F	
Eddy e beu a besti fi 1568:	HELBERT KILER	[ E	LFD	SEP 74	SWD	F	
LOCK & DAM T LOCK & DAM 4	ARYANDAS RIVER	CE	LRE	SEP 74	SMD	F	
_	· · · ·	Ų.		GE1 / 7	24.5	,	
LOCK & DAM I	ARKANSAS RIVER	£ E	LFD	SEP 74	S₩D	F	
	ARKANENE BIVER	ĘΕ	LRD	SEP 74	S₩Û	F	
EBOK & DAM 1 (AS) PEST BANAL!	ARKANSAS RIVER	CE.	LRD	SEP 74	SWD	£	
PED RIVER MASTES		C.E.	715	CCD /7	מכר	A F:	
ALTUS (1)	W COOL DER	33	TD TD	FEP 63		AR	
MOUNTAIN PASK (1)	N. FORK RED OTTED COCC.	8£	TD	96 T30	OCE		
TRUSCOTT BRINE LAKE	OTTER CREE; BLUFF CREE;	₽Ŕ	10	MAR 76	SND	Ŕ <b>÷</b>	
LAKE FEMP (1)		CE	TE:	11111	<b>.</b>		
MAURILA	WICHITA RIVER	#CID	10	JUN 73	5#D		
F055 :1)	BEAVER CREEK	EE .	TD	APR 77	SMO		
FORT CORR (1)	WASHITA RIVER	₽R	10	MAY 61	OCE		
ARBUCELE (1)	CORR CREEK	<b>8</b> £	15	MAR 61	330		
TEXONA	ROCK CREEK	8E	TD	SEP 67	330		
PAT HAYSE	RED RIVER	CE	TD	SEP 82	SWD		
SARDIS	SANDERS CREEK	CE	TD	OCT 67	DCE		
MCGEE CREEK (1)	JACKFORK CREEK	CE	TD	AUG 84	SWD		
	MUDDY BOORY CREEK	BR	70	MAY 87	SWD		FEB 89 F
HUG0	⊁IAMICHI RIVER	CE	TĐ	JUL 82	SMD	AF	

#### STATUS OF WATER CONTROL MARGALS IN SWO (Report Control Symbol DAEN-EME-16) Revised: January 1989

PESSRVD1F	STREAM	OWNER	DIST	APPRO	/E0	SCHEDULED THEO FY 91		
LITTLE RIV SYS	177. F - 0.1055	rr	7.5	214 74	rut.	A.F.		
FINE CREE!	HITTLE RIVER	ίξ [ <b>Ε</b>	TE:	JUL 74 NOV 74				
BROHEN BON	MOUNTAIN FOFF	53						
DEGLEEN	POLLING FORE			-				
GILLHAM	COSSATOT RIVER							
DIERUS	SALINE RIVER LITTLE RIVER	EE EE	LED Led					
MITTMOSD	Civile niven	FE	LND	BUY 15	247.	r		
SULPHUR RIV MASTER								
COGFER	SULPHUR RIVER	CE	EKD				356 8 <b>6</b>	
MRISHT PATHAN	SULPHUR RIVES	33	FWE	NOV 74	LMVE	F	95T 89	
LAKE ET THE PINES	CYPRESS CREE:	23	FWI	NOV 74	LMVE	F		
NECHES RIV MASTER		E E	FWD	MAR 6]	GCE	48		
B. A. STEINHAGEN	NECHES RIVER	CE	FND	FEE 63	DOE	AR.		
SAM RAYBURN	ANSELINA RIVER		FND	FEB 73		AF	JAN 97	
TRINITY RIV MASTER		CE	Fub	May 75	SWI	ţ.	34M 64	
BENBROCH	CLEAP FOA:	33	FHI	MAY 75				
DOE POOL	MOUNTAIN CREEK	ΞĬ	FWD	JAN 85				
RAY ROBERTS	ELM FOF	CE	FHI	Jan 85			AUC EF F	
LEWISVILLE	ELM FOR	CE	FNS	MAx 75	5#D	F	j <u>u</u> ∟ 44	
GRAFEUINE	BENTON EREEL	33	F#D	MAY 75	S≒Đ	F	AFF 8º	
E4404	EAST FOR:	E.E.	FWD	MAY 75	SHE	F	SEF 90	
NAVAFRO MILIS	PICHLAND CREEK	(E	FWE	JUL 64	QCE	ÁF	JUN EF F	
BARDWELL	WATCHACIE CREE!			JUL e5	ECE.	<del>A</del> F	EEB Bo E	
WALLISVILLS	TRINITY RIVER	£E	GE					
BUFFALO BAYOU MASTER		C.E	13					
BARTER	RUFFALD BAKOU		60	007 72	E LIT.	F		
ADDIENS	RUFFALD RAYDU	CE	GI.	OCT 72	SWD			
BRAIDE RIV MASTER		CE	FWD	MAR 73	SHE		JUN 90 R	
MHITNEY	rraios river	E <b>E</b>	FWD	MAY 75	SWD			
A301LLA	AUUILLA CRESE	£Ε	FWI	JUL 68	S₩D			
PROCTOR	LEON RIVER	CE	FND	APR 74	SWD			
BELTON	LEON RIVER	£E	FND	MAY 76	SWD			
STILLHOUSE HOLLOW	Lampasas River	CE	FND	FER 79	5 <b>#</b> D			
BEORGETOWN	N.F.SAN GABRIEL	EE	FWD	JUN BO	SMD		NOV 88 R	
GRANGER	SAN BABRIEL	CE	FND	NOVB2	SWD		DEC BS R	
WAC0	BOSQUE RIVER	ξE	FWI	AUG 73	5#0			
SOMERVILLE	YEGUA EREEK	EΕ	₽₩Ð	NOV 23	SWD	F		

#### ETATUE OF WATER CONTROL MANUALS IN SWI (Report Control Evabol DAEN-CME-16) Revised: January 1989

RESERVOIR	STREAM						THE . E.	٤ ١
COLORADO PIL MASTEP		CE	FWD					
HORDS CREEK	HORDS CREEK		FWD	MAY ST	GEE	ΔF		
O.C. FISHEF	N. CONCHA		FWD	DEC 61				
TRIN BUTTES (1)	S. DONOHO	98					ger ge	
MARSHALL FORD (1)	COLOFADO RIVER	BR	FWD	MAY 80			JAN 59	
GUADALUPE RIV MASTER		CE	FWD	JAN 66	95 <b>F</b>	ù¢		
CANTON	SUABALUPE FIVEF							
RIO BRANCE MUSTER		CĒ	A[:	FER 67	הרכ	t		
RICUIU	FIG [HaM4		έŪ	JUN 82				
100m111	FILE GRANDE	CE	AD	JUN 81			EEC 89	1.
ALISTED	GALISTED CREEK		ΑĐ				100 27	ν.
EMEZ CANYON	JEMEZ PIVER		AB	AUE 84	SMD			
EATORO (1)	CONEGES PIMER	EF	нŢ	MAY 64		F	JYN si	11
EIOS RIV MASTER		CE	AĐ.	NDV 77	S.ul-	<i>1</i> -0		
ANTA POSA	FECOS RIVER	CE	Aŭ	SEP 81				
DAMER (1)	PECOS RIVER		AL:	JUL 84		AR:	M6: 91	t:
WB RIMERS	FIG HENES	CE.	AD.	JUN 54			ני מוו	L
RANTLE: (1)	* FECOS FIVER	CE	AD	<b>55</b> C	511	•	3UN 89	
MAVAJO (1)	SAN JUAN RIVER	BF	<b>A</b> 5	JHN 76	or F	E	SEF <b>9</b> 0	11

#### NOTES:

(1) = Section 7 project, flood control regulation by EE.

AR = Approved, comments to be answered.

F = Expression =

FR = Published in Federal Register.

P = Plan.

R = Revision or answer to comments.

Re = Returned without approval.

U = Update of existing approved manual.

BRDA = Brand River Dam Authority.

WCID = Wichits County Water Improvement District.

LERA = Lower Colorado River Authority.

BR = Rureau of Reclamation.

# SOUTHWESTERN DIVISION SCHEDULE OF HIGH PRIORITY WATER CONTROL MANUALS FY 89 THRU FY 94

	:		DISTRICT		:
FY	: ALBUQUERQUE	:FORT WORTH	: GALVESTON	:LITTLE ROCK	:TULSA :
89	:	:GRANGER :GEORGETOHN :MARSHALL FORD :TWIN BUTTES	:	:	KEYSTONE : TORONTO : MCGEE CREEK :
90	: :		: AODICKS : BARKER : :	.WHITE RIVER MAS :L & D #13 :	PENSRCOLR
	:SUMNER : :	:TRINITY RIV MAS :BRAZOS RIV MAS :BENBROOK :LEWISVILLE :LAVON			HULAH ALTUS
-	:TRINIDAD	:WRIGHT PATMAN :SAM RAYBURN :PROCTOR :	: : : : :	:	KAH HUDSON FT GIBSON FOSS ELK CITY EUFAULA TÙM STEED
93	:	:LAKE O' PINES :NECHES RIV MAS :DAM B :	:		: TEXOMA : : DOLOGAH :
94	: : : :	:COLORADO MAS : : : :	: : :	:	:RED RIVER MAS : :THUNDERBIRD : :GREAT SALT : :FALL RIVER :

\*Revised Feb 1 1989

JANUARY 1989

# IABLE TV

# STATUS OF DROUGHT CONTINGENCY FLANS IN SWD

SCHEDULED COMFLETION DATE	AUGUST 1989	AUGUST 1989	DECFIRER 1990	JULY 1990	НАКСН 1996	AUGUST 1989	AUGUST 1989
UIST	1870 1870 1870 1870 1870 1870	A A A D I I A A D I I		7 11 11 11 11 11		1 T T T T T T T T T T T T T T T T T T T	2525
STREAM	WHITE RIVER WHITE RIVER WHITE RIVER WHITE RIVER PLACK RIVER LITTLE RED RIVER	FURGATORIE RIVER ARKANSAS RIVFR	WALNUT RIVER ARKANSAS RIVER SALT FORK AFK ARKANSAS RIVER POLECAT CREFK	VERDIGRIS RIVER FALL RIVER ELK RIVER BIG HILL CREEK	CANEY RIVER CANEY RIVER BIRD CREEN HOMINY CREEK	NEOSHO RIVER COTTONWOOD RIVER NEOSHO RIVER	NEOSHO RIVER Illinois fiver Foifau Riyfr
FASIN/FROJECT	WHITE RIV BASIN REAVER TABLE ROCK PULL SHOALS HOKFORK CLEARWAIER GREERS FERRY	UFFER ARKANSAS RIVER BASIN IRINIDAD JOHN MARTIN	MID-AKNANSAS RIVER RASIN EL DORADO NAW GREAT SALT FLAINS NEYSTONE HEYBURN	UFPER VERDIGRIS RIVER BASIN TORONTO FALL RIVER ELK CITY FEAKSON-SKURITZ-BIG HILL	LOWER VERDIGRIS RIVER BASIN FORAN HULAH PIRCH Shintonk NOLOGAH	UFFER NEOSHO RIVER RASIN COUNCIL SROVE MARION JOHN REPRONT	IDWER ARN RIVER RASIN FORT GIRSON TENKILLER FEFRY JISTER

<b>FASIN/FRUJECT</b>	STREAM	nist	SCHEDULED COMPLETION DATE
UPPER CANADIAN RIVER BASIN CONCHAS	CANADIAN RIVER	An An	MARCH 1990
LOWER CANADIAN RIVER BASIN OPTIMA FORT SUFFLY CANTON ARCADIA EUFAULA	N. CANADIAN RIVER WOLF CREEK N. CANADIAN RIVER DEEF FORK RIVER CANADIAN RIVER	91 91 91 91 91	JULY 1990
NAVIGATION PROJECTS NEWT GRAHAM: L&D 18 CHOUTEAU:L&D 17 WERRERS FALLS:L\D 16 F.S. NERR:L\D 15 W.D. MAYO'L\D 14	ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER	10 17 17 10 11 11 11	DECEMBER 1990
LOWER ARKANSAS RIVER BASIN BLUE MOUNTAIN NIMROD OZARK-JETA TAYLOR DARDANELLE NAVIGATION L&D'S(10)	FETIT JEAN FOURCHE LA FAVE ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER	LRP LRP LRP LRP LRP LRP LRP	MARCH 1990
UPPER RED RIVER BASIN TEXOMA Waurika	RETO RIVER BEAVER CREEN.	7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	August 1989
HID-RED RIVER BASIN FAT MAYSE SARDIS HUGO FINE CREEN BEONEN BOW	SANDERS CREEK JACKFORK CREEK KIAMICHI KIUFR LITTLE KIUFR HOUNTAIN FORK		JULY 1990
LITTLE FIVER PASIN REQUEEN GILLHAM GIEFNS MILLWOOD	ROLLING FORA COSSATOT RIVER SALINE RIVER LITTLE RIVER	4 6 7 4 8 7 4 8 7 4 8 7 4 8 7	NOVEMBER 1989

	STATUS OF DR	STATUS OF PROUGHT CONTINGENCY FLANS IN SWD	JANUARY 1989
BASIN/FROJECT	STREAM	pist	SCHEDULED COMPLETION DATE
LOWER RED RIVER BASIN COOPER WFIGHT FATMAN LAKE O'THE FINES	SULPHUR KIVER SULFHUR KIVER CYFRESS CREEN	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	AUGUST 1990
NECHES KIV BASIN R. A. STEINHAGEN Sam rayburn	NECHES RIVER Angelina River	<b>ጉሠ</b> ኒ <b>ጉሠ</b> ! <b>ጉሠ</b> !	FERRUARY 1991
TRINITY RIU BASIN BENBROOK JOE FOOL RAY ROBERTS LEWISVILLE GRAFEVINE LAVON HAVARRO MILLS	CLEAR FORK MOUNTAIN CREEK ELM FORK ELM FORK DENTON CREEK EAST FORK RICHLAND CREEK		AURUST 1989
ARAZOS KIV BASIN WHITNEY AGUILLA FROCTOR BELTON STILLHOUSE HOLLOW GEORGETOWN GRANGER WACO	PRAZOS RIVER AQUILLA CREEK LEON RIVER LEON RIVER LAMFASAS RIVER N.F.SAN GARRIEL SAN GABRIEL BUSOUE RIVER	44444444444444444444444444444444444444	MAY 1990
COLORADO RIV BASIN HORDS CREEK O.C. FISHER	HORDS CREEK N. CONCHO	FWT ក្រុង F មហ្គ	NOVEMBER 1990
GUADALUPE RIV PASIN (ANTON	GUADALUFE KTHER	FWD FWD	MAY 1991
BIO GRANDE RIVFE BASIN GRIOUIU GOCHIII BALISTEO TEMEZ CAHYON	FIO CHAMA RIO GRANDE GALISTEO CREEN JEHEZ RIVER	<b>4</b> 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	IANUARY 1990
TECOS RIU RASIN TANIA ROSA	PECNS RIVER	הף הף	FFREUARY 1990

SECTION V - REGULATION OF
MULTI-PURPOSE PROJECTS WITH HYDROPOWER

# SECTION V HYDROPOWER GENERATION AT SOUTHWESTERN DIVISION PROJECTS

The 17 Hydropower Projects are listed in Table 1. Generation by project for the last five fiscal years are shown in Table 2. Also, generation by the projects, since impoundment, is shown on the following graphs.


#### TABLE 1


				Total	
			No.	Capacity	11, 110.
<u>Projects</u>	<u>Basin</u>	Stream	<u>Units</u>	MW	No.
Beaver	White	White	2.	112	V – 1
Table Rock	White	White	4	<b>20</b> 0	V-2
Bull Shoals	White	White	8	<b>34</b> 0	<b>V</b> – 3
Norfork	White	North Fork	2	70	V - 4
Greers Ferry	White	Little Red	2	<b>9</b> 6	<b>V</b> -5
Keystone	Arkansas	Arkansas	2	<b>7</b> 0	A - C
Ft. Gibson	Arkansas	Grand	4	45	<b>V</b> - 7
Webbers Fallas	Arkansas	Arkansas	3	<b>6</b> 0	V - 8
Tenkiller Ferry	Arkansas	Illinois	2	34	<b>V</b> -9
Eufaula	Arkansas	S. Candian	3	90	V-10
R.S. Kerr	Arkansas	Arkansas	4	110	V-11
Ozark-Jeta Taylor	Arkansas	Arkansas	5	101	V-12
Dardanelle	Arkansas	Arkansas	4	124	V-13
Denison	Red	Red	2	70	V-14
Broken Bow	Red	Mountain Fork	2	100	V-15
Sam Rayburn	Neches	Angelina	2	52	V-16
Whitney	Brazos	Brazos	2	30	V-17

#### TABLE 2

## Fiscal Years (1,000 GWH)


Projects	<u>1984</u>	1985	<u>1986</u>	<u>1987</u>	<u>198</u> 8
Beaver	116.3	222.5	214.5	155.1	192.F
Table Rock	471.2	886.0	645.9	<b>43</b> 2.2	<b>63€</b> .3
Bull Shoals	697.1	1397.9	875.0	566.8	897.7
Norfork	209.7	396.1	214.7	126.5	223.9
Greers Ferry	158.3	315.8	148.9	105.7	<b>201</b> .8
Keystone	234.4	306.5	333.0	<b>500.9</b>	312.4
Ft. Gibson	203.6	321.8	294.9	286.7	201.5
Webbers Falls	190.3	320.7	350.9	286.9	197.8
Tenkiller Ferry	78.3	176.3	174.1	147.5	134.7
Eufaula	195.1	360.0	336.1	461.2	282.4
R.S. Kerr	526.5	750.7	725.8	772.9	536.3
Ozark-Jeta Taylor	193.2	437.1	488.0	341.1	334.6
Dardanelle	595.8	823.5	799.6	830.1	600.6
Denison	198.9	343.0	294.5	533.2	291.3
Broken Bow	139.5	229.6	147.4	93.9	142.4
Sam Rayburn	125.3	97.8	105.6	147.4	112.4
Whitney	15.0	57.1	50.8	109.9	17.5







ZZZ TOTAL GENERATION IN GWH

ZZ TOTAL GENERATION IN GWH







ZZ TOTAL GENERATION IN GWH




ZZZ TOTAL GENERATION IN GWH





ZZZ TOTAL GENERATION IN GWH







ZZZ TOTAL GENERATION IN GWH










ZZ TOTAL GENERATION IN GWH






ZZZ TOTAL GENERATION IN GWH





ZZZ TOTAL GENERATION IN GWH



PRINCE PROPERTY OF THE PROPERT

ZZ TOTAL GENERATION IN GWH 

SECTION VI - DISTRICT WATER CONTROL ACTIVITIES

## SECTION VI - DISTRICT WATER CONTROL ACTIVITIES

1.	PROJECT VISITATION BY WATER MANAGEMENT PERSONNEL	VI- 1
2.	SPECIAL RESERVOIR OPERATIONS	VI- 3
3.	WATER QUALITY PROGRAM AND ACTIVITIES	VI-14
4.	SEDIMENT PROGRAM AND ACTIVITIES	VI-20
5.	NAVIGATION ACTIVITIES	VI-22
6.	COOPERATIVE PROGRAMS	VI-24
7.	ANNUAL FLOOD DAMAGES, PER RIVER BASIN, PREVENTED BY BOTH CORPS AND SECTION 7 PROJECTS	VI-26
8.	ANNUAL FLOOD DAMAGES, BY STAGE, PREVENTED BY CORPS PROJECTS	VI-30
9.	ANNUAL FLOOD DAMAGES, BY STATE, PREVENTED BY CORPS SUPPORTED EMERGENCY OPERATIONS	VI-31
10.	HYDROPOWER PRODUCTION	VI-32
11.	LAKE ATTENDANCE	VI-33
12.	WATER SUPPLY STORAGE	VI-35

## 1. PROJECT VISITATION BY WATER MANAGEMENT PERSONNEL

- a. <u>ALBUQUERQUE</u> <u>DISTRICT</u>. During FY 88, Abiquiu, Brantley, Cochiti, Galisteo, Jemez Canyon, Navajo, Pueblo, Santa Rosa, Sumner, Trinidad, and Two Rivers projects were visited by Reservoir Regulation personnel.
- b. FORT WORTH DISTRICT. Seven of the twenty-four District reservoir projects were visited by Water Management personnel during Fiscal Year 1988. Canyon and Somerville Lakes were visited in October 1987, Benbrook Lake was visited in February 1988, Georgetown and Whitney Dams were visited in April 1988, Joe Pool and Waco Lakes were visited in May 1988, and Canyon Dam was revisited in September 1988 for inspection of non-federal hydropower facilities. Water Control Manuals, flood control and emergency operation procedures, gate operations and calibration. potential areas of flooding, shoreline and downstream erosion. impacts of project operations, and the Water Control Data System data collection and dissemination were discussed with project personnel during these visits. In addition the impacts of non-Federal hydropower operation were discussed with the Canyon Dam personnel.
- c. <u>GALVESTON</u> <u>DISTRICT</u>. On 7 October 1988, Hydrology and Hydraulics personnel visited the Addicks Project Office to discuss operational procedures and interrogate the Alert Base Station for dial-in capability problems with project personnel.
- d. <u>LITTLE ROCK DISTRICT</u>. During FY 88 nearly all reservoir control section personnel were able to visit either projects or other sites involved in real time water control operations.

The Section Chief and White River engineer spent two days at Clearwater Lake to tour the project and train Resident Office personnel. Appurtenant structures and recreational areas were seen as well as several downstream sites for a future tailwater DCP. Modifications to the emergency spillway and dam were observed while under construction and effects on project regulation were discussed. Resident Office personnel received training in basic inflow computations, use of the runoff index and shutdown criteria.

The Section Chief and two other reservoir control personnel viewed the low stages on the Mississippi and Arkansas Rivers this summer by helicopter. The flight originated in Memphis, Tennessee and took a course down the Mississippi River to the entrance channel then up the Arkansas River. Particular attention was paid to the low flow conditions and navigability in the entrance channel and the Arkansas River downstream of Lock and Dam 2.

Two reservoir control personnel accompanied streamgaging personnel on a trip to inspect the DCP and gaging equipment at the mouth of the White River (MW-5). Access to the gage was by river and necessitated lockage through Locks 2 and 1. The gage required

lowering due to the extremely low stages on the river this summer.

On another trip with streamgaging personnel the Blue Mountain project regulator was able to observe the installation of conduit for a tailwater gage, tour the project, meet with personnel and observe a gate change while in the gate tower.

The Arkansas River engineer also spent a day with streamgaging personnel at the Blue Mountain project. This trip was to observe work related to relocating the headwater gage during a summer fishery drawdown and enabled the engineer to tour the project as well. The Nimrod project was visited on this trip also.

On a trip to Bull Shoals dam the White River engineer was able to observe changing river conditions immediately downstream from the project due to hydropower releases. Downstream channel conditions were also observed at the confluence with the Norfork River and at Calico Rock, Arkansas.

Lock and Dam 7 was visited twice this year by reservoir control personnel. One visit was with streamgaging personnel to check the DCP installation and enabled the Arkansas River engineer to tour the control room, gate structure and visit with personnel. The other visit was by two reservoir control personnel to observe the lockage of military equipment enroute from Fort Chaffee, Arkansas to Camp Grayling, Michigan.

e. <u>TULSA DISTRICT</u>. Twenty-three project sites were visited by Reservoir Control Section personnel this fiscal year. The projects visited and purposes for the visits are listed in the following table.

# PROJECT VISITATION DURING FISCAL YEAR 1988

PROJECT PURPOSE OF VISIT

Altus Scheduled reservoir control visit.

Arcadia Site familiarization.

Big Hill Site familiarization.

Broken Bow Periodic Inspection.

Canton Scheduled reservoir control visit.

Council Grove Scheduled reservoir control visit.

Denison Periodic Inspection.

El Dorado Site familiarization.

Elk City Site familiarization.

Fall River Stilling Basin Inspection.

Fort Supply Scheduled reservoir control visit.

Foss Site familiarization.

Great Salt Plains Scheduled reservoir control visit.

Hudson Scheduled reservoir control visit.

John Redmond Scheduled reservoir control visit.

Kaw Scheduled reservoir control visit.

Marion Scheduled reservoir control visit.

Optima Scheduled reservoir control visit.

Pensacola Scheduled reservoir control visit.

Sanford Scheduled reservoir control visit.

Tom Steed Scheduled reservoir control visit.

Toronto Site familiarization.

Webbers Falls Site familiarization.

## 2. SPECIAL RESERVOIR OPERATIONS.

a. <u>ALBUQUERQUE DISTRICT</u>. The watersheds within Albuquerque District received well below normal snowmelt runoff in 1988. The Rio Grande Basin observed about 70 percent of normal. This ended a six year stretch of above normal runoff conditions.

Between Jan 88 and 31 Mar 88, 51,000 acre-feet of 1987 carryover storage were released from Cochiti Lake. At the end of Mar 88 there were approximately 73,000 acre-feet of carryover storage remaining. This was initially due to delays in the rehabilitation of the Rio Grande channel below El Paso, Texas, which was being completed by the International Boundary and Water Commission (IBWC). Storage was transferred from Cochiti to the flood control pool in Caballo Reservoir, which is administered by

IBWC, while the channel work was being completed. The Bureau of Reclamation, who is the project owner of Caballo, began noticing increased seepage and small sand boils below the dam in early March. They requested a delay in the Cochiti evacuation concurrent with the emergency evacuation of 48,000 acre-feet of Caballo storage. The remaining Cochiti storage, along with some snowmelt runoff water, was completely evacuated by 15 Jun 88.

Construction of the Abiquiu hydropower project continued in 1988. The conduit was closed from Dec 87 through Feb 88 to permit installation of a steel liner in the conduit. During this period, a flow of 50 cfs was pumped over the dam to meet downstream needs. The installation of the plenum chamber will start in mid Nov 88 and continue through Feb 89.

In Nov 87, Reservoir Regulation personnel participated with the Bureau of Reclamation's testing of the automatic operation of the spillway gates at Sumner Dam. The spillway gates open automatically when the flood space is 60 percent utilized resulting in a large increase in the release. The test showed that these gates open very rapidly and, therefore, every effort will be made to limit the pool elevation to avoid unregulated large changes in release.

On 6 Sep 88, the Bureau of Reclamation began the initial filling of the newly completed Brantley Dam and Reservoir. Brantley Dam consists of a central concrete gravity section with earth sections on either side for total length of about four Dam safety is the primary project purpose. Dam safety evaluations for McMillan and Avalon Dams on the Pecos River revealed inadequate spillway capacities for both. McMillan Reservoir is contained within the new reservoir area of Brantley and the dam will be breached in 1989. Avalon Dam is below Brantley and is used primarily as a diversion structure. Additional benefits from Brantley are derived from irrigation, flood control, fish and wildlife enhancement, and recreation. Initial storage allocations are: 2,000 acre-feet inactive, 40,000 acre-feet conservation, 189,700 acre-feet flood control, 617,800 acre-feet surcharge and 116,800 acre-feet sediment space.

In 1988 the staff of the Reservoir Regulation Group initiated the Rio Grande Reevaluation study. This 2-year study, as authorized by Congress, directed the Corps to take the lead in evaluating the operation of the Federal reservoirs in the Rio Grande Basin above Fort Quitman, Texas. The system will be studied to identify opportunities to provide flood protection and additional beneficial use of available water. A status report was distributed in Sep 88 with the final report being scheduled for completion in FY 89.

There were a total of 10 deviations in 1988. Aside from the major ones of which were discussed above, minor deviations assisted construction and maintenance activities, movie filming, and fish surveys.

b. <u>FORT WORTH DISTRICT</u>. Fiscal Year 1988 started out with most lake projects in very good condition. By mid January 1988 rainfall had caused several projects to enter the flood pool. Fourteen flood control projects out of twenty-four used part of their flood control storage at least once during the year. Heavy rainfall in the Brazos River basin caused all but Georgetown and Whitney Lakes to go into the flood pool at least twice. There were thirteen requests from the Fort Worth District to the Southwestern Division for deviations from the approved project plans of Southwestern regulation.

## (1) <u>Drought Operations</u>.

By mid-May many parts of the State of Texas were experiencing well below normal rainfall and the beginning of drought conditions. By the end of September yearly rainfall ranged from 68% of normal in the eastern part of the state to 75% of normal in the panhandle region. According to the Palmer Drought Index most divisions within Texas ranged from -2.0 to -2.7. Thus, most of the agricultural area of the state was considered to be in a moderate drought. Much of the eastern third of Texas was gripped in a drought that was causing barren pastures, scarce hay supplies, and lowered cash crop yields. By the end of September, the drought had crept westward to affect the south, southwestern, and west central counties of the state. Soil moisture conditions, however, were still reasonably adequate in far west Texas, the South Plains, the Rolling Plains, and the Panhandle.

Due to the perceived drought conditions and the prospect of the drought only being in the first year of unknown length, the Fort Worth District Water Management personnel undertook the task of preparing Drought Contingency Plans. After several meetings with the other districts in the Southwestern Division, a framework for the plans was adopted. The plans are being prepared by basin and/or sub-basin. The Drought Contingency Plans for the Fort Worth District river basins are scheduled to be completed by the end of 1990.

In May 1988, while much of the state was entering a drought, the Brazos River Authority was requesting large releases from Stillhouse Hollow Lake in order to prove up its Water Rights. A heavy local rainfall of 10+ inches of rain above Proctor Lake, located in the upper Brazos River Basin, caused the failure of a non-Corps lake and the water level at Proctor Lake to go into the flood pool. After several discussions the Brazos River Authority agreed to utilize the flood waters at Proctor Lake (rather than the Stillhouse Hollow conservation water) to meet downstream water needs. This arrangement lasted for approximately 4 weeks.

In mid-July 1988, a locally heavy thunderstorm caused Canyon Lake to go into the flood pool by 9 percent. Because of the perceived drought conditions the Fort Worth District Water

Management personnel, after coordination with downstream interests, requested a deviation from the Plan of Regulation so that the flood waters could be released at a rate that could be utilized by downstream users without waste for the next month.

## (2) Non-federal Hydropower.

On 18 November 1987 Canyon Lake had been lowered 8-feet below normal by the Guadalupe Blanco River Authority and the gates were closed. At this time construction was initiated to reline the conduit for non-federal hydropower facilities. Careful coordination by the Water Management personnel for the next five months of closure allowed the conduit to be relined, downstream slide gates with headwall to be installed, and takeout section with penstocks to be constructed. An inspection of the hydropower facilities was conducted in September 1988. Pressurization testing of the conduit and bypass system are scheduled for October and November 1988.

Construction of non-federal hydropower facilities is also underway at Town Bluff Dam on the Neches River. projected date of completion of construction is April 1989. the non-federal addition to hydropower facilities under construction at Canyon and Town Bluff, CESWF is also reviewing applications for other projects. License applications are under review for Lewisville, Ray Roberts, Wright Patman, and Lake O' the Pines. Lewisville is the most advanced with the City of Denton having contracted for design, specifications, and plans.

- c. <u>GALVESTON DISTRICT</u>. There were no special reservoir operations during FY 1988.
- d. <u>LITTLE ROCK DISTRICT</u>. During FY 88 the Little Rock District (LRD) experienced extremes in rainfall and project inflow amounts. The water year was characterized by above average rainfall amounts in the early winter months and below average amounts during most of the summer months in all of the river basins in LRD.

Special operations and activities related to water control projects are summarized as follows:

### (a) White River System

(1) In December 1987 basin rainfall amounts in excess of 4 to 5.5 inches above normal caused pool rises in the upper White River basin lakes of from 2 to 10 feet, with 6 feet at Greers Ferry and up to 22 feet at Clearwater Lake. Flood pools were evacuated in time for the second and last major event of the water year in late March and early April of 1988. Basin rainfall amounts of from 2 to 3 inches above normal during this time period produced pool rises of from 1 to 4 feet at all the White River lakes and 16 feet at Clearwater Lake. All flood pools in the upper White River basin lakes and at Greers Ferry were evacuated

by late April to mid May and have remained below their power pools since.

- (2) Beginning on 1 May a deviation was put into effect to assist the downstream farmers in planting and harvesting in the lower White River Valley. This deviation reduced the target operating stages at Newport and at Georgetown for the 1988 agricultural season, which is estimated to end on 1 December 1988. This deviation had no substantial effect on the flood control operations in the White River basin.
- (3) In July 1988, a drawdown at Greers Ferry was initiated at the request of the Arkansas Game and Fish Commission (AG&FC) to enhance the fisheries of the lake. Coordinated with the Southwestern Power Administration (SWPA), the drawdown was completed in mid August and will extend into FY 89 until the "first winter freeze".
- (4) There were seven additional deviations in the White River basin during FY 88. Four were at hydropower projects and involved the SWPA, two were at Clearwater to assist the AG&FC and a canoe race, and the other at Bull Shoals to assist in recovery of a drowning victim. Other special operations involved coordination of releases at Bull Shoals and Norfork for two canoe races on the White River.

## (b) Little River System

- (1) In November and December of 1987 the Little River system also experienced basin rainfall amounts above normal. Approximately 5.5 inches of rainfall above normal for both months produced average pool rises of from 2 to 15 feet with the largest rises of 21 and 32 feet occurring at DeQueen and Gillham Lakes, respectively. Other minor rises occurred in January and February of 1988 but, as in the White River basin, late March and early April brought rainfall amounts of 5 to 6 inches and caused pools to rise an average of 1 to 5 feet at all the lakes. In light of the drought conditions this summer the basin did experience another minor rise in July and August.
- (2) Drawdowns for the Arkansas Game and Fish Commission (AG&FC) to enhance fisheries were completed at DeQueen and Millwood Lakes early this past summer.
- (3) There were eight deviations in the Little River basin during FY 88. Three were for canoe races, four for maintenance to boat ramps and clearing of stumps in boating lanes and the last to increase minimum releases from Gillham Lake to prevent potential damage to water supply intake pumps in Millwood Lake.

### (c) Arkansas River System

(1) Flows on the Arkansas River were well above

normal during the same time periods that other basins in the Little Rock District (LRD) were receiving above normal basin rainfall amounts. These flows were more of a result from rainfall that occurred in the Tulsa District (TD) though. The flows that were experienced during December through January and March through April were two to three times above average. The trend quickly came to an end as rainfall amounts fell to 2 to 5 inches below monthly normals in Arkansas during March through August of 1988. A navigation emergency was declared in May and assistance was received from the upstream TD projects for a short time. addition to this deviation there were eight other deviations to raise pool limits to assist navigation and one to provide farmers irrigation During the summer months, water. maintaining navigation on the lower portions of the river was the primary As the Mississippi River receded to a record low at the Mouth of the White River (MW-5) to elevation 104.2 NGVD in early July the Corps had five dredges working to keep the entrance channel navigable. The system was kept open for all but two days.

- (2) At Blue Mountain and Nimrod Lakes the rainfall that occurred in November and December produced pool rises of from 1 to 5 feet with maximum rises of 17 to 18 feet, respectively. The events of late March and early April produced pool rises of from 2 to 7 feet.
- (3) Blue Mountain and Nimrod each had one deviation during FY 88. The deviation at Blue Mountain was for a drawdown for the Arkansas Game and Fish Commission (AG&FC) to enhance fisheries. It was started in June 1988 and completed in November 1988. The deviation at Nimrod was to provide releases for a water quality study that the Waterways Experiment Station (WES) was conducting.
- (2) Studies, reports and investigations related to water control projects are summarized as follows:
- Report published in 1984 recommended study of the seepage beneath Dike 1 which has existed since the initial pool filling operation in 1966. Supplement 1 to the Reconnaissance Report, completed in April of 1986, recommended that a cutoff wall be constructed through Dike 1. In January 1986 a deviation established the top of the flood control pool at elevation 1128.0 NGVD in lieu of 1130.0 NGVD, with the stipulation that water not be held above 1125.0 NGVD in excess of four days, to alleviate the problem and is still in effect. A Request for Technical Proposal was issued to prospective bidders for the cutoff wall in September of 1988. LRD plans to award a construction contract in April of 1989 with a two year construction period anticipated. Beaver Dam has been rated the highest priority dam safety problem in SWD.
- (b) White River Lakes Regulation Study. During the early part of FY 88 refinements were made to the candidate plan which was then again presented to the Resident Engineers for comments

regarding the plan's acceptability. The majority of the comments received dealt with the effects of the higher summer pool stages during the recreation season caused by the lower summer regulating stages. An on-board review was also held in February 1988 with these and additional comments, regarding effects on hydropower production and flood control operations, discussed. Further production runs were made to address these and other concerns. To date, a plan that attempts to address all concerns has been produced and is ready for presentation at the District level. Upon completion of this presentation the plan will be ready for Division review.

- Table Rock Dissolved Oxygen Study. The modeling of a (c) multilevel intake structure was completed by the Experiment Station (WES) in April 1988. Results ind Waterways Results indicate this structure would not achieve the target water quality desired. Therefore, WES has suggested a hypolimnetic oxygenation (hyp-ox) system be installed in the reservoir as a possible alternative measure for meeting the required temperature and dissolved oxygen WES (D.O.)standards. is currently studying the alternative alone and in combination with other alternatives such penstock oxygen injection and turbine venting to arrive at a solution which minimizes total costs and maximizes D.O. levels. Results will be presented in a report expected to be completed by December 1988. Funding used in FY88 was \$50,000. Funding for FY89 is \$250,000.
- The Clearwater Lake Spillway Adequacy Study in 1978 found that the spillway at Clearwater was inadequate to pass the maximum probable flood as it was defined at that time. Subsequent to that study a comprehensive analysis of the seepage through the left abutment was completed in 1981. In May 1986 a revised Reconnaissance Report was submitted to SWD and forwarded to OCE. The report recommended that the seepage be corrected using material excavated from the spillway area, thereby enlarging the spillway at the same time. Also recommended was the addition of a parapet wall along the crest of the dam. The seepage correction and the parapet wall were approved, but not the enlargement of the spillway beyond the seepage excavation requirement. Construction commenced in November 1986 and is approximately 60 percent complete as of September 1988. Construction should be completed by November 1989.
- (e) <u>Development of Norfork Unit Number 3</u> The Conway Corporation of Conway, Arkansas has submitted a proposal to the Southwestern Power Administration (SWPA) to become the sponsor for Federal construction of an additional unit at Norfork Dam. If selected, the Conway Corporation will provide financing for the design, construction and O&M&R of the project in exchange for a power allocation from SWPA. The Corps will be responsible for approving and performing the design, construction and operation of the project.
- (f) <u>The Arkansas River Basin Study</u> is a general investigation study. The cost-sharing agreement with the non-federal sponsors was completed in July 1987. The navigation

portion of the study will address the possible need for additional system storage or changes in system operating plans to reduce the magnitude and duration of flows which hamper navigation. The non-navigation feasibility studies will address the need for water supply, flood control, recreation and fish and wildlife in Oklahoma and Arkansas. An "Operational Plan Review Status Report" was completed in March 1988 and addressed three operating plans. The feasibility report is scheduled for completion in September 1990.

- (g) The Arkansas River Land Impact Study was initiated as a result of numerous complaints concerning the frequency and duration of flooding along the main stem of the Arkansas River. The study objective is to identify any lands where additional real estate acquisitions are required. The results investigations will be reported in a summary letter report and also in a Real Estate Design Memorandum Supplement for each pool where additional real estate actions are required. If, for a given pool, no real estate action is required, data supporting this finding will be forwarded for review in the form of a Hydrologic and Hydraulic Report. The study began in March 1986. The letter report is scheduled to be completed in September 1989. The Real Estate Design Memorandum Supplements are tentatively scheduled to be completed in 1991.
- (h) The Beaver Lake Water Quality Study (General Investigations Survey) is a one-year comprehensive study whose purpose is to identify measures to preserve and enhance the quality of the reservoir's water. The quality of the water in the lake has deteriorated due to pollution from both point and non-point sources. Efforts have already been made to reduce the amount of pollution entering the lake from point sources. However, the majority of the pollution is caused by non-point sources, which are more difficult to find and control. The project has been funded and work is in progress. The study report is scheduled to be completed by April 1989.
- (i) White River and Tributaries, Arkansas is a general investigation study of the impacts of Little Rock District reservoir operations on navigation in, and recreation activities on, the White River and its tributaries in Arkansas during low-water periods. It has been requested that water releases from the White River reservoirs be modified to augment flows for navigation and recreation. Many times in the summer and fall navigation on the White River is delayed. This increases shipping costs for agriculture and other commerce in the region. Recreational interests are concerned with the effects that low flows have on the trout fishery and the other recreational uses of the river. A reconnaissance report is scheduled for September 1989.
- (j) <u>Arkansas/White River Containment Structure</u>. A new channel is developing between the Arkansas and White Rivers. Should this new channel develop the sand laden flows from the

Arkansas River could be carried to the White River. This sediment would have to be dredged from the White River at an annual cost of approximately \$3.1 million. The construction of an extension to the containment structure along the White River Entrance Channel has been approved. The FDM was submitted in April 1988 and a construction contract is scheduled for award in April 1989. The construction is expected to be completed within two years after award of the contract. A fish and wildlife mitigation plan has been approved by the Corps of Engineers and the U.S. Fish and Wildlife Service.

- (k) Montgomery Point Lock and Dam (Lock and Dam 0). Low water levels in the Mississippi River at the mouth of the White River cause delays in navigation and increase dredging costs on the White River portion of the McClellan-Kerr Arkansas River Navigation System. Preliminary results received from the Waterways Experiment Station indicate that the only feasible solution is a new lock and dam. Additional testing has confirmed that the most economical location is in the White River channel at approximately mile 0.5. The present schedule calls for submission of a Justification Report in September 1990.
- (1)Wilbur D. Mills Dam (Dam No.2). This dam has a history of erosion of the riprap scour protection downstream of the stilling basin. During the December 1982 flood, improperly moored barges in Pool 2 were swept from their moorings and rendered 12 tainter gates inoperable or blocked. The resulting flow concentration caused extensive damage to the scour protection at Dam No. 2. These instances of erosion have required numerous intermittent repairs. Since the dam in constructed on piling. extensive scour could cause the structure to fail. Model studies by the Waterways Experiment Station have determined the most feasible solution is to extend the stilling basin by grouting riprap downstream from the stilling basin end sill. The grouted riprap will be placed by sinking used barges in the desired An FY 1990 construction start is planned contingent on location. approval and funding.
- Non-Federal Hydropower Development. A milestone was recently reached in the Little Rock District (LRD) with two of three 10 megawatt (MW) units at James W. Trimble Lock and Dam (No. 13) and one of two 19.5 MW units at Murray Lock and Dam (No. coming on-line. Licenses for non-federal hydropower development were issued and construction is approximately 99 percent complete at these projects on the Arkansas River. The units at Lock and Dam 13 can operate between 3,000 and 110,000 cubic feet per second (cfs) with a maximum release rate of 31,000 cfs. The units at Lock and Dam 7 can operate between 2,600 and 135,000 cfs with a maximum release rate of 38,600 cfs. Also on the Arkansas River, licenses have been issued at Arthur V. Ormond Lock and Dam (No. Lock and Dam No. 3, Wilbur D. Mills Dam (No. 2) and at Nimrod 9). Dam. continues to be responsible for reviewing preliminary permits and applications filed with the Federal Energy Regulatory Commission (FERC) for development of non-federal hydropower at Corps projects or non-Corps projects within the limits of LRD to

ascertain potential impacts on Corps responsibilities. The Corps also has the responsibility to review all designs, plans, and specifications for features which affect the integrity of the existing Federal structure or its operational adequacy.

- 3. Other significant items relating to water management activities are as follows:
- (a) <u>Water Control Data System (WCDS)</u>. Reservoir Control personnel are utilizing applications software developed by LRD to enter all daily reservoir data, perform water budget computations, and prepare daily reports and forecasts. (Data Collection Platform) data are currently being retrieved from the National Environmental Satellite, Data and Information Service (NESDIS) downlink. DCP data are being stored in the Data Storage System (DSS), a data base developed by the Hydrologic Engineering Center (HEC). Modifications continue to be made to the system to more fully utilize DCP data and, thereby, minimize the project reporting requirements for daily reservoir data. Additional software was developed to use DCP data directly from DSS in generating daily reports. The TOTAL data base was installed on the system last year and data is currently being stored in both TOTAL and DSS. Applications programs from HEC and modifications of those programs allow users to view, edit, and plot the data and to generate reports. Software has also been installed to graphically display rainfall data using programs developed by the Tulsa District.
- (b) <u>Data Collection Platform (DCP) Status</u>. The Little Rock District (LRD) currently has a total of 91 DCP stations with 36 located in the Arkansas River basin, 13 in the Little River basin and 42 in the White River basin. Of these, 33 are maintained by LRD. Application has been made for 3 new channel assignments which will bring the total number of DCP stations to 94 in the near future. LRD also monitors 20 DCF stations located outside the district as a secondary user. During FY 88, time slots vacated by the Fort Worth, Galveston and Tulsa Districts on the GOES western satellite were filled by LRD resulting in all DCP data currently being received on two channels (7 and 41).
- (c) <u>Automation of Field Operations and Services</u> (AFOS). LRD is currently receiving AFOS system data from the National Weather Service (NWS) Tulsa River Forecast Center through a line that also provides data to the Tulsa District and SWD. Selected products are routed to the TOTAL data base and to a printer, while others can be viewed with the VUENWS program. Current software has been added to allow utilization of AFOS graphics products as well.

### e. <u>TULSA DISTRICT</u>.

(1) ARKANSAS RIVER BASIN. Flows in the Arkansas River during

The variation of flows FY 1988 were about 140% of normal. throughout the year was much more pronounced than the normal seasonal variation. Flows for the months of December 1987 through April 1988 were about 310% of normal while the flows from June through September 1988 were only 20% of normal. Because of the abrupt change in early May, from flooding conditions to a prolonged drought, it became necessary for the Division Commander, for the first time, to declare a navigation emergency. declaration was necessary to allow the conservation pools, in some of the storage reservoirs, to be drawn below the limits set forth in the Arkansas River Master Manual to provide the flows needed to keep the navigation system open until maintenance dredging could be completed. The reservoirs used to provide the needed flows were Kaw, Keystone, Oologah, Hulah, Copan, Tenkiller and Eufaula.

Keystone Lake was drawn to elevation 718.5 (top conservation pool at elevation 723.0) in September for tainter gate repair work. The seasonal drawdown scheduled for July at Kaw Lake was foregone due to the drought conditions and to assure that water will be available during January 1989 to help replenish the depleted Keystone conservation storage.

Special releases were made at Eufaula and Fort Gibson in July, August, and September, and at Great Salt Plains and Oologah Lakes in August and September to alleviate fish kill problems. The Kansas Water Office requested water supply releases from John Redmond for the Wolf Creek Nuclear Generating Plant in June, August, and September, and from Council Grove Lake for the City of Emporia in August and September. Oklahoma City requested water supply releases from Canton Lake in July. Annual raft races for various organizations required special releases from Council Grove, Robert S. Kerr. W. D. Mayo, and Keystone Lakes.

(2) <u>RED RIVER BASIN</u>. Flows in the Red River basin during FY 1988 were about 140 percent of normal upstream and 50 percent of normal downstream of Lake Texoma, while annual rainfall was about 70 percent of normal upstream and 60 percent of normal downstream of Lake Texoma. On an annual average, above normal inflows during the winter months generally more than offset below normal inflows during the summer months.

Only one significant flood event occurred during FY 1988 This flood resulted from rains that fell from December 24-27, 1987. The heaviest rainfall was downstream of Lake Texoma, in the lower Red River basin. Rainfall totals during this storm ranged from about 2 1/2 inches at Lake Texoma to about 8 inches in the extreme southeastern part of the Tulsa District. Rainfall totals in southwestern Arkansas ranged from about 5 to 14 inches for this period. Although this was not a major flood, it did result in the third highest pool elevation at Broken Bow and the sixth highest pool elevation at Hugo.

The last half of FY 1988 was very dry. Rainfall was much below normal in many areas in the Red River basin below Lake Texoma. Pool elevations at the end of FY 1988, however, were not

extremely low. Conservation storages ranged from 87 percent full at Broken Bow to 100 percent full at Pine Creek. Lake Texoma reached a low of 612.03 (75 percent of conservation storage remaining) on 16 September 1988, but rose about 4 feet by the end of September as a result of rainfall from the remnants of Hurricane Gilbert.

Several significant events occurred this FY in the Red River basin. The Lake Texoma Advisory Committee was formed and had meetings on 20 January and 24 May 1988. The conservation storage at McGee Creek filled for the first time on 19 February 1988. Also, a Drought Contingency Plan (DCP) was begun for the upper Red River basin (above Lake Texoma). The DCP is scheduled for completion by 31 December 1988.

## 3. WATER QUALITY PROGRAM AND ACTIVITIES.

a. <u>ALBUQUERQUE DISTRICT</u>. The goals of the Albuquerque District water quality data collection program are to provide an accurate picture of lake conditions as to pH, turbidity, temperature, and dissolved oxygen. Trends are monitored to show improvement or degradation of water quality and the data used to identify public health, fish and wildlife problems.

Readings are made on a monthly basis for the following parameters: surface pH, conductivity secchi disk, and dissolved oxygen and temperature at the surface and at one-meter increments to the bottom.

This data is available in the District Operations Office. The following is a listing of sampling locations for each project:

## WATER QUALITY SAMPLING LOCATIONS

PROJECT	LOCATIONS	NUMBER
Abiquiu	Chama inflow, Canones inflow, reservoir near dam, release	4
Cochiti	Bland canyon, reservoir near dam, release	3
Conchas	Conchas and Canadian inflow, reservoir	4
John Martin	Arkansas inflow, reservoir near boat ramp, reservoir near dam, reservoir near Ft. Lyon Hospital, two Lake Hasty locations, release	7
Trinidad	Purgatoire inflow, reservoir near dam, reservoir near Carpios Ridge	4
Jemez Canyon	Inflow, reservoir near dam	2
Santa Rosa	Pecos inflow, reservoir near dam, reservoir near asphalt pit, release	4

Biological samples are tested monthly at all projects. District personnel are trained in the use of a gas chromatograph to test for dissolved nitrogen.

### b. FORT WORTH DISTRICT.

- (1) For FY 1988, a water quality report for Lake O' the Pines was completed and submitted to SWD for reviews and approval. Of the 24 projects in the Fort Worth District, water quality reports for 15 projects have been completed and submitted to-date. Water quality reports for Waco, Whitney, Belton, Bardwell, Wright Patman and Lake O' The Pines are still pending approval by SWD. No major water quality problems of any significance have been found in any of these projects.
- (2) The City of Grapevine installed a destratification system at Grapevine Lake in April 1987 but has not yet determined the effectiveness of the system. At one time during the summer of 1988, a concentration level of dissolved manganese, more than minimum allowable limit was observed. The City is investigating why the higher levels of dissolved manganese occurred following the installation of the destratification system.
- (3) Canyon Lake was selected by WES as a research field site for developing techniques by evaluating the impacts associated with lake releases before and after hydropower installation. An intensive water quality data collection for this research project was initiated in the summer of 1988 (prior to power-on-line) and will continue through the summer of 1989 (after power-on-line).
- (4) Water quality surveillance at SWF for FY 1989 is \$248,590, compared to \$212,350 for FY 1988 and, therefore, an increase of \$36,240. The increase is associated with additional water quality sampling sites at Ray Roberts Lake and an increase in the cost of sampling.
- c. <u>GALVESTON</u> <u>DISTRICT</u>. There were no Water Quality Activities during FY 1988.
- d. <u>LITTLE ROCK DISTRICT</u>. The District water quality management programs are divided between the Construction-Operations Division and Engineering Division by functional missions.
- (1) <u>Construction-Operations Division Responsibilities.</u> The Permits Branch has responsibility for conducting the District water quality program for Construction-Operations Division. Since the regulatory functions of the branch under the Section 10/404 permit program closely parallel functions of the Division's water

quality management program, field activities are very conveniently and efficiently combined to implement the programs. These responsibilities include the following programs relating to water

- (a) Reservoir Monitoring. General reservoir water quality monitoring of all Little Rock District reservoirs other than the main stem of the Arkansas River is presently performed three times per year at six to eight stations per lake at various depths. Sample collection in the field and water quality analyses done by USGS personnel under the Corps of Engineers Interagency Agreement. Approximately 26 parameters are measured to ascertain general reservoir water quality and to provide background data in detecting water pollution. There are no State or other Federal programs which routinely provide these data on reservoirs operated by the Corps. Data obtained are maintained in the Permits Branch and are stored in and available from STORET, WATSTORE, and annual USGS Water Resources Data Publications for Arkansas and Missouri. Data obtained are used to evaluate basic water quality and long and short term water quality changes, to identify pollution sources, and to properly manage reservoir water quality. Their evaluations include identification of potential pollution sources so as to enable the Corps to have meaningful input in the decision making processes of other agencies and groups with regulatory authority over basin These findings are published in Water Quality discharges. Management Reports and annual updates for each project. Greers Ferry and Table Rock Water Quality Management Reports have been published and the Blue Mountain report is in progress. A statistical analysis has been performed on data collection thus far (1974-present) and has proved to be very valuable. Bottom sediment samples were collected from eight LRD reservoirs in 1984 and have been analyzed for organics, nutrients, and metals. This program is conducted pursuant to ER 1130-2-334.
- Monitoring. Discharge permit and operational monitoring of 34 Corps-operated wastewater treatment systems in the District is performed in accordance with National Pollutant Discharge Elimination System (NPDES) permit requirements. The USGS obtains the necessary monthly samples and analyzes these for Biochemical Oxygen Demand (BOD), bacteria, and suspended solids. Operational monitoring performed twice weekly by the sewage treatment plant operators includes in some cases pH, flow, chlorine residual, dissolved oxygen, and settleability. Operational changes are recommended as necessary. Data are formatted and computer stored in Permits Branch. This program is conducted in accordance with Section 402 of the Clean Water Act which requires reporting to the Department of Natural Resources in Missouri and the Department of Pollution Control and Ecology in Arkansas.
- (c) <u>Bathing Beach Monitoring</u>. Monitoring is performed five times monthly by resident area personnel on District bathing beaches during the swimming season to insure safe bacterial quality of reservoir waters. Samples are analyzed by the Missouri and Arkansas Health Departments free of charge. A central log containing results for all projects is maintained by the Permits and Water Quality Section. This program is

administered in accordance with SWD Regulation 1130-2-9 and applicable State laws.

- (d) Potable Water Monitoring. Potable water supplies of the District are tested for physical, chemical, and bacterial quality. Samples are collected by resident area personnel and mailed to the appropriate health departments, which perform the analyses free of charge. When tests indicate a bacterial problem, corrective measures are immediately taken. In some cases chronic problems detected by this sampling causes wells to be replaced or reworked. Permits Branch personnel collect samples for complete chemical analysis by the health departments on each new water supply and for periodic nitrate analysis thereafter. Data obtained are used in the periodic sanitary survey and report forwarded to SWD for reporting to OCE. program is conducted in accordance with ER 1130-2-407 and applicable Federal and State drinking water standards for noncommunity water supply systems.
- Periodically, a bottom sediment survey is performed at twelve locations along the Arkansas River navigation project and less frequently at other locations on other District rivers and reservoirs. Sediment and water column samples are frozen and sent to SWD laboratory for sediment, water, and elutriate analyses. The purpose of this program is to detect potential effects of dredging operations on water quality, and to have these data available for the required 404(b)(1) evaluations of future Corps and private dredging. These operations include both commercial dredging under Corps permits and channel maintenance dredging performed under Corps of Engineers contract.
- Substances. Permits Branch and Resident Offices receive calls reporting instances of pollution and hazardous substance spills. These reports are coordinated with the appropriate Federal and State officials. On occasion, Corps personnel investigate these pollution complaints to verify existing conditions and determine effects on project operations. During oil and other hazardous substance spills, Corps personnel participate in notification and other emergency measures with Coast Guard and EPA officials and when so designated, act as the Federal on-scene coordinator for these two agencies under the National Contingency Plan. The LRD Oil and Hazardous Substances Pollution-Contingency and Spill Prevention, Containment and Countermeasure Plan was rewritten and updated as of August 1983.
- (g) <u>Special Activities</u>. Permits Branch periodically assists Engineering Division and Planning Division in obtaining samples and analyses for special water quality and planning studies. Coordination is also accomplished on studies being performed by other agencies such as the EPA, Health Department, Soil Conservation Service, etc. Cooperative water quality studies are periodically conducted with other agencies in monitoring activities authorized under Corps Section 10 and 404

- permits. Permits Branch personnel are also involved on a daily basis with personnel from the Arkansas Department of Pollution Control and Ecology in the processing of Corps permits and resolving the water quality matters arising therein.
- (2) <u>Engineering Division Responsibilities</u>. There is no specific organization for water quality studies within the Engineering Division. Responsibility is assigned to the various elements based on the nature of the program study.
- (a) Reservoir <u>Profile</u> and Release Monitoring. Water quality data have been collected at Beaver, Table Rock, Bull Shoals, Norfork, and Greers Ferry Lakes since 1966; at Blue Mountain, Clearwater, and Nimrod Lakes since FY 81; and at DeQueen, Dierks, Gillham and Millwood Lakes since April 1981. Presently, monthly profiles of pH, temperature, dissolved and specific conductance are obtained from the 12 reservoirs, as well as a gravel sample below each dam. Additional profiles are obtained from Table Rock Lake during critical times of the year. These data are used in the design of the operating features needed for preventing or lessening water quality problems downstream of the dams. They also contribute to the water control management of releases from Table Rock and to maintain acceptable temperatures downstream of all reservoir projects from May through October. Hydraulics Branch is responsible for this program and data collection is contracted to USGS.
- (b) <u>Special Studies</u>. The Hydraulics Branch in conjunction with the Planning Division, periodically conduct water quality studies as part of normal project planning efforts such as preparation of survey reports, design memorandums, and environmental impact statements.
- (3) <u>Laboratory Capabilities</u>. Water quality analysis performed at the District level are limited to the following capabilities:
- (a) Field testing of water quality which may be conducted by the Corps personnel includes dissolved oxygen, temperature, pH, specific conductivity, Secchi Disc measurements, and others using HACH field test kits approved by EPA.
- (b) A small laboratory located in Construction-Operations Division can perform the following analyses: dissolved oxygen, color, turbidity, alkalinity, hardness, and others using colorimetric methods of analyses.
- data collected and analyzed by USGS are entered into WATSTORE and STORET, the computerized data management systems of the USGS and EPA, respectively. These data are also published in the annual USGS water resources reports for Arkansas and Missouri. Results of potable water, bathing beaches, NPDES, and other monitoring are kept in computer storage, log books, or files as appropriate. Special data collection results are contained in the reports

dealing with the specific subject for which data were collected.

- e. <u>TULSA</u> <u>DISTRICT</u>. Environmental Resources Branch performed several water quality studies during FY 1988.
- Lake Texoma Netpen Aquaculture Demonstration Project. Environmental Resources Branch continued to collect data at Lake Texoma for determining the effects of netpen aquaculture of channel catfish on lake water quality. Data were collected biweekly during the fish growing season. Activities included field measurements, laboratory analysis of water and sediment samples for a number of physicochemical parameters, sediment trap experiments, and determinations of in-situ sediment oxygen demand. The study is a three-year project to be completed during FY 1989. Results of the study will be summarized in a final report and will provide a basis for a computer model capable of predicting water quality based on varying conditions of facility hydrodynamics, morphometry, and existing water quality.
- (2) Release Plans for the Prevention of Fish Kills. Environmental Resources Branch, in cooperation with Operations and Engineering/Construction Divisions, developed release plans for minimization of summertime fish kills at several Tulsa District projects. Activities included computer modeling and evaluation of test releases at these projects. As a result of these activities, no major fish kills occurred in the Tulsa District during the summer of 1988. Similar plans for all Tulsa District projects will be developed at a rate of approximately five per fiscal year.
- Methodology. A field device for determination of <u>in-situ</u> SOD was developed by the Environmental Resources Branch. The device is a dome-shaped apparatus that isolates and circulates water over lake or river sediments. SOD rates are determined by monitoring oxygen depletion rates within the dome. While the device was developed primarily for use in the netpen study at Lake Texoma, it should prove valuable in a number of water quality studies at other projects.
- (4) <u>M&I</u> <u>Water Suitability Studies</u>. Eleven potential reservoir sites in the Arkansas River basin were evaluated regarding their potential for municipal and industrial (M&I) water supply. Water quality data from the general vicinity of each site were retrieved via the Environmental Protection Agency's STORET computerized database.
- (5) <u>Tenkiller Lake</u>, <u>OK</u>. Environmental Resources Branch completed a final report on results of water quality sampling at Tenkiller Lake, Oklahoma. This study was initiated in response to growing public concern about eutrophication of Tenkiller Lake. The investigation revealed significant problems with nutrient inputs, decreased water clarity, and nuisance algal blooms. Further studies at Tenkiller Lake are planned for FY 1989.
  - (6) Releases of 50 cubic feet per second (cfs) were made

through one of the flood conduits at Denison Dam-Lake Texoma from 5 August 1988 through 5 October 1988 to alleviate a low dissolved oxygen problem in the stilling basin. Also, a special release of 140 cfs was made through the spillway sluice gate at Broken Bow on 21 and 22 August 1988. This release was made at the request of the Oklahoma Department of Wildlife Conservation to aid them in developing a trout fishery below Broken Bow Dam. A special release was made from Waurika in May and June to alleviate fish kill problems in the stilling basin.

#### 4. SEDIMENT PROGRAM AND ACTIVITIES.

- a. <u>ALBUQUERQUE</u> <u>DISTRICT</u>. A sediment survey (aerial) of Two Rivers Reservoir was completed this year. The new area-capacity table will be ready for adoption by 1 Jan 89. The sedimentation survey report is scheduled to be completed in 1989.
- b. <u>FORT WORTH DISTRICT</u>. Following the sedimentation resurvey of Stillhouse Hollow Lake in December 1987, a sedimentation resurvey report of Stillhouse Hollow Lake was completed and submitted to SWD in October 1988 for review and approval. For FY 1989, no projects in the Fort Worth District are scheduled for resurvey as funds requested for sedimentation resurveys in FY 1989 were not approved.
- c. <u>GALVESTON DISTRICT</u>. A sediment policy was established in 1985 by the District to provide guidance relative to settling basins or alternative control methods on inflowing streams to reduce velocity and essentially preclude the permanent deposition of sediment in the federally-owned lands of Addicks and Barker Reservoirs. Enforcement of this policy continues, there have been no other sediment activities in FY 88. Dredging activities for FY 87 and FY 88 are shown in the following Table.

# GALVESTON DISTRICT - DREDGING NAVIGATION PROJECTS (Cubic Yards)

Project	<u>FY</u> <u>87</u>	<u>FY 88</u>
Brazos Island Harbor	1,169,359	
Channel to Port Bolivar	36,289	
Corpus Christi Ship Channel	2,481,588	<b>* 6,117,053</b>
Freeport Harbor	1,300,305	1,687,918
Galveston Harbor & Channel	675,549	
Houston Ship Channel	4,502,058	<b>*</b> 272,800
Matagorda Ship Channel	2,464,282	2,625,072
Sabine - Neches Waterway	6,719,213	* 3,165,031
Mouth of the Colorado River		<b>*</b> 522,000
Trinity River and Tributaries	<b>395,62</b> 8	172,886
Texas City Channel	948,267	122,764
Double Bayou	<u>331,227</u>	
SUBTOTALS	21,023,765	14,685,524
GIWW		
Sabine River to Galveston	324,372	797,042
Galveston to Corpus Christi	7,247,974	2,485,795

 Corpus Christi to Mexican Border
 3,531,662
 1,792,204

 SUBTOTALS
 11,104,008
 5,075,041

TOTALS 32,127,773 19,760,565

\* Preliminary data subject to revision.

#### d. LITTLE ROCK DISTRICT.

- (1) <u>Summary of Activities</u>. Suspended sediment samples are collected at 16 stations. The 247 sediment ranges on the main stem of the Arkansas River are re-surveyed as near annually as funds and survey workload permit. From October 1987 through September 1988, there were 185 ranges scheduled for resurveying; no resurveys were accomplished. There are 143 ranges scheduled to be resurveyed in FY 89. 56 tributary ranges are resurveyed less frequently when appreciable deposits are suspected. About 50 index ranges out of 350 sediment ranges in the other 8 reservoirs are resurveyed at 10-year intervals. During the period from October 1987 through September 1988, none were resurveyed. Index ranges are scheduled to be resurveyed at 12 reservoirs during FY 89.
- White River Entrance Channel Model. The entrance channel model is a physical, movable bed, hydraulic model which has been constructed at the Waterways Experiment Station (WES) to study the navigation depth problems which occur on the White River between its confluence with the Mississippi River and Lock and Dam This reach of the White River serves as the entrance to No. 1. the Arkansas River Navigation System. Design of the model began in November 1981 and construction was completed in September 1983. Adjustments and verification tests were completed in September 1983. Tests with additional contraction works were completed in August 1984. A sediment trap plan was tested but did not provide an acceptable navigation channel. Tests diverting Arkansas River flow into the entrance channel have been completed. This improved the navigation channel but did not provide a reliable channel. Tests of a lock and dam at White River Mile 0.5 were initiated in 1985. The tests indicate that the lock and dam will improve navigation for the low flow, low stage periods. Studies are underway to determine the economic feasibility of a solution.
- (3) Channel Maintenance. Maintenance dredging to maintain navigable depths amounted to approximately 5.8 million cubic yards in FY 88. For the river system this was an overall increase of about 2.0 million cubic yards from the FY 87 dredging requirements. Dredging was performed in Pools 2 and 3 and the White River Entrance Channel (WREC). Approximately 1.2 million cubic yards were dredged in the Arkansas River, 96 percent of which was from Pool 2, and approximately 4.6 million cubic yards in the WREC. Approximately 1.2 million cubic yards was dredged in the WREC during the low water season from October through December 1987 and 3.4 million cubic yards was dredged during the drought from May through September 1988. Shoals downstream of Lock Numbers 3, 4, 5, 7, 8, and 13 and at the Benzol Bridge (Navigation Mile 7.6) were removed by the Corps-operated Arkansas River Fleet

with two clam dredges operated by the Resident Offices. Approximately ten groundings exceeding one hour each occurred on the navigation system in FY 88.

e. <u>TULSA DISTRICT</u>. During FY 1988, a detailed reconnaissance resurvey was conducted on Elk City Lake, Kansas, and a contract was awarded to perform a detailed resurvey of Keystone Lake, Oklahoma, of all sediment ranges in the lake and 18 of the 26 degradation ranges. This resurvey is being performed due to the results of the unexpectedly high sediment deposition that was detected from the FY 1987 reconnaissance resurvey. The new hydrographic survey system installed on the survey vessel TD 8504 was installed in March 1988 and ongoing revisions to the software are currently being made by the manufacturer. This effort should be completed within the next 6 weeks.

Sediment forecasting is still a major effort to be performed, but due to other work priorities this effort has been stalled. Sediment estimates are now being computed for small reservoirs with drainage areas of about 10 square miles. New procedures for evaluating these reservoirs are being developed. The transfer of data from the Honeywell computer at the Division Office to the Tulsa District Harris computer is going to extend into late FY 1989. Suspended sediment samples were collected by the U. S. Geological Survey at 39 sites.

During FY 1988, hydrographic surveys were conducted on Stillhouse Hollow Lake, Texas, for Fort Worth District and on Pennington Creek (an arm of Lake Texoma) near Tishomingo, Oklahoma. Sediment data was collected and processed in the upper Little Arkansas River for the Survey Report and Environmental Impact Statements. A contract was awarded and completed to process the results of the sediment survey of Hugo Lake, Oklahoma. This effort presented positive results and another contract has been awarded for similar data processing for Kaw Lake, Oklahoma.

- 5. NAVIGATION ACTIVITIES.
- a. ALBUQUERQUE DISTRICT. N/A
- b. FORT WORTH DISTRICT. N/A
- c. GALVESTON DISTRICT. Consolidated statement of tonnage handled by ports and moving on the Gulf Intracoastal Waterway is shown in the following table for calendar years 1985 and 1986.

		(SHORT CALENDAR YEAR 1985	TONS) CALENDAR YEAR 1986
1.	Brownsville, Texas	1,442,790	1,212,743
2.	Port Isabel, Texas	279,578	291,713
3.	Corpus Christi, Texas (6*)	41,057,313	50,104,579
4.	Freeport, Texas (35*)	12,918,289	13,370,117
5.	Galveston, Texas	7,791,729	7,987,857

<ol> <li>Houston, Texas (3*)</li> <li>Texas City, Texas (13*)</li> <li>Sabine Pass Harbor, Texas</li> </ol>	90,669,169 33,440,917 547,160	101,659,064 35,479,909 385,202
9. Port Arthur, Texas (26*)	15,754,931	18,879,546
10. Beaumont, Texas (19*)	26,842,008	27,453,660
11. Orange, Texas	648,350	661,570
12. Port Lavaca-Point Comfort	4,365,748	4,858,515
13. Anahuac, Texas	52,859	48,662
	52,639	40,002
14. Clear Creek, Texas		
15. Channel to Liberty, Texas	58,486	43,930
16. Double Bayou, Texas	20,845	14,145
17. Cedar Bayou, Texas	218,608	275,900
18. Colorado River, Texas	480,181	571,818
19. Sweeny, Texas	519,417	324,528
20. Palacios, Texas	10,116	
21. Dickinson, Texas	194,932	330,172
22. Aransas Pass, Texas	9,649	293,681
23. Port Mansfield, Texas	204,007	3,883
24. Harlingen, Texas	692,170	668,733
25. Channel to Victoria, Texas	3,414,087	3,078,476
26. Chocolate Bayou, Texas	4,076,999	2,874,357
27. Johnsons Bayou	<b>248,959</b>	<u>329,759</u>
ATOT	L 245,959,297	271,202,514
Gulf Intracoastal Waterway, Texas: (Traffic on Waterway)		
Sec. 1. (Sabine River to Galveston)	42,443,030	47,401,050
Sec. 2. (Galveston to Corpus Christi		23,809,550
Sec. 3. (Corpus Christi to Mexican		1,723,040
TOTA	L (1) 67,509,304	72,933,640
(*National Post Posting - 1096)	(1) Include	- duplications

(\*National Port Ranking - 1986)

(1) Includes duplications.

d. <u>LITTLE ROCK DISTRICT</u>. Record low stages on the Mississippi River during the drought this past summer caused extremely low stages on the White River Entrance Channel (WREC). In June, a grounded tow blocked the WREC causing the channel to be closed for two days. Upon reopening, tows were restricted to 70 feet wide by 600 feet long (including towboat) and restricted to daylight usage with a Corps of Engineers escort boat. The tow size and draft restrictions remained in effect through the end of September. For approximately one week during June a minimum draft restriction of 7 feet was imposed.

Projections indicate that about 8.0 million tons of commerce will be moved on the McClellan-Kerr Arkansas River Navigation System in CY 88. This represents a decrease of 10 percent from the CY 87 level. Commodities moved consisted of iron and steel, chemicals and chemical fertilizers, petroleum products, coal, sand and gravel, rock, soybeans, wheat and other grains, and miscellaneous commodities. Inbound movements are predicted to decrease by 2 percent and outbound movements to decrease by 11 percent.

e. <u>TULSA DISTRICT</u>. Commercial movements in Oklahoma for FY 1988 were within one percent of the tonnages moved in FY 1987. Navigation conditions were far from ideal with high flows occurring in the winter and spring months followed abruptly by the drought of the summer. Wheat, chemical fertilizer, iron and steel, and petroleum products are the leading commodities shipped. Movements of military equipment have increased steadily. The following table provides the total tonnage for both the Little Rock and Tulsa Districts.

## MCCLELLAN-KERR ARKANSAS RIVER NAVIGATION SYSTEM (Total Tonnage Little Rock and Tulsa Districts)

	1987 * (Tons)	1988 ** (Tons)
Inbound Outbound Internal Through	2,131,022 3,348,218 2,751,562 <u>654,637</u>	2,096,000 2,980,000 2,352,000 <u>572,000</u>
Totals	8,885,439	8,000,000

<sup>\*</sup> Unofficial figures

#### 6. <u>COOPERATIVE PROGRAMS</u>.

#### a. <u>ALBUQUERQUE DISTRICT.</u>

- 1. <u>National Weather Service</u>. Albuquerque District does not have a cooperative program with the National Weather Service to support rainfall gages.
- 2. <u>U.S. Geological Survey.</u> The cooperative stream gaging program with the U.S. Geological Survey covered 44 stations in FY 88. Total program cost was \$200,870, as shown in Table VI-7. The following is a summary of number of stations by river basin.

#### STATION SUMMARY

#### STATIONS

BASIN	STREAM	RESERVOIR	TOTAL
Arkansas	5	2	7
Canadian	3	2	5
Rio Grande	11	8	19
Pecos	9	4	13

Note: 6 gages are not associated with project operation.

#### b. FORT WORTH DISTRICT.

<sup>\*\*</sup> Projected figures

#### (1) National Weather Service.

Funds were transferred by CESWF to the NWS in the amount of \$89,519 for FY 1988. Under ongoing programs, the Corps collects rainfall at project offices while the NWS collects all other rainfall reports and maintains weather stations, including those at Corps' projects. Rainfall summaries are transmitted to the Corps via telephone and a daily computer printed map which displays current totals for reporting stations. supplemental and accumulative storm total printouts are provided upon request. Additional hydrometeorological information was received from the NWS via AFOS. Radar scans were obtained on a Kavouras radar acquisition access and display terminal via a direct connection to the NWS Stephenville radar site (which covers the geographic where the majority of the District's projects concentrated) and via commercial long-distance telephone into NWS radar sites at Galveston, Hondo, and Brownsville, Texas, and into Oklahoma City, Oklahoma. Continuous updates are possible during storm periods.

#### (2) <u>U. S. Geological Survey</u>.

#### a. <u>General</u>.

The USGS performed, maintained, and operated all streamflow, lake level, and some water quality stations in cooperation with the Fort Worth District. They arranged for reporting at river stages during flood events, made supplemental flow measurements, and processed all published data. In addition to the cooperative streamgaging program the USGS under memorandum of agreement provide operation and maintenance service to the Fort Worth District Data Collection Platform network.

#### b. Funds.

The Fort Worth District transferred to the USGS, for the Cooperative Streamgaging Program, \$663,460 for FY 1988 to support 135 gages as shown in Table VI-8

#### c. GALVESTON DISTRICT.

- (1) National Weather Service The cooperative program with the NWS provides for the operation and maintenance of precipitation gages and for the transmission of rainfall summaries via teletype circuits. The total program cost for FY 1988 was \$6,972 as shown in Table VI-9. The total program cost for FY 1989 will be \$7,126.
- (2) <u>U. S. Geological Survey</u> Two cooperative programs are currently in existence with the USGS. One provides the operation and maintenance of stream gages and the second provides the operation and minor maintenance for Data Collection Platforms. The total program cost for FY 1988 was \$159,230. The total program cost for FY 1989 will be \$165,770.total program cost for

d. <u>LITTLE ROCK DISTRICT</u>. Approximately 202 rainfall and/or river stage reporting stations were operated by the National Weather Service and the Corps of Engineers in or near the Little Rock District. Of these, 117 stations are in the Corps of Engineers/National Weather Service program. The remaining 85 stations are operated solely by the National Weather Service within or near the Little Rock District. Six of these stations are airway stations that report at 6-hour intervals. Reports from these stations are used in forecasting streamflows for flood warnings and operation of reservoir projects. The FY 88 total cost for this program was \$37,340. The FY 89 cost is projected to be approximately \$39,000.

#### (2) U.S. Geological Survey

The streamgaging data required by the District is collected under a cooperative agreement with the USGS. During the fiscal year 110 stations were operated. Of these, 74 were operated cooperatively and 36 were operated by the Corps of Engineers. The FY88 total cost for collection of streamflow and sediment data was \$531,850 of which \$393,870 was transferred to the USGS as shown in Table VI-10. The FY89 cooperative program cost is \$562,050 of which \$398,340 will be transferred to USGS.

#### e. <u>TULSA</u> <u>DISTRICT</u>.

- (1) <u>National Weather Service</u>. Real-time water control and investigation and design of our water resources projects requires the measurement and reporting of rainfall and evaporation data. These data are provided through a cooperative program with the National Weather Service. During FY 1988, the rainfall and evaporation program in the Tulsa District cost \$131,023 through transfer of funds to the National Weather Service.
- (2) <u>U.S. Geological Survey</u>. Much of the information required for water control, hydrologic investigation, and design of water resources projects results from the reporting and measurement of flow, water quality, and sediment provided by a cooperative stream gaging program with the USGS. During FY 1988, this cooperative program included 196 stations, six of which were operated independently by the Corps of Engineers. The stream gaging program in the Tulsa District cost \$1,862,433 in FY 1988 with \$980,740 of this being transferred to the USGS for operation of stations and data publications as shown in Table VI-11. The total CE/USGS program cost for FY 1989 will be \$1,058,680.

## 7. ANNUAL FLOOD DAMAGES PER RIVER BASIN PREVENTED BY BOTH CORPS AND SECTION 7 PROJECTS

a. <u>ALBUQUERQUE</u> <u>DISTRICT</u>. The following is a listing of damages prevented by Corps and Section 7 reservoir projects during FY88. Total damages prevented in FY 88 are \$2,000.

<u>Damages Prevented in Thousands of Dollars</u>

Basin	<u>Project</u>	FY 88 Damages <u>Prevented</u>	Cumulative Benefits <u>Through FY 88</u>
Arkansas	John Martin	0	87,609
	Pueblo	0	2,852
	Trinidad	0	0
Canadian	Conchas	0	81
Rio Grande	Abiquiu	2	229,340
	Cochiti	0	249,834
	Galisteo	0	O
	Jemez Canyon	0	10,639
	Platoro	0	4,508
	Rio Grande Fldw.	536	44,011
	Alb. Div. Channel	20,990	77,774
	Santa Rosa	0	?
	Sumner	0	O
	Two Rivers	O	6,862
	Brantley	0	Ci
San Juan	Navajo	<u>0</u>	<u>50</u>
	TOTAL	21,528	713,567

b. <u>FORT WORTH DISTRICT</u>. Annual flood damages prevented by river basin and project for both Corps' and Section 7 lakes are shown in Table VI-I. The table presents the damages prevented for both FY 1988 and cumulative through FY 1988.

#### TABLE VI-I

#### FLOOD DAMAGES PREVENTED BY PROJECTS FISCAL YEAR 1988

PROJECT	FY88 DAMAGES PREVENTED (in \$1,000's)	CUMULATIVE BENEFITS THROUGH FY88 (in \$1,000's)
BRAZOS RIVER BASIN		
Aquilla	\$ 0.0	<b>\$ 1,234</b> .0
Belton	462.2	118,597.7
Georgetown	4.1	4,610.2
Granger	68.1	14,484.2
Proctor	1,011.9	8,733.3
Somerville	0.0	32,194.0
Stillhouse	54.7	25,360.9
Waco	0.0	60,053.9
Whitney	0.0	<u>134,777.0</u>
Subtotal	\$1,601.0	\$400,045.2
COLORADO RIVER BASIN		
Hords Creek	\$0.0	\$ 937.0
O. C. Fisher	0.0	2,375.6
Subtotal	<b>\$</b> 0.0	\$ 3,312.6

GUADALUPE-SAN ANTONIO RIVER Canyon San Antonio	<u>BASIN</u> \$0.0 <u>0.0</u>	\$ 58,878.3 117,514.0
Subtotal	\$0.0	117,514.9 \$176,393.2
NECHES RIVER BASIN Sam Rayburn Subtotal	\$ <u>2,761.3</u> \$2,761.3	\$ <u>130,255.7</u> \$ 130,255.7
RED RIVER BASIN Lake O' The Pines Wright Patman Subtotal	\$ 497.6 162.4 \$ 660.0	\$ 6,636.0 13,859.4 \$ 20,495.4
TRINITY RIVER BASIN  Bardwell  Benbrook 1/ Big Fossil  Grapevine 2/ Joe Pool Lavon Navarro Mills Subtotal	\$ 0.0 0.0 0.0 481.9 0.0 0.0 0.0 \$ 481.9	\$ 9,112.7 51,449.4 6,322.8 943,202.2 1,764.8 91,035.1 27,732.0 \$1,130,619.0
Grand Total	\$5,504.2	\$1,861,121.1
COLORADO RIVER BASIN 3/ Marshall Ford Twin Buttes Subtotal	\$ 522.2 -0.0 \$ 522.2	\$191,415.6 418.6 \$191,835.6
Grand Total	\$6,026.4	\$2,052,954.7

- 1/ Includes Fort Worth Floodway System
- 2/ Includes Lewisville and Dallas Floodway System
- 3/ Built by Bureau of Reclamation but under Corps Corps Flood Control Jurisdiction

c. <u>GALVESTON</u> <u>DISTRICT</u>. Damages prevented for river and stream projects were impacted by the near drought conditions of FY 1988. There were no flood damages prevented in Galveston District during FY 88. The cumulative total of flood damages prevented at the Addicks and Barker projects is \$161,754,000. The cumulative total of flood damages prevented for all Corps projects in the District is \$828,266,000.

	Flood Damages Total for <u>FY 88</u>	Prevented (\$000) Cumulative <u>Total</u>
Addicks and Barker 1/	0	161,754
Brays Bayou	0	208,677
White Oak Bayou	0	20,917
Lavaca-Navidad Rivers	0	637

Tranquitas Creek	0	5,333
San Diego Creek	O	2,908
Texas City, Texas (Hurricane-Flood)	0	10,614
Torado River, Matagorda	0	844
Galveston Seawall	0	400,000
Vince Bayou	0	2,582
Port Arthur (Hurricane-Flood)	0	6,000
Freeport (Hurricane-Flood and	0	8,000
Tide Gate)		
Nueces River (Three Rivers)	<u>O</u>	<u>O</u>
Total	0	828,266

#### 1/ Piney Point Gage-Flood Stage 50.0 feet (NGVD).

a. <u>LITTLE ROCK DISTRICT</u>. The annual flood damages prevented by river basins during FY 88 in the Little Rock District are shown in the following table and amount to \$19,081,000.

<u>Basin</u>	FY 88 Damages <u>Prevented</u>	Cumulative <u>Through FY 1988</u>
Arkansas River	\$ 5,933,000	\$315,575,000
White River	12,635,000	342,918,000
Little River	<u>523,000</u>	<u> 19,353,000</u>
TOTALS FY 88	\$ 19,081,000	\$677,836,000

e. <u>TULSA DISTRICT</u>. Flood damages prevented by the Tulsa District Lakes in the Arkansas and Red River Basins during FY 1988 are shown in the following table and amount to \$142,144,000.

		CUMULATIVE
ARKANSAS RIVER BASIN	<u>FY 1988</u>	THROUGH FY 1988
Arcadia		1,065,000
Big Hill	<b>66,0</b> 00	441,000
Birch	1,576,000	8,878,000
Canton	275,000	8,346,000
Cheney	228,000	14,164,000
Copan	11,394,000	104,985,000
Council Grove	305,000	17,757,000
El Dorado	897,000	15,235,000
Elk City	4,780,000	55,587,000
Eufaula	11,209,000	71,014,000
Fall River	3,421,090	42,686,000
Fort Gibson	2,542,000	46,852,000
Fort Supply	3,000	3,169,000
Great Salt Plains	2,194,000	39,641,000
Heyburn	234,000	7,681,000
Hulah	20,746,000	220.025,000
Iola	1,520,000	<b>14,197,</b> 000
John Redmond	5,921,000	86,739,000

Jenks Kaw Keystone Marion Markham Ferry Norman Oolagah Optima Pensacola Sanford Skiatook Tenkiller Toronto Tulsa & West Tulsa Wister	318,000 9,913,000 15,580,000 1,545,000 580,000 990,000 11,988,000 2,196,000  7,197,000 2,642,000 4,949,000 2,826,000 9,005,000	2,618,000 266,449,000 410,194,000 37,689,000 8,513,000 12,516,000 93,304,000 11,000 49,384,000 162,000 39,201,000 17,953,000 43,092,000 261,372,000 84,877,000
Total Arkansas Basin	137,038,000	2,085,785,000
RED RIVER BASIN		
Altus Arbuckle Broken Denison Fort Cobb Foss Hugo Lake Kemp Mountain Park Pat Mayse Pine Creek Sardis Waurika	966,000  203,000 85,000 46,000 22,000 357,000 20,000 134,000 1,206,000 977,000 1,090,000	4,729,000 452,000 15,737,000 64,581,000 733,000 2,811,000 8,286,000 3,170,000 619,000 4,325,000 12,860,000 6,599,000 22,275,000
Total Red River Basin	5,106,000	147,178,000
Grand Total	142,144,000	2,232,963,000

# 8. ANNUAL FLOOD DAMAGES BY STATE PREVENTED BY CORPS PROJECTS

#### a. <u>ALBUQUERQUE DISTRICT</u>

State In Thousands of Dollars
Colorado 0

New Mexico Kansas

\* 21,528 0

Damages Prevented

- \* Primarily the Albuquerque North Diversion channel (Local Protection Project)
- b. <u>FORT WORTH DISTRICT</u>. Flood damages prevented by Corps projects during FY 1988 in the state of Texas were \$6,026,400.

- c. <u>GALVESTON DISTRICT</u>. There were no flood damages prevented by Corps projects in the state of Texas during FY 1988.
- d. <u>LITTLE ROCK DISTRICT</u>. The annual flood damages prevented in each state served by the Little Rock District during FY 88 is shown in the following table:

State FY 88 Damages
Prevented

#### Arkansas

Levees, Arkansas River (Little Rock District)	\$ 5,345,000
Reservoirs, Arkansas River (Little Rock District)	578,000
Levees, White River (Little Rock District)	2,493,000
Reservoirs, White River (Little Rock District)	8,874,000
Reservoirs, Little River (Little Rock District)	523,000

Arkansas Total \$ 17,813,000

#### <u>Missouri</u>

Levees, White River (Little Rock District)	2,000
Reservoirs, White River (Little Rock District)	1,266,000
Missouri Total	1,268,000

TOTAL DAMAGES PREVENTED FOR FY 88

\$ 19,081,000

- e. TULSA DISTRICT. Annual flood damages prevented in FY 88 by Corps projects in FY 1988 for the state of Kansas amounted to \$16,712,000; for Oklahoma, \$109,979,999; for Arkansas, \$15,542,000; and for Texas, \$219,000.
- 9. ANNUAL FLOOD DAMAGES BY STATE PREVENTED BY CORPS SUPPORTED EMERGENCY OPERATIONS.
  - a. ALBUQUERQUE DISTRICT. None
  - b. FORT WORTH DISTRICT. None
  - c. GALVESTON DISTRICT. None
- d. LITTLE ROCK DISTRICT. The flood damages prevented in FY88 by Emergency Operations occurred primarily over the Christmas holiday weekend along the Arkansas River and upper Black River basins. Little Rock District (LRD) received widespread heavy rains of over 10 inches in many locations which caused severe flash flooding and localized high water in most streams along the Arkansas River and upper Black River basins. LRD assisted the city of Shannon Hills in preventing 7 homes from being flooded in the vicinity of the Otter Creek Channel Improvement Project. Hydraulics, Emergency Management and Navigation Branch personnel monitored flood threats, notified navigation interests, coordinated with levee officials, and coordinated with state and local emergency officials and analyzed flood damages throughout the holiday weekend. Contact was maintained with the Tulsa

District concerning releases into the Arkansas River and its effects on localized flooding. Timely decisions were made and damages were minimized. Field Office personnel from Clearwater Lake monitored the rising Black River in the vicinity of Poplar Bluff, Missouri and patrolled critical areas. The North Inter-River Levees were watched for possible problems. No pumping operations had to be conducted since crops had been harvested. There were no appreciable cost savings in Missouri. Flood damages prevented in Arkansas are as follows:

Location	Description	Damages Prevented
Arkansas River	Loose barge rescued	\$50,000 (barge) \$100,000 (lock)
City of Shannon Hills	7 homes protected by sandbag operations	\$140,000
Arkansas River	navigation warnings	\$100,000
Total Damages Prev	ented	<b>\$3</b> 90,000
Total Cost of Emer	gency Operations	\$2,470

e. <u>TULSA DISTRICT</u>. Not available.

#### 10. HYDROPOWER PRODUCTION.

- a. ALBUQUERQUE DISTRICT. N/A.
- b. <u>FORT WORTH DISTRICT</u>. Hydropower production by project for Fiscal Years 1984 through 1988 is shown in Table VI-2.

TABLE VI-2

Project	Gross Generation (MWH)	Fiscal <u>Year</u>
Sam Rayburn	110,577 147,319 106,726 97,971 125,477	1988 1987 1986 1985 1964
Whitney	18,152 110,216 51,900 57,529 14,364	1988 1987 1986 1985 1984

#### c. <u>GALVESTON DISTRICT</u>. N/A

d. <u>LITTLE ROCK DISTRICT</u>. The annual hydropower production at LRD plants in total GWH by fiscal year is shown in the following tabulation.

Project	<u>1984</u>	<u>1985</u>	<u> 1986</u>	<u> 1987</u>	<u>1988</u>
Beaver Table Rock Bull Shoals Norfork Greers Ferry Ozark Dardanelle	117.8 473.5 702.5 211.1 160.0 195.9 599.0	224.1 888.3 1402.9 397.3 317.3 439.9 826.9	215.8 648.2 880.5 215.9 150.6 490.6 802.8	156.6 434.7 572.2 127.8 106.9 343.9 833.3	192.4 636.3 897.2 223.9 201.8 334.6 601.8
Totals(GWH)	2459.8	4496.7	3404.4	2575.4	3088.0

e. <u>TULSA DISTRICT</u>. Hydropower generation at Tulsa District projects for FY 1984 through 1988 is shown in the following tabulation.

#### HYDROPOWER PRODUCTION FOR TULSA DISTRICT PROJECTS

#### NET ANNUAL GENERATION (GWH)

PROJECT	FY	FY	FY	FY	FY
	1984	1 <u>985</u>	<u>1986</u>	<u>1987</u>	<u>1988</u>
Denison	199	3 <b>43</b>	295	533	193
Broken Bow	140	230	147	88	107
Sub-Total	339	573	442	621	300
Keystone Fort Gibson Webbers Falls Tenkiller Ferry Eufaula Robert S. Kerr	234	307	333	501	180
	204	322	295	288	138
	190	321	351	287	103
	78	176	172	148	75
	195	360	336	461	198
	<u>526</u>	<u>751</u>	<u>726</u>	773	<u>371</u>
Sub-Total	1,427	2,237	2,213	2,458	1,065
Total	1,776	2,810	2,655	3,079	1,365

#### 11. LAKE ATTENDANCE.

a. <u>ALBUQUERQUE DISTRICT</u>. The following is a listing of attendance at Corps and Section 7 projects in the Albuquerque District.

#### Project Attendance in Thousands

<u>Year</u>

<u>Project</u> 1984 1985 1986 1987 1988

Abiquiu	331.9	331.9	571.4	406.5	512.3
Cochiti	519.5	716.6	978.1	819.7	867.2
Conchas	331.9	449.7	586.7	408.8	<b>6</b> 25.0
Galisteo	5.1	7.6	8.3	5.8	5.9
Jemez Canyon	44.9	51.0	53.5	53.3	58.9
John Martin	698.9	742.5	702.9	1,012.7	754.3
Santa Rosa	240.8	248.2	233.3	191.6	156.1
Trinidad	164.9	275.4	274.3	282.1	395.9
Two Rivers	11.6	62.7	17.6	13.2	11.3
Pueblo	906.8	1,335.4	1,509.1	1,476.5	1,365.1
Platoro	21.5	17.4	13.2	8.4	8.8
Sumner	137.7	129.7	138.3	95.5	106.2
Navajo	485.1	486.2	527.6	417.0	<b>*479.0</b>

#### \* Estimate

b. <u>FORT WORTH DISTRICT</u>. Lake attendance for both the Fort Worth District Corps' lakes and the Section 7 lakes is presented in Table VI-3. The attendance is presented for the period FY 1984 through FY 1988.

TABLE VI-3

PROJECT	ATTENDANCE	TN	THOUSAND
11000101	TILL TOUR OF	T 14	THOUGHT

PROJECT	<u>1984</u>	<u> 1985</u>	<u>1986</u>	<u>1987</u>	<u>1985</u>
Aquilla Bardwell Belton Benbrook Canyon Georgetown Granger Crapevine Hords Creek Joe Pool	26.6 974.8 2,355.3 3,083.4 2,327.0 889.4 256.1 4,932.2 805.9	100.4 984.7 2,307.5 2,504.1 2,316.8 1,064.7 322.1 4,315.3 578.0	104.1 769.6 2.504.1 2,584.6 2,429.2 970.5 325.6 4,077.7 437.0	105.0 780.0 2,600.0 2,700.0 2.000.0 800.0 340.0 4,200.0 450.0	106.1 801.0 2,701.0 2,570.0 2,170.0 950.0 350.0 4,450.0 600.0
Lake O' The Pines Lavon Lewisville Navarro Mills O. C. Fisher Proctor Ray Roberts Sam Rayburn Somerville Stillhouse Town Bluff Waco Whitney Wright Patman Marshall Ford Twin Buttes	3,116.1 3,121.1 6,482.0 1,371.0 1,328.9 916.1  3,094.3 2,057.8 987.3 627.9 4,683.3 2,056.1 2,220.9	2,392.2 4,072.5 5,752.4 1,540.5 787.3 962.7  3,258.3 1,639.8 915.2 707.7 4,599.9 2,249.7 2,320.3 NOT NOT	2,434.8 3,652.9 7,204.3 1,319.5 534.7 928.2  3,319.6 1,380.0 1,206.3 589.2 4,891.2 2,350.2 3,072.6 AVAILABLE AVAILABLE	2,400.0 3,700.0 7,300.0 1,400.0 940.0 1.0 3,400.0 1,400.0 1,300.0 600.0 4,900.0 3,400.0 3,100.0	2,750.0 3,950.0 6,990.0 1,450.0 610.0 965.0 2.0 3,550.0 1,460.0 1,250.0 625.0 4,875.0 2,750.0 2,990.0

#### c. GALVESTON DISTRICT. N/A

d. <u>LITTLE ROCK DISTRICT</u>. Annual lake attendance at all LRD projects in visitor days by calendar year is shown in the following table:

1984 - 42,137,000 1985 - 42,700,000 1986 - 44,128,000 1987 - 47,000,000 1988 - 49,500,000 (estimated) \*

- \* equals 187,720,749 visitor hours (as now being reported)
- e. <u>TULSA DISTRICT</u>. Lake attendance figures for calendar years 1984 through August 1988 are tabulated in Table VI-4. Official visitation figures have recently been converted to a visitor hour basis (estimated number of hours spent by all visitors to the project). 1984 and 1985 figures are shown in recreation days (estimated number of persons visiting the project for any length of time). 1986 figures are shown in both visitor hours and recreation days of use, and 1987 and 1988 figures are shown in the visitor hours only.

#### 12. WATER SUPPLY STORAGE.

a. <u>ALBUQUERQUE DISTRICT</u>. Cochiti, Galisteo, Jemez Canyon and Two Rivers projects do not have storage allocated for water supply. The following table is a listing of reservoirs with space allocated.

#### Storage in Thousands of Acre-Feet

Project	Storage <u>Allocated</u>	Amount Contracted	Number of Contact	Water St	pplied FY 88
Conchas John Martin Santa Rosa Trinidad Abiquiu	254 345 200 20 20	0 0 0 0 170.9	0 0 0 0	40.1 149.1 31.0 17.8	32.7 213.1 57.8 35.3 0

b. <u>FORT WORTH DISTRICT</u>. Water supply information by project is shown in Table VI-5

#### TABLE VI-5

				Water
	Storage	Storage	Number	Supplied
	${\tt Contracted}$	Allocated	Contracted	In FY 88
Project Name	(AC-FT)	(AC-FT)	(USERS)	(AC-FT)

Aquilla Lake	33,600	52,480	1	2,400
B. A. Steinhagen Lake	1/	1/	1	1,944,200
Bardwell Lake	21,400	42,800	1	4,100
Belton Lake	372,700	372,700	2	55,200
Benbrook Lake	23,708 2/	23,708 2/	1	4,800
Canyon Lake	366,400	366,400	1	104,500
Georgetown Lake	101	29,200	1	6,700
Granger Lake	0	<b>37,9</b> 00	1	0
Grapevine Lake	161,250	161,250	3	36,300
<ul> <li>Hords Creek Lake</li> </ul>	5,780	5,780	1	360
Joe Pool Lake	0	142,900	1	310
Lake O' The Pines	250,000	250,000	1	12,900
Lavon Lake	220,000	220,000 3/	1	101,100
Lewisville Lake	436,000	436,000	2	155,800
Navarro Mills Lake	53,200	53,200	1	7,000
O.C. Fisher Lake	80,400	80,400	1	10,500
Proctor Lake	31,400	31,400	1	12,300
Ray Roberts	749,200	749,200	2	0
Sam Rayburn Reservoir	43,000 1/	43,000	2	0
Somerville Lake	143,900	143,900	1	15,600
Stillhouse Hollow Lake	204,900	204,900	1	66,310
Waco Lake	104,100	104,100	2	23,700
Whitney Lake	50,000	50,000	1	1,700
Wright Patman Lake	91,263	91,263	1	36,400

- 1/ LNVA is permitted to withdraw from B. A. Steinhagen lake not to exceed 2,000 c.f.s. This lake acts as a reregulation dam to Sam Rayburn Reservoir.
- 2/ Remaining 48,792 ac-ft of navigation storage is in the process of being negotiated with water user.
- 3/ NTMWD has given assurances for an additional 160,000 ac-ft of storage in Lavon Lake.
- c. GALVESTON DISTRICT. N/A
- d. <u>LITTLE ROCK DISTRICT</u> Water supply allocations, contracts and usages for FY87 and FY88 are shown by project in the following table:

	Amount of Storage Allocated	Amount of Storage Contracted	Number of		Supplied -Ft)
Project	(AC-Ft)	(AC-Ft)	<u>Contracts</u>	<u>FY87</u>	<u>FY88</u>
Beaver	117,000	40,000	2	31,165	34,084
Norfork	2,400	2,400	1	2,430	2,624
Greers Ferry	3,215	1,125	3	1,856	1,870
Nimrod	33	33	1	92	87
DeQueen	17,900	0	0	0	0
Gillham	20,600	123	1	661	627
Dierks	10,100	190	1	246	254
Millwood	150,000	32,828	1	53,944	54,187

e. <u>TULSA DISTRICT</u>. Storage allocated to water supply totals 3,840,240 acre-feet in the Tulsa District. The Corps has 2,115,220 acre-feet in 30 projects while the Section 7 projects totaled 1,725,020 acre-feet in 11 projects. The following table (V-6) is a project listing showing water supply storage, yield, amount contracted, number of contracts (existing and pending), and usage.

TABLE VI-4
TUISA DISTRICT
ATTENDANCE AT CORPS OF ENCINEERS
PROJECTS (IN THOUSANDS)

	7001	3000	1086	1086	1987	1988*
PROJECT	1984	nac, davs	nec. davs	Visitor bours	Visitor hours	Visitor hours
Creat Salt Dlains	297.4			6059.2	7204.0	5263.0
Fort Simply	898.7	860.5	729.5	4295.4	8903.0	7361.0
Canton	2738.1	2625.0	2706.1	24764.0	33595.0	29102.0
Halah	428.7	357.7	337.8	1634.3	3818.0	1214.0
Tenkiller	2065.1	2182.0	2379.1	42435.4	49419.0	46979.0
Wister	971.1	838.2	771.6	7752.6	10785.0	15314.0
Kevstone	2627.3	3262.6	3240.9	6399.9	14634.0	10065.0
Colorah	3003.4	2837.1	2300.0	23031.6	21436.0	18888.0
Fort Gibson	3881.8	4933.9	4493.7	62783.8	77190.0	43647.0
Fall River	209.7	192.5	228.3	2797.1	2241.0	2154.0
Toronto	145.6	161.9	197.2	4357.0	3511.0	3162.0
Elk City	253.1	281.2	280.2	7886.3	3508.0	2392.0
Contima	178.1	141.1	131.4	421.2	346.0	195.0
Dat Mayse	370.1	386.8	456.9	3753.9	3768.0	2223.0
Fifaila	4162.5	4607.3	4154.5	57851.1	70942.0	60647.0
Hevhairm	275.0	280.2	269.8	1847.4	1893.0	2238.0
Hydro	937.3	917.2	846.4	4472.0	5746.0	3470.0
The scritter	8342.3	8683.5	8479.1	141609.5	179969.0	107550.0
Wanrika	850.3	829.6	843.3	4495.3	5163.0	10936.0
Tohn Bedmand	313.5	242.0	296.2	1654.4	1915.0	1350.0
Comeil Grove	512.0	473.9	473.2	7801.4	8769.0	8599.0
Broken Bow	861.0	949.2	906.3	25638.7	26556.0	17462.0
Marion	235,3	325.1	317.0	5280.9	5793.0	4292.0
Pine Creek	847.9	849.7	983.7	11949.7	7285.0	4038.0
Robert S. Kerr	1042.9	1031.6	1128.2	5807.4	6382.0	5272.0
W.D. Mayor I.A.D	221.0	197.1	244.0	9.068	975.0	688.0
Charteau I&D	421.6	373.3	348.4	3160.4	3915.0	2811.0
Newt Graham I&D	458.6	338.8	239.1	2347.6	2423.0	2114.0
Webbers Falls	942.5	1111.4	917.1	13530.2	12502.0	8635.0
Birch	343.1	241.6	246.6	1535.1	1414.0	1127.0
Kaw	1051.0	1139.0	1317.9	586.4	5599.0	11322.0
Big Hill	431.4	472.4	396.2	2047.2	2096.0	5479.0
Sardis	311.9	316.1	310.3	2215.3	1586.0	5443.0
El Dorado	503.1	525.3	772.6	958.2	7678.0	7564.0
Copan	214.4	209.4	213.8	1051.4	1873.0	203.0
Skiatook			408.8	4321.7	4097.0	3876.0
DISTRICT TOTAL	41330.0	43503.3	42390.2	509923.6	604829.0	464511.0
*Total for January through September	ry through S	eptember 1988.				

VI-3637a

TABLE VI - 6

# WATER SUPPLY STORAGE

# Corps of Engineers Projects (October 1988)

			(conser 1300)			Page	Page 1 of 3
	STORAGE ALLOCATED TO	ESTIMATED	AMOUNT	ao dadwin		AMOUNT SUPPLIED	UPPLIED
PROJECT	WALLER SUPPLE	MGD	AF	일	PENDING	FY 87	FY 88
ARKANSAS RIVER BASIN	BASIN						
ARCADIA	23090	H	23090	т	0	0	2247
PEARSON—SKUBITZ BIG HILL	25700	8.5	25700	1	0	523	582
ВПКСН	7630	8	0	0	0	0	0
CANTON	38000 (1)	10	0	0	0	0	36330
COPAN	7500	М	2000	1	0	94	06
COUNCIL GROVE	24400	9	24400	ч	0	0	0
EL DORADO	142800	22.2	142800	г	0	7959	8052
ELK CITY	24300	10	24300	1	0	0	0
EUFAULA	26000	50	11980	16	ч	1055	1637
FORT GIBSON	0	0	0	0	0	14385	15758
FORT SUPPLY	400	0.2	400	ч	0	137	145
HEYBURN	2000 (2)	1.7	2000	m	0	1733	1816
HULAH	19800	12.4	19800	4	0	2708	6612
JOHN REDMOND	34900	24.5	34900	1	0	217	11085

WAITER SUPPLY STORAGE TABLE VI - 6

Corps of Engineers Projects (October 1988)

			(mmet 1300)			Pack	Page 2 of 3
	STORAGE ALLOCATED TO	ESTIMATED	AMOUNT	ac cacen	SILVEGIANO	AMOUNT SUPPLIED	UPPLIED
PROJECT	WALER SUPPLIE	MGD	AF	EXISTING	PENDING	FY 87	FY 88
KAW	171200	167	00806	е	0	4347	6861
KEYSTONE	20000	20	18000	1	1	5396	5402
MARION	38300	က	38300	1	0	727	762
COLOGAH	342600	154	322390	7	Ħ	54307	54192
OPTIMA	76200	4.5	0	0	0	0	0
SKIATOOK	62900	14	17308	2	0	0	0
TENKTLLER	25400	26.6 (3)	17260	ω	Ħ	5465	4752
TORONTO	400	0.1	400	8	0	11	06
WISTER	14000	20.03	13653	က	0	1355	3685
RED RIVER BASIN							
BROKEN BOW	152500	175	0	0	2	0	0
HUGO	47600	58	44890	٣	0	5681	5831
PAT MAYSE	109600	55	109600	ч	0	13316	12488
PINE CREEK	49400	84	28800	ч	0	33604	33788
SARDIS	297200	140	297200	Ħ	0	0	0
TEXOMA (4)	150000	150	114956	2	1	120	104
WAURIKA	151400	36.2	41800	1	0	4901	5178

Section 7 Projects (October 1988)

		Pac	Page 3 of 3
	STORAGE ALLOCATED TO	AMOUNT V	AMOUNT WITHINRAWN
PROJECT (5)	WALEK SUPPLY AF	FY 87	AF FY 88
ARKANSAS RIVER BASIN			
CHENEY	146980	27445	29345
HUDSON	0	0	0
MEREDITH	499700	64169	63426
THUNDERBIRD	105900	16212	17378
RED RIVER BASIN			  - 
ALTUS	122900	41332	71546
AREUCKLE	62570	7489	8269
FORT COBB	78350	9204	11051
FOGS	243670	1992	1987
LAKE KEMP	268000	47991	77187
MOUNTAIN PARK	88950	4210	4794
MOGEE CREEK	108000	0	œ
11 Other Property and the Company of			

Stet based on 1979 sedimentation survey.

Estimated storage to be available in year 2000.
Revision due to water supply yield restudy.
Joint water supply and power provided between elevation 617.0 - 590.0.
Estimated yield and contract information not available. £36£

STATION SUNMARY COOFERATIVE STREAM GAGING FROGRAM FISCAL YEAR 1988

ALBUQUERQUE DISTRICT

	DESERAL	RAL BATIONS	CONSTRUCTION General	UCTION ERAL				CORPS	
	STUBIES	0EN. COV	PLAN	PROJ.	K O	#R 8 T	CORPS	PER- CENT	PROGRAM
CITED OF COURT SERVICE	8 6 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	! ! ! ! ! ! !	1 1 1 1 1 1 1						
						•	000	6	211.280
MA . BA . T. MAG.	o	7.600	•	•	188.480	<b>-</b>	1969080	? •	267117
	•		c	0	•	0	0	0	<b>غ</b>
3		> <	• •	•	o	0	4.790	100	4.790
GC (4)	4.740	<b>5</b> (	•	• <	• •	0	•	0	0
- 01	•	•	•	•		•	000.000	-	214.070
TOTAL	4,790	7,600	•	0		•	2.8102	2	
3 14 14 14 14 14 14 14 14 14 14 14 14 14	2.4	<b>a.</b>	0.0	0.0	93.8	0.0	100.0		
TERCEN :									
NUMBER OF EQUIVALENT BAGES FUNDED	ES FUNDED								1
		1.2	0.0	0.0	39.4	0.0	40.7	9 Y	43.0
GAGE CLASS - BE			6	0.0	0.0	0.0	0.0	•	0.0
t	• ·	?			0.0	0.0	٠.	100	1:0
65 60 1	o.~	9	?			0.0	0.0	•	0.0
- 01	0.0	•	•					6	0.44
TOTAL	1.0	1.2	0.0	0.0	39.4	•		2	

NUMBER OF GAGING STATIONS/SITES: 44

NUMBER OF GAGES FUNDED 100% BY COOP PROGRAM: NOTE: INCLUDES AER FUNDS

+

O DUPLICATE GAGE NUMBERS WERE FOUND

TABLE VI - 8

STATION SUMMARY COOFERATIVE STREAM GAGING FROGRAM FISCAL YEAR 1988

FORT WORTH DISTRICT

	GEWERAL INVESTIGAT	ERAL IGAT IONS	CONSTR	CONSTRUCT ION GENERAL				CORFS	
	STUDIES	GEN. COC	PLAN	PROJ. CONST	¥ # 0	HRBI	CORPS	PER-	FROCKAN SUPFORT
FUNDS (DOLLARS)									
	•	•	•	1.110	450.000	•	451,110	46	477.970
1	• •	•	•	0	212,350	0	212,350	90	236,090
1	•	•	•	0	•	•	0	•	•
10 -		•	0	0	0	•	0	•	•
TOTAL	•	•	۰	1,110	662,350	0	663.460	63	714.060
PERCENT	0.0	0.0	0.0	0.2	99.8	0.0	100.0		
	ES FUNDED								
GAGE CLASS - SM		0.0	0.0	3.0	88.8	0.0	91.8	897	105.0
20	0.0	0.0	0.0	0.0	27.0	••	27.0	2	30.0
97	0.0	0.0	0:0	0.0	0.0	0.0	0.0	•	0.0
- 01	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0	0.0
TOTAL	0.0	0.0	0.0	3.0	115.7	0.0	118.7	88	135.0

NUMBER OF BABING STATIONS/SITES: 114

NUMBER OF GABES FUNDED 160% BY COOP PROGRAM: 12 NOTE: INCLUDES AER FUNDS

O DUPLICATE GAGE NUMBERS WERE FOUND

STATION SUMMARY COOPERATIVE STREAM GAGING PROGRAM

		)	FISCAL YEAR 1988	AL YEAR 191	8				
			BALVE	DALVESTON DISTRICT	ICT	1	1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		}
	DENERAL	RAL	CONSTRUCTION GENERAL	CT 10H RAL				CORPS	
	BTUBIES	9EN. COV	PLAN	PROJ. CONST	NBO	MRST	CORPS	CEST	SUPPORT
		, , , , , , , , , , , , , , , , , , , ,	; ; ; ; ;						
FUNDS (DOLLARS)				1	6	G	159,230	98	184,460
	4.190	0 (	o <	7,080	094./41	0	0	00	<b>0</b> 0
30 -	<b>0</b> C	9 0	• •	•	•	• •	•		• •
10 -	•	0 6	00	7,080	147.960	• •	159,230		184,460
TOTAL	4.190	>	1	•	6	0.0	100.0		
PERCENT	2.6	•	0.0	٠ •	45.4	;	, , ,		
NUMBER OF EQUIVALENT BASES FUNDED	SES FUNDED					•	28.2		
SALE CLASS - SE	4.0	00	000	0.0	9.0 0.0 7	000	00	00	<i>o</i> o
	9 6	0	0.0	• •		•	•		
<b>:</b> 5		0.0	0 6	9.0		0.0	20.5		
TOTAL	•	•	•	<b>)</b>					

17 MUNBER OF GAGES FURDED 1801 BY COOP PROGRAM! NOTE: INCLUDES AER FUNDS 7 NUMBER OF GAGING STATIONS/SITES!

VI-43

O BUPLICATE GAGE MUNBERS WERE FOUND

STATION SUNNARY COOPERATIVE STREAM GAGING PROGRAN FISCAL YEAR 1988

		P
	1	۱
	ı	ı
	1	ė
	ì	
	3	
	Ų	Ľ
	•	١
	i	
	2	
i	i	
1	į	ï
1		ì
1	ı	
i		
•		٠
•	-	1
		J

	GENERAL Investigat	BENERAL /estigations		CONSTRUCTION General	JCT I ON		1 2 4 6 8 7 1 1	• • • • • • • • • • • • • • • • • • •	!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!	
•	, f ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! !		!	•					CORFS	
	STUDIES	BEN. COV	200	PLAN	PROJ. CONST	W\$0	HRBT	CORPS	PER	PROGRAM
FUNDS (BOLLARS)					1				CERT	SUPPORT
GASE CLASS - RU	•									
30 -	10.720	5,480		•	•	351,390	•			
85 ·	۰ ه	0 00		۰ ،	•	17,500	<b>,</b>	367.790	78	470.760
TO -	•			•	o (	099.9	• •		<b>.</b> ?	18.100
	10.920	7.400		•	<b>&gt;</b>	0	0	•	•	029.
PERCENT	2.8	1.0		•	•	2000	•	393.870	78	503,480
NUMBER OF EQUIVALENT GAGES FUNDED	S FUNDED			•	•	65.3	0.0	100.0		
BAGE CLASS - SW	0.8	•		•						
30 ' '	0			• •	0 0	51.3	0.0	56.9	7	72.0
-	•	7.0		0.0	•	. v	0.0	4.4	<b>&amp;</b>	7.0
TOTAL	9 C	•		0,0	0.0	0	9 6	12.2	<b>7</b>	16.0
		•		o 9	0.0	63.4	0	76.0	•	90.0

NUMBER OF GAGING STATIONS/SITES: 74

NUMBER OF GAGES FUNDED 100% BY COOP PROGRAM: NOTE: INCLUDES AER FUNDS

18

O BUPLICATE GAGE MUNDERS WERE FOUND

STATION SUMMARY COOPERATIVE STREAM GAGING PROGRAM FISCAL YEAR 1988

TULSA DISTRICT

	INVESTIBATI	ATIONS	BENERAL	KAL				CORPS	
		GEN. COV	PLAN	PROJ. CONST	N80	## # T	CORPS	PER- CENT	PROGRAM SUPFORT
FUMDS (DOLLARS)									
BAGE CLASS - SE	٠	•	•	•	884.300	•	884.300		1,288,560
30 -	•	•	•	•	85.890	•	08.80		86,275
: of:	• •	•	•	•	15,950	•	15.950		15,950
10 -		•	•	•	•	•	•	•	•
TOTAL	•	•	•	•	786.140	•	986.140		1,390,785
PERCENT	0.0	0.0	0.0	0.0	100.0	0.0	100.0		
NUMBER OF EQUIVALENT GAGES FUNDED	ES FUNDED								
6AGE CLASS - SE	0.0	0.0	0.0	0.0	136.6	0.0	136.6	71	
	0.0	0.0	0.0	0.9	9.0	0.0	0.6	100	
87 H	0.0	0.0	0.0	0.0	40.0	0.0	0.0 <del>4</del>	100	
10 -	0.0	0.0	0.0	0.0	0.0	0.0	0.0	•	
101AL	0.0	0.0	0.0	0.0	185.6	0.0	185.6	77	241.0

NUMBER OF GAGING STATIONS/SITES: 196

VI-45


MUNDER OF BAGES FUNDED 100% BY COOP PROGRAM: Note: Includes aer funds

52

O DUPLICATE GAGE MUNBERS WERE FOUND

#### SECTION VII - RESERVOIR DATA SUMMARY

- 1. SWD MAP
- 2. INDEX BY BASINS
- 3. INDEX IN ALPHABETICAL ORDER
- 4. DATA TABLES



				ÿ	1 000	71 C A F C	rafra.		
LANE NAME	STREAM	1814	SIATE	COMP	_	FC TON	CONS	1900 Hr S FC	D N
			WHI1F R	IVER BASI	z				
PEAVER	WHITE	LRU	ΑŔ	99	1120.00	1130.00	1652	300	-
TABLE ROCK	WHITE	1 67	AR/MO	e.	915.00	931,00	2702	760	-
FULL SHOALS	WHITE	LRI	AR/MO	C-1	654.00	695.00	3048	2360	c.
NORFORK	NORTH FORK	LRT	AR/MB	4. P.	552.00	580,00	1251	732	C4
CLEARWATER	BLACK	ار 13	£	48	494.00	567.00	51 51	391	ŀΩ
GREERS FERRY	LITTLE RED	LRD	AR	<b>29</b>	461.00	487,00	1119	934	м
			ARKANSAS	RIVER	EASIN				
FUEBLO	ARKANSAS	ADA		74	4880.60	4898.70	264	63	4
TRINIBAD	PURGATORIE R	ΑŪ	00	78	. 9	6260.00	64	58	4
JOHN MARTIN		ΑŪ	0.3	51	3851.00	3870.00	351	270	ເກ
CHENEY	N F NINNESCAH	10*	κS	64	1	1429.00	167	91	רט
ELDORADO	A	T.[i	S	80	0	1347.50	157	62	9
N ₩ V	ARKANSAS	1	OK/KS	76	0	1044.50	426	919	9
GREAT SALT PLAINS	SALT FORK ARK	ij	9 S	4 1	CI LU	1138.50	31	240	7
KEYSTONE	ARKANSAS	Ţ	<del>ا</del> م	64	1	24	618	1219	7
HEYBURN	FOLECAT CR	ī	NO.	50	761.50	84	۲.	48	æ
TORONTO	VERPIGRIS R	ī	S 2	09	901,50	31	22	178	ထ
FALL RIVER	FALL	ű.	s ¥	4	48	87	4 61	235	٥
ELK CITY	ELK	<u>:</u>	S	99	792.00	2. 13.	3.4	256	٥
RIG HILL	HIL	Ē	S	81	858.00	67	27	13	<u>e</u>
00L06AH	GRIS	10	O.Y.	63	638.00	÷	553	996	10
HULAH	CANEY	ĩ	OK/KS	51	733.00	65	34	208	-1
COPAN	L CANEY	1	OK/KS	80	710.00	٣	43	184	Ξ
BIRCH	BRICH CREEK	ű.	ě	29	750.50	774.00	19	39	12
SKIATOOK		ī.	ě	85	714.00	C1 Dv	305	182	<u>.</u>
NELT GRAHAM LD 18	VERDIGRIS	<u>-</u>	¥ 6	20	532,00	00.	4 1	0 ;	رج. ا
CHOUTEAU LD 17	VERDIGRIS	Ξ;	¥ 0	٥ ز	00.115	0	11:00	o ř	51.
COUNCIL GROVE	9	<u>-</u> ;	n (	n (	12/0:00	7 0 7	000	0 (	* •
MAKIUN John Bernadan	COLLONADOR K	= =	n u 2 2	9 9	1550.50	00.80.00	7 o	000	+ u
PENSACOLA (GRAND LAKE)	NEGSHO (GRAND)	# = = =	2 2	4 0	745.00	2 10	1672	ាស ខេត្ត ស្រ	) <u>   </u>
LAKE HUDSON		***	Ą	64	1.9	~	200	244	16
FORT GIRSON	•	ŢŢ	O.K	52	•	582,00	345	919	1,4
WEBBERS FALLS LD 16	8	ďL	OK	20	90	00.	165	0	17
TENKILLER FERRY		ū	96	52	632.00	00.799	654	577	17
CONCHAS	CANADIAN E	ΑŪ	£	39	4201.00		330	198	<del>د</del> ۳
SAWFORD (MEREDITH)		T.[:*	Ϋ́	65			945	463	13
NORMAN (THUNDERBIRD)	LITTLE R	11.04	ΥL	65	1039.00		120	77	1.0
OPTIMA	CANA	ī	9 X	78	~		129	101	3.0
FORT SUPPLY		ũ	9 ¥	<b>4</b>	4.0		14	87	130
CANTON	N CANADIAN R	ű	ě	<b>4</b> 8		٠	116	268	50 50
ARCADIA	RKANSAS	1	Š	98	0.90	(C)	28	89	7.
ELFAULA	CANAPIAN R	110	ő	4 9	85.0		2329	1470	<b>.</b> .∶
R S KERR LD 15	ARKANSAS	Ĩ	<del>.</del>	20	460.00	00.	464	0	N N

LAKE NAME	STREAM	TSIO	STATE	YR Comp	POOL ELEV CONS	ELEVATION FC	CAFAC 1000 CONS	CAFACITY## 1000 AF S FC	F.AL-1
41 B 1 B 14	ARKANSAS	Ū1	Ş	7.0	413.00	00.	16	c	ç. •
ELSTER.	FOTEAU R	ũ	Ŋ	49	471.60	502,50	27	400	53
JAMES W TRIMBLE LD 13	ARNANSAS	LRI	AR/OK	69	392.00	00.	40	0	4
	ARKANSAS	LRD	AR	69	372,00	00.	148	c	2.4
DARBANELLE LD 10	ARKANSAS	1.5.1	AK	64	338,00		486	- 1	er Se
	FETIT JEAN	LRI	AR	٧,	384.00	419,00	ני ניק	66. 13.	រោៈ (*)
	ARKANSAS	LRD	A.	59	287.00	00.	(-) (-) (-)	0 (	9 :
JCK FERRY LD		. K.	A .	\$ ¢	265.00	,	ა ი ი	0 7 0	0 r
NIMROD	FOURCHE LA FAVE	= i	G A	4 	347.00	3/3,00	11 0 V V	\ 0°	, ,
	ARKANGAG	1	ž ú	, a	244.00	00.	r h	> C	) i
ILL TERRIT LID O	ARKANDAD	. E	. 4 . 3	90	213.00	00.	່ ທີ່ ວ່າຍ	0	; ;
	ARKANSAS	יי צייי ציייי	Ą	89	196,00	00.	ůζ	0	52
	ARKANSAS	18.0	AF	89	182.00	00.	46	0	59
	ARKANSAS	LRD	ል	67	62	00.	110	0	30
	ARKANSAS	LRD	A.R.	47	•	00.	¢!	0	3.0
			<u>п</u>	FI KTUFE	F 651X				
21118	2 2 2 2	# I L	×		1559.00	1562,00	141	21	31
MOUNTAIN PARK (TOM STD.)	W OTTER CREEK	*aL	Š	75	0	14	96	20	32
	CHITA	1 fi #	×	77	1144.00	~	568	225	32
		11	OK OK	78	951.40	CI	203	140	4.6
F055	WASHITA	¥.J.L	OK.	61	1562,00		256	181	33
FORT COBB	COBB CREEK	¥ű.	O. X	59	1342.00	1354,80	78	64	34
ARBUCKLE	ROCK CREEK	¥úL	OK YO	67	872.00	LO.	72		34
LAKE TEXOMA		Ţ	TX/OK	<b>4</b> 00	617.30	ó,	2836	2660	5 M
McGEE CREEK	CREE	<b>1</b> [] <b>*</b>	¥0	87	577.00	595.50	113	199	32
FAT MAYSE	ĸ	Ē	×	89	451.00	$\circ$	124	ရှာ (	36
SARDIS	JACK FORK CREEK	= 1	¥ :	69 i	599.00	Ċ,	305 4 102	128	36
HUGO	KIAMICHI K	Ē	<del>5</del> 6	4,	404.50	437.50	15/	808	٠ د د
PINE CREEK	LITTLE R	= ;	¥ :	69	443.00	480.00	0 0	000	70
BROKEN BOW	MOUNTAIN FORK	= : - :	8 °	9 1	544.50	05./29	717	000	0 G
JE GUEEN	KULLING FURN	1 E	۷ ü	//	00.405	00.045	9 6	186	- 0- - 1-1
	COSSH CO	. c	í ú	7,0	506.00	557.50	) K	67	<b>4</b>
	117756 8	LRD	A.	99		287.00	207	1653	0
WRIGHT PATHON	SULPHER RIVE	FW	×	56	20.	259.50	143	2509	41
LAKE O THE PINES	CYPRESS CREEK	FW	×	09	28.5	249.50	251	580	41
			NECHE	FS RIVER	RASIN				
SAM RAYBURN	ANGEL INA R	S M	×	9	_	173.00	3898	1009	
B A STEINHAGEN	NECHES R	FILE	Ϋ́	51	81.0	83.00	20	24	42
			TRINI	-	R BASIN				
BENBROOK	CLEAR FORK	FW	×	52	694.00	724.00	88	170	43
JOE FOOL	MOUNTAIN CREEK	ニコル	¥	98	522,00	536,00	143	123	4
RAY ROBERTS	ELM FORK	ŪΜL	×	87	632.50	640.50	749	260	4
LEWISVILLE	ELM FORK	FW	ĭ	54	515.00	532.00	<b>4</b> 65	525 	4 4
GRAPEUINE	DENTON CR	FWT	×	ات دا	535,00	560.00	189	2 <b>4</b> 8	 

				34 >-	1 1 1003	NOTTON	CAFAC	CAPACII)***	F. A.G.F
LANE NAME	STREAM	1214	STAIE	COMF		ال	CONS		NC
LAUDN	FAST FORK	FWE	×	77	492,00	503.50	457	277	45
NAVARRO MILLS	RICHLAND CR	FWE	×	89	424.50	443.00	63	149	4 6
BARDWELL	WAXAHACHIE CR	FWD	ΧL	59	421.00	439.00	n S	Ē	<b>4</b> د
			¥ 5	CACINTO RIVER	JER BASIN				
RAFKER	RUFFALO BAYOU	ű.		4.0		107,00	0	202	47
ADDICKS		6.0	1×	48	00.	114.00	0	205	47
			HRA	PRAZOS RIVFR	ž				
WHITNEY	BRAZUS	E I	×	51	533,00	571.00	627	1372	48
ANUILLA	ABUILLA	FWT	×	83	537,50	556.00	34	87	48
0003	BOSOUE	in.	×	65	455.00	500.00	153	574	45
PROCTOR	LEON R	FWI	ΥL	63	1162.00	1197,00	69	315	49
RELTON	LEON R	ΨĮ	ř	5.4	594.00	631.00	<b>4</b> 58	640	00
STILLHOUSE H	LAMPASAS R	i M	×	8 <b>9</b>	622.00	966.00	236	395	00
GE. OR GE. TOWN	N F SAN GARRIEL	ニヌ	×	7.0	791.00	834.00	32	63	51
GRANGER	SAN GRARIEL	FWD	×	29	504.00	524.00	99	129	ត
SOMERVILLE	YEGUA CR	3	×	29	238.00	258,00	160	347	<u>.</u>
			COL	COLORADO RIVER	JEE RASIN				
THIN BUTTES	S&M CONCHO R	FWIT	×	63	1940.20	1969,10	186	454	53
O C FISHER	N CONCHO R	E W	×	52	1908.00	1938.50	119	277	~: 5
HORDS CR	HORDS CR	FWI	×	48	1900.00	1920.00	٥	17	<b>e</b>
MARSHALL FORD	COLORADO R	FED*	×	40	681.00	714.00	1172	780	54
			9119		RIVER RASIN				
CANYON	GUADALUPE R	<u> </u>	×	64	00.606	943,00	386	13 13 13 13 13 13 13 13 13 13 13 13 13 1	ŝ
			100	ORAPO RIV	COLORADO RIVER BASIN				
NAVAJO	SAN JUAN	<b>₩</b> 1₩	Ĭ	62	2000.00	6085.00	t	:	26
				KIO GRANI	GRANDE BASIN				
FLATORO	CONEJUS R	¥ij∀	00	51	10027.50	10034,00	رة 4	9	57
AFIGUIU	RIO CHAMA	ΦŪ	Į	63	00.	6283.50	٥	568	5.7
COCHITI	RIO GRANDE	ΑŪ	E Z	75	5321.45	5460.50	47	539	:: (1)
G, LISTED	GALISTED CR	ijΨ	ĭ	20	60.	2408.00	0	06	n B
JEMEZ CANYON		ΑŪ	I	53	5160.00	5232,00	נו	104	6
SANTA ROSA	PECOS R	ĒΦ	Į	80	7	4797.00	267	182	<u>ن</u> 6
SUMMER	FLC0S R	Ati*	ĭ	37	4261.00	4282.00	47	98	60
TWO RIVERS	RIO HONDO	ĄŖ	£	63	00.	4032.00	C:	168	99

#Section 7 Flood Control Projects ##Includes dead storage, conservation: water supply: power: irrisation, etc.

#### ALPHABÉTICAL INDEX

PROJECT	RIVER	
NAME	BASIN	PAGE NO.
ABIQUIU	RIVER BASIN  RIO GRANDE SAN JACINTO RIVER RED RIVER BRAZOS RIVER RED RIVER ARKANSAS RIVER ARKANSAS RIVER TRINITY RIVER SAN JACINTO RIVER WHITE RIVER BRAZOS RIVER TRINITY RIVER ARKANSAS RIVER	5. <b>7</b>
ADDICKS	SAN JACTNTO RIVER	) ( ) 7
ALTUS	RED RIVER	* (
AQUII.I.A	BRAZOS BIVER	3 t
ARBUCKLE	RED RIVER	4 8
ARCADIA	VED WIACK	34
ARTHUR V ORMOND (ID 12)	ADVANCAC DIVED	21
B A STEINHAGEN	NEURES DIVER	20
RARDWEII	TRINITY RIVER	42
BARKER	CAN IACTNED DEVED	46
REAVER	MUTTE DIVER	4 /
REI TON	NOTIC STACK	1
BENBROOK	TRINITY RIVER	50
RIC UTII	ADVANCAC DIVED	4 3
BIDCU	ARKANSAS RIVER	10
DIRCH DIGE MOUNTAIN	ARKANSAS KIVEK	12
BEOKEN BON	ARKANSAS KIVER	25
DRUKEN BUW	RED RIVER	38
CANTON	WHITE RIVER	2
CANYON	ARKANSAS RIVER	20
CANION	GUADALUPE RIVER	55
CHENEY	ARKANSAS RIVER	5
CHOUTEAU (LD 17)	ARKANSAS RIVER	13
CLEARWATER	WHITE RIVER	3
COCHITI	RIO GRANDE	58
CORAN	ARKANSAS RIVER	18
COPAN	ARKANSAS RIVER	11
COUNCIL GROVE	ARKANSAS RIVER	1 4
DARDANELLE (LD 10)	ARKANSAS RIVER	25
DD TERRY (LD 6)	ARKANSAS RIVER	28
DEQUEEN	RED RIVER	39
DIENKS	RED RIVER	40
ELDORADO	ARKANSAS RIVER	6
ELK CITY	ARKANSAS RIVER	9
EUFAULA	ARKANSAS RIVER	21
FALL RIVER	ARKANSAS RIVER	9
FORT COBB	RED RIVER	34
FORT GIBSON	ARKANSAS RIVER	16
FORT SUPPLY	ARKANSAS RIVER	20
FOSS	RED RIVER	33
GALISTEO	RIO GRANDE	5.8
GEORGETOWN	BRAZOS RIVER	51
GILLHAM	RED RIVER	39
GRANGER	BRAZOS RIVER	5 1
GRAPEVINE	TRINITY RIVER	45
GREAT SALT PLAINS	ARKANSAS RIVER	7
GREERS FERRY	WHITE RIVER	3
HEYBURN	ARKANSAS RIVER	8
HORDS CR	COLORADO RIVER	54
HUGO	RED RIVER	37
HULAH	ARKANSAS RIVER	11
		• •

#### ALPHABETICAL INDEX

PROJECT Name	RIVER	
NAME	ARKANSAS RIVER RIO GRANDE TRINITY RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER RED RIVER RED RIVER RED RIVER TRINITY RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER COLORADO RIVER RED RIVER RED RIVER RED RIVER RED RIVER RED RIVER RED RIVER ARKANSAS RIVER	PAGE NO.
JAMES W. TRIMBLE (LD 13)	ARKANSAS RIVER	24
JEMEZ CANYON	RIO GRANDE	5 9
JOE POOL	TRINITY RIVER	43
JOHN MARTIN	ARKANSAS RIVER	5
JOHN REDMOND	ARKANSAS RIVER	15
KAW	ARKANSAS RIVER	6
REISIUNE	ARKANSAS RIVER	7
LAKE NEMB	AKKANSAS KIVER	16
TAKE NEMP	MED MINER	32
TAKE O THE PINES	RED RIVER	41
TAVON	TOTATTY DIVED	35
LD 1	ADVANCAC DIVED	45
LD 3	ARKANSAS RIVER	30
LD 4	ARKANSAS RIVER	29
LD 5	ARKANSAS RIVER	29
LEWISVILLE	TRINITY RIVER	2 O
MARION	ARKANSAS RIVER	14
MARSHALL FORD	COLORADO RIVER	5.4
McGEE CREEK	RED RIVER	35
MILLWOOD	RED RIVER	40
MOUNTAIN PARK (T. STEED)	RED RIVER	32
MURRAY (LD 7)	ARKANSAS RIVER	27
NAVAJO	SAN JUAN RIVER	56
NAVARRO MILLS	TRINITY RIVER	46
NEWT GRAHAM (LD 18)	ARKANSAS RIVER	13
NOBEOBR	ARKANSAS RIVER	27
NORMAN (THUNDEDDEDD)	WHITE RIVER	2
O C ETCHED	ARKANSAS RIVER	19
OUTOGAH	COLORADO RIVER	53
OPTIMA	ARKANSAS KIVER	10
07ARK-J T (ID 12)	ADVANCAC DIVED	19
PAT MAYSE	BED BIVES HIVEN	24
PENSACOLA (GRAND LAKE)	ARKANSAS RIVER	30 15
PINE CREEK	RED RIVER	37
PENSACOLA (GRAND LAKE) PINE CREEK PLATORO	RIO GRANDE	5 <i>7</i>
	BRAZOS RIVER	49
PUEBLO	ARKANSAS RIVER	4
RAY ROBERTS	TRINITY RIVER	44
R S KERR (LD 15)	ARKANSAS RIVER	22
SAM RAYBURN	NECHES RIVER	42
SANFORD (MEREDITH)		18
	RIO GRANDE	59
<b></b>	RED RIVER	36
	ARKANSAS RIVER	12
SOMERVILLE	BRAZOS RIVER	52
<b>*</b> • • • • • • • • • • • • • • • • • • •	BRAZOS RIVER	50
	RIO GRANDE	60
	WHITE RIVER	1
TENKILLER FERRY TOAD SUCK FERRY (LD 8)	AUVANCAC BIVEB	17
The state of the s	AUNANOAS RIVER	26

#### ALPHABETICAL INDEX

PROJECT NAME	RIVER BASIN	PAGE NO.
TORONTO TRINIDAD TWIN BUTTES TWO RIVERS W D MAYO (LD 14) WACO WAURIKA WEBBERS FALLS (LD 16) WHITNEY WILBUR D. MILLS (LD 2) WISTER WRIGHT PATMAN	ARKANSAS RIVER ARKANSAS RIVER COLORADO RIVER RIO GRANDE ARKANSAS RIVER BRAZOS RIVER ARKANSAS RIVER BRAZOS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER ARKANSAS RIVER RED RIVER	8 50 22 4 37 4 30 31 4 32 4
WKIGHI PAIMAN		

# SUMMARY OF LAKE CONDITIONS FOR WATER YEAR 1988 LITTLE ROCK DISTRICT WHITE RIVER BASIN

BEAVER	200	\$	DEC	JAN	FEB	HAR	APR	KA.	3	a a	AUG	SEP	TOTAL
Inflows (1,000 AC. FT.) Avg 1968 thru 1988 ur 1988	53.0 12.6	112.9	126.6 382.5	74.5 82.0	102.8 65.8	1%.6 305.5	173.6 261.1	118.4 22.3	7.8.7	21.3	15.5 5.5	28.6	1102.5 1254.5
Releases (1,000 AC. FT.) Avg 1968 thru 1988 Wr 1988	34.6 9.6	52.6 6.3	92.7 215.7	86.5 168.9	90.8 124.8	101.7	119.0	99.7 119.2	34.2	84.8 16.2	80.4 37.3	53.4	977.6 1151.3
Basin Rainfall (inches) Avg 1968 thru 1988 WY 1988 Deviation	4.6 3.2 -1.4	4.4 6.5 5.5	3.5 9.1 5.6	1.9 4.1 5.	2.2	7.9	2,4	4.8 1.7 -3.1	4.0 1.4 -2.6	2.7 5.3 2.6	3.2 2.3 .9	6.0 5.3 5.3	44.2 49.8 5.6
Pool Elevation End of Month Naximum Minimum	1116.59 1116.74 1116.28	1118.79 1118.79 1116.41	1124.44 1125.38 1118.79	1121.30 1124.44 1121.30	1119.03 1121.32 1119.03	1121.48 1121.48 1118.42	1124.23 1125.14 1121.48	1120.46 1124.23 1120.46	1119.14 1120.49 1119.11	1118.92 1119.17 1118.88	1117.35 1118.92 1117.33	1116.82 1117.42 1116.76	
Pool Content EOM (1,000 AC. FT.)	1557.7	1618.1	1780.8	1689.1	1624.8	1694.2	1774.5	1665.1	1627.9	1621.8	1578.4	1564.0	
TABLE ROCK LAKE	50	AON	DEC	JAN	FE8	MAR	APR	HAY	NO.	¥	AUG	SEP	TOTAL
Inflows (1,000 AC. FT.) Avg 1961 thru 1988 ur 1988	110.9 30.1	226.0 130.2	263.3 959.2	212.5 329.0	234.8 312.7	404.6 771.5	421.8 <b>63</b> 4.6	352.2 198.1	221.2	141.2 85.5	135.6 61.8	98.5 52.9	2822.6 3628.9
Releases (1,000 AC. FT.) Avg 1961 thru 1988 VY 1988	108.6 40.3	183.6	280.0 335.6	250.2	214.8 332.9	308.9 560.6	350.2	319.1	205.4	206.4	166.8 192.9	121.6	2715.6 3509.8
Intervening Basin Rainfall (inches) Avg 1961 thru 1968 LY 1968 Seviation	inches) 4.6 3.4	5.7 5.0 8.	3.6 5.2	<b>.</b> 0. 0.	2.2 2.2	4.2 6.2 2.0	3.8	4.4 2.1 -2.3	4.4 1.6 -2.8	2.9 7.4 1.8	ы. 8. ж. 2.	3.9 5.2 1.3	43.8 47.7 3.9
Pool Elevation End of Month Maximum Minimum	905.78 906.35 905.58	905.08 905.79	919.84 919.84 903.46	914.13 920.00 913.20	913.43 914.16 911.63	918.00 918.00 913.16	914.50 921.58 914.50	913.02 914.60 912.91	911.20 913.02 911.13	910.61 911.81 910.61	906.86 910.61 906.80	905.06 906.86 905.00	
Pool Content ECM (1,000 AC. FT.)	2326.6	2300.0	2915.8	2664.6	2635.1	2833.0	2680.5	2617.8	2542.2	2518.0	2368.5	2299.3	

#### WHITE RIVER BASIN

MUL SHOALS LAKE	961	NO.	DEC	NYC	FEB	<b>KA</b>	APR	¥	3	Į,	AUG	<b>33</b>	TOTAL
Inflows (1,000 AC. FT.)											1		
Avg 1953 thru 1968	143.9	274.2	390.5	306.2	332.3	526.2	562.0	554.1	336.5	364.0	200.4	156.7	4147.0
ur 1988	65.0	258.6	9.096	8.769	461.5	945.7	1098.9	97.62	155.6	168.9	233.8	145.1	5506.1
Relesses (1,000 AC. FT.)													
Avg 1953 thru 1988	204.1	18.4	286.9	356.6	323.5	370.5	6.807	395.7	309.9	390.6	341.5	243.9	3828.5
W 1988	45.1	359.7	383.4	849.0	554.6	7.669	963.8	455.2	234.2	177.2	274.6	155.3	5211.8
Basin Rainfall (inches)													
Avg 1953 thru 1988	3.9	4.3	3.3	1.7	2.1	3.7	4.1	4.2	3.4	3.2	3.4	3.9	41.2
ur 1966	3.5	4.5	9.0	٥.	2.1	6.0	3.3	2.1	2.4	5.3	3.6	4.4	47.1
Deviation	<b>4.</b> -		5.7	<b>.</b>	٥.	2.3	•	-2.1	-1.0	2.1	۲.	'n	5.9
Pool Elevation													
End of Month	647.30	644.52	657.80	654.16	651.77	656.78	659.16	655.24	651.53	650.76	649.26	19.879	
Heximan	647.31	15.739	657.80	660.34	654.16	656.78	663.46	659.40	655.33	651.97	650.84	649.26	
Minimum	646.88	644.52	644.25	654.16	651.41	651.77	656.78	655.24	651.27	650.51	648.54	648.23	
Pool Content EQM													
(1,000 AC. FT.)	2754.6	2639.3	3223.6	3055.3	2947.9	3175.7	3288.7	3104.4	2937.3	2903.4	2838.2	2810.2	
		•	;			;	!		į	:	:	;	
WALLEN LANG	3	\$	DEC	3	7	Ĭ	APR	ž	Ş	<b>ặ</b>	SE S	<b>S</b>	TOTAL
inflows (1,000 AC. FT.)	:	8	,	•	;		,	į	,		•	:	
AVG 1940 TRIU 1966 VY 1968	33.8	88.5 57.1	76.6 36.3	127.3	108.1	186.0 292.4	197.7	186.4 92.1	5. S.	88.2 2.2 2.1	4.8.3 2.8.3	56.6 50.0	2163.3
Releases (1,000 AC. FT.)	**	5	•	7 144		ķ	9	7.47	2		•	•	
uy 1968	2 02		154.7	700	118 4	2,57	27.0	2. 79	9 5	7 28	107.5 7.7.4	? °	
										2	2		
Basin Rainfall (inches)													
Avg 1946 thru 1966	H.	3.8	3.2	5.4	2.7	3.7	<b>+</b> .1	4.8	4.0	3.5	3.0	3.5	41.8
VY 1988	3.2	4.1	8.6	1.4	2.0	5.9	3.1	2.7	1.6	2.0	3.4	4.3	45.3
Deviation	τ.	ų.	5.4	-1.0	7	2.2	-1.0	-2.1	-2.4	1.5	٧.	€.	3.5
Pool Elevation													
End of Month	550.54	552.17	560.98	552.04	551.32	553.18	552.05	553.68	554.55	554.55	552.31	550.68	
Maximum	\$51.16	552.26	560.98	561.46	552.10	553.18	557.33	553.68	554.55	555.14	554.57	552.36	
Minimum	550.22	550.54	551.58	552.04	551.26	249.67	\$52.05	551.67	553.68	554.50	552.31	550.65	
Pool Content ECM													
(1,000 AC. FT.)	1219.4	1254.9	1459.6	1252.1	1236.2	1277.3	1252.3	1288.5	1308.1	1308.1	1258.0	1222.4	

#### WHITE RIVER BASIN

CLEANATER LAKE	8	<b>MOV</b>	DEC	JAN	FEB	MA	APR	K	<b>3</b> 5	Ę	AUG	SEP	TOTAL
Inflows (1,000 AC. Fl.) Avg 1949 thru 1968 WY 1968	22.8	50.6 24.5	64.9 177.8	55.8 78.1	57.2	90.5 103.0	93.5	75.2	36.5 10.6	26.4 18.2	19.2 12.9	20.6 15.9	615.2 592.7
Releases (1,000 AC. FT.) Avg 1949 thru 1968 WY 1966	23.4	33.0 22.8	60.1	61.6 154.8	59.1 55.1	78.9 65.9	88.4 99.1	74.9	50.3	33.3 19.6	27.4	27.0 18.3	617.4 590.7
Basin Rainfall (inches) Avg 1949 thru 1966 WY 1906 Deviation	w.w. o.t. t.	1. W	3.5	2.5	2.7 2.0 7	6.1 5.8 1.7	4.3 1.7 -2.6	4.5 2.3 -2.2	3.7 1.5 -2.2	3.7 6.3	3.4 2.0 -1.4	4.8 4.0	42.9 42.1 8
Pool Elevation End of Month Maximum Minimum	494.32 497.29 494.05	495.26 495.47 494.06	521.93 522.26 494.02	494.41 521.93 494.41	494.09 495.77 493.76	510.55 510.55 494.03	494.15 511.91 493.76	497.99 498.19 494.15	497.90 497.99 497.59	\$8.8 \$8.3 \$6.3 \$6.3	496.49 497.06 496.40	494.89 497.79 494.89	
Pool Content EOM (1,000 AC. FT.)	22.4	24.0	8.5	22.6	22.1	58.9	22.2	28.9	28.7	26.6	26.1	7:2	
G	\$	MON	DEC	JAN	<b>2</b>	ž	APR	¥	ş	¥	27	SEP	TOTAL
Inflows (1,000 AC. FT.) Avg 1965 thru 1988 Wr 1988	45.9	71.0	192.5 363.0	108.4 176.3	138.0 132.3	140.5	224.2	160.0 20.8	53.4	10.8 15.5	7.8	26.0 10.1	1217.4
Releases (1,000 AC. FT.) Avg 1965 thru 1968 ur 1966	7.5g 8.9	40.9	78.5 33.7	144.8 244.0	136.5 292.5	137.6	136.0 186.4	126.4 26.5	90.0 43.9	103.9 90.2	101.8 48.3	53.4	1186.5
Basin Rainfall (inches) Avg 1964 thru 1968 WY 1968 Deviation	2.8	6.9 2.2	6.6 3.9 3.9	2.6 2.9 3.	3.1 2.7 2.4	6.9 5.7 8.	441	5.1 2.5 -2.6	3.6 1.1 -2.5	8.4 9.4 9.6	3.3 -1.2	44.	48.9
Pool Elevation Maximum Minimum	455.64 456.28 455.60	457.68 457.68 455.51	467.81 467.81 457.68	465.66 468.00 465.63	69.094 69.094 60.49	459.54 462.03 459.28	460.63 462.21 459.54	460.03 460.63 460.03	<b>458.29</b> <b>460.05</b> <b>458.29</b>	455.39 458.29 455.39	453.30 455.39 453.30	452.92 453.31 452.71	
Pool Content ECH (1,000 AC. FT.)	1746.2	1807.4	2132.5	2060.0	1894.4	1864.7	1896.8	1879.9	1826.0	1738.7	1676.7	1665.7	

#### RUPHO RESIENOIR

[ref] case (1000) Ar-35-)	<b>6</b>	ğ	DBC	JAN	<b>201</b>	MAR	AFR	YAN'	N	JOL	AUG	SES	TOTAL
Avg 1894 thru 1988 FY 1988	22.13	28.36	21.35 30.85	19.92 30.23	16.75 23.61	16.16 27.39	24.11 27.95	68.51 48.95	128.29 100.93	87.26 48.51	55.89 39.59	25.97 21.77	508.84 464.21
Releases (1000 Ac-Ft) Avg 1966 thru 1988 FY 1988	20.41 25.64	16.35 16.56	14.23 14.59	14.56 29.55	13.47 16.94	14.90 21.98	27.17 33.33	66.12 59.11	124.91 101.85	89.14 94.62	56.42 77.13	25.01 24.39	482.70 515.69
Rainfall (Inches) Avg 1938 thru 1988 FY 1988	8 9	%. 8.	87. 47.	£.	.26	1.04	8. 3.	1.84	1.60 3.46	1.75	2.22	6. 77.	11.94
Pool Elevation (BDM) Maximum Minimum	4872.43 4872.64 4872.43	4875.03 4875.03 4872.30	4878.55 4878.64 4875.21	4878.62 4878.80 4878.43	4879.96 4879.96 4878.50	4880.83 4881.07 4880.11	4879.24 4880.79 4879.24	4876.44 4879.04 4876.44	4875.66 4876.37 4875.66	4863.74 4875.54 4863.74	4852.46 4863.30 4852.46	4851.24 4852.34 4851.24	
Pool Conternt (BDM) (1000 Ac-Ft)	228.85	239.99	255.65	255.97	262.11	266.14	258.80	246.19	242.75	194.23	154.70	150.78	
IRINIDAD LAKE	<b>5</b> 5	Š	DBC	JAN	82	MAR	AFR.	MAY	JÜN	JE	AUC	SE	TOTAL
Inflows (1000 Ac-Ft) Avg 1896 thru 1988 FY 1988	2.37	1.70	1.51	1.30	1.23	1.61	4.29	10.96	13.21 5.48	10.16 5.92	8.47	3.72	57.27 30.32
Releases (1000 Ac-Ft) Avg 1978 thru 1988 FY 1988	1.73	84.	.25	.18	22.	.21 .19	1.98	9.60	13.97	12.63	10.54	9.33 6.95	61.10 55.71
<b>Rainfall (Inches)</b> Avg. 1978 thru 1988 FY 1988	.98 .37	8. 8.	.68 1.14	.52 .57	<b>2</b> ; 8;	1.21	1.39	3.03	2.33	2.24	3.35 1.65	1.42	18.78 16.55
Pool Elevation (ECM) Maximum Minimum	6209.72 6209.72 6208.76	6210.31 6210.31 6209.52	6211.29 6211.29 6210.35	6212.24 6212.24 6211.30	6213.18 6213.18 6212.25	6213.92 6213.92 6213.21	6214.87 6214.87 6213.97	6206.51 6214.93 6206.51	6198.74 6206.19 6198.64	6193.28 6198.67 6193.28	6180.18 6193.04 6180.18	6173.58 6179.63 6172.20	
Pool Content (ECM) (1000 Ac-Ft)	46.51	48.37	97.67	\$0.54	51.61	52.47	53.59	44.34	36.87	32.03	21.87	17.66	

### ARCANGAS RIVER BASTIN

# JOHN PARTIN RESIDENCIE

TOTAL	76.6	68.4 6.4.8	31.84 19.98 -11.85				TOTAL	2128.5 1052.9	2309.5	30,80 18,88 -11,92		
SEP	5.50	0.71	3.80	1337.23 1337.83 1337.23	143.29		SEF	141.41	94.41	3.58 0.93 -2.65	1010.06 1011.79 1009.83	429.64
AUG	3.40	1.21	3.18 3.50 0.32	1337.83 1 1338.64 1 1337.83 1	147.84		AUG	131.96 33.62	81.84 23.55	3,17	1009.93 1011.05 1009.90	427.42
חחר	7.40 5.48	2.70	3.65	1338.64 1338.87 1338.52	154.16		JUL	239.71 78.64	239.24 69.98	3.50 2.59 -0.91	1010.01 1011.04 1009.96	428.77
חחר	14.40	6.72	4.84 1.19 -3.65	1338.58 1339.11 1338.56	153,69		NOU	342,30 69,12	325.13 57.72	4,44 1,23 -3,21	1010.08 1010.11 1009.93	429.98
MAY	11.80	8.54 4.40	4,34 1,12 -3,22	1339,11 1339,40 1338,92	157,89		¥ B ¥	301.29	246.28 229.75	4,29	1010.03 1013.45 1009.20	429.12
AFR	10.20	12,08	2.91 4.27 1.36	1339,36 1340,22 1337,64	159.92		AFR	249.25 584.33	355.75 508.12	2.86 3.79 0.93	1013.33 1023.54 1009.45	488.17
E A A	6.20	6.17	1.96	1337.64 1337.92 1337.09	146.40	NISON	HAR	171.76	283.26 229.28	1.88 1.38 -0.50	1009.45 1013.46 1007.52	419.36
FEB	2.80	2.17	0.08	1337.09 1337.12 1337.03	142.23	RIVER	F	96.99	105.27 125.50	1,03 0,16 -0,87	1007.58 1009.08 1007.36	388.66
24%	2.70	2,52	08.0 08.0 08.0	1337,09 1337,60 1336,95	142.23	ARKANSAS	NAC	85.12 211.83	119.72 363.98	0.87 0.28 -0.59	1009.08 1017.75 1009.06	413,14
BEC	2.80 9.28	6.66	1.14	1337.60 1338.51 1337.60	146.10		DEC	84.51	103.09	1.13	1017.20 1017.20 1010.80	564.26
>0 %	4.0	3.39	1.67	1338,15 1338,33 1338,11	150.31		200	125.65 91.04	154.45	1.66	1011.20 1011.23 1009.78	449.46
OCT	5.00	16.00	2.49	1338,32 1338,75 1338,30	151.65		00.1	158.53	201.06	2,39 1,22 -1,17	1010.06 1010.51 1009.88	429.64
ELDORADO	INFLOWS(1000AC.FT.) AUG 1921 THRU 1978 FY 1988	RELEASES(1000AC.FT.) AUG 1983 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF HONTH MAXINUM HINIHUM	FOOL CONTENT-EOM (1000AC.FT)	VII-6	KAW LAKE	INFLOWS(1000AC.FT.) AUG 1922 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AUG 1977 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF HONTH MAXIMUM HINIMUM	FOOL CONTENT-EOM (1000AC.FT)

TOTAL	283.5 420.3	319.1	24.47 13.38 -11.09				TOTAL	4664.2 6063.6	5035.7 5969.3	30.24 23.84 -6.40		
SEP	19.10	11.23	2,39 1,01 -1,38	1124.40 1124.62 1124.21	26.53		SEF	328.51 272.43	198.90	3.40 4.95 1.55	722.07 723.93 717.91	536.06
AUG	21.24	5.61	2.89 1.94 -0.95	1124.53 1 1125.37 1 1124.53 1	27.59		AUG	283,50 56,13	183.24	2.99 1.83 -1.16	719.25 721.51 719.25	475.08
אטר	22.56 16.36	23.40	2.54 1.83 -0.71	1125.27 1 1125.52 1 1124.90 1	33.92		JUL	466.47	463.65	3.14 2.69 -0.45	721.43 732.12 721.43	521.67
NOL	45.26	55.55 19.88	3.57	1125.16 1126.05 1125.08	32.90		NOL	738.79	713.86	4.16 1.46 -2.70	722.70 724.26 722.68	550.65
Æ ≻	33.12	56.51 36.88	3.71 0.81 -2.90	1125.62 1126.47 1125.26	37.17		Æ	752.88 463.34	675.59 492.56	4,41 1,05 -3,36	723.96 725.47 721.30	580,72
APR	31.69	41.01	2.35 2.68 0.33	1126.47 1128.49 1125.56	45.63		A F R	536.34 1711.14	682,35 1670,37	2.87 4.74 1.87	725.47 739.18 724.32	618.89
Æ A A	21.07	38,51	1.52 1.58 0.06	1125.58 1127.26 1125.30	36.80	BASIN	# APR	336.81 1119.67	586.61 1050.37	1.87 3.07 1.20	724.32 731.96 721.53	589,68
r R	13,13	14.77	0.00	1125.47 1125.68 1125.35	35.78	RIVER	FEB	194.73 284.83	226.89 421.95	1.15 0.13 -1.02	721.67 727.66 721.67	527,05
Z V	9.23	11.15	0.69	1125.67 1126.18 1125.38	37.64	arkansas	NAL N	167.90	228.06 831.89	0.97	727.66 731.84 727.66	677.93
DEC	9.13	11.21	0.84	1125.61 1125.92 1125.27	37.08		DEC	175.45 522.64	220.96	1.18	731.63 731.63 723.24	796.17
20	15.25	22.43 12.82	0.25	1125.51 1125.57 1125.18	36.15		202	288.16 192.40	307.50	1.72 1.59 -0.13	724.48 724.48 721.35	593,68
100	21,23	27.72	1.87	1125.37 1127.52 1125.31	34,85		00.1	394.68 377.26	548.13 400.96	2.38 0.66 -1.72	721.35 724.92 721.03	519,88
GREAT SALT PLAINS LAKE	INFLOWS(1000AC.FT.) AUG 1923 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AVG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF HONTH MAXIMUM HINIMUM	POOL CONTENT-EOM (1000AC.FT)	VII-7	KEYSTONE LAKE	INFLOWS(1000AC.FT.) AUG 1923 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AUG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF MONTH MAXIMUM HINIMUM	FOOL CONTENT-EOM (1000AC.FT)

TOTAL	4.65 4.4	46.6 55.1	34.77 35.39 0.62				TOTAL	314.9	334.9	35.02 25.19 -9.83		
SEP	3.77	0.56	3.99 4.47 0.48	761.85 762.03 760.91	7.42		SEP	23.24	8.77	4.28 1.48 -2.80	900.90 901.32 900.89	19.45
AUG	1.53	0.00	2.98 1.79 -1,19	761.16 761.46 760.96	6.81		AUG	9.13	10.10	3.36 4.47 1.11	901.32 902.00 901.32	20.55
JUL	1.02	0.68	3.12 5.91 2.79	761.46 761.77 760.00	7.08		JUL	34.79	16.96 13.40	3.88 3.57 -0.31	902.00 904.89 901.17	22.36
אחר	7.59	5.57	4.32 0.73 -3.59	761.01 761.60 761.01	89.9		30%	52.97	55.47	5.05 0.58 -4.47	901.17 901.56 901.13	20.15
AAY	7.82	10.02	1.25	761.60 761.83 761.60	7.20		MAY	40.55	33.98	4,63 1,23 -3,40	901.50 901.88 901.45	21.03
A የ	6.15	5.57	3.51 3.63 0.12	761.83 769.26 761.83	7.40		APR	46.42	58.11 164.11	3.23 4.45 1.22	901.68 924.18 901.62	21.51
HAR	3,24	7.76	2.33 6.29 3.96	763.85 767.26 761.77	9.43	RAS] N	MAR	32.04	46.01 68.62	2.42 2.06 -0.36	902.30 909.95 901.37	23.20
FER	1.92	4.70	1.54 0.86 -0.68	761.79 762.22 761.70	7,37	RIVER	FER	13,35 8,92	22.12	1.05	901.67 901.95 901.52	21.48
ZAZ	1.30	2.30	1.43	761.80 762.48 761.59	7.38	ARKANSAS	A A	12,33	10.10	1.05	901.89 904.41 901.62	22.07
DEC	1.50	2.97	1.49 3.67 2.18	762.24 765.48 761.64	7.78		DEC	11.46	18.22 69.66	1.31	904.41 912.89 901.59	29.35
NON	2.65	2.60	2.27 4.57 2.30	761.88 762.45 760.71	7.45		NON	18.97 19.28	23,45 13,33	2.05	903,73 904,59 901,54	27.29
130	2.44 0.08	3.81	2.84 1.11 -1.73	760.79 761.15 760.73	6.51		100	19.64 1.08	31.02	2.71 2.99 0.28	901.62 901.89 901.42	21.35
HEYBURN LAKE	INFLOMS(1000AC.FT.) AUG 1929 THRU 1981 FY 1988	RELEASES(1000AC,FT,) AUG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF HONTH HAXIMUM HINIMUM	POOL CONTENT-EOM (1000AC.FT)	VII-8	TORONTO LAKE	INFLOWS(1000AC.FT.) AUG 1922 THRU 1981 FY 1988	RELEASES(1000AC,FT,) AUG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 REVIATION	FOOL ELEVATION END OF MONTH MAXIMUM HINIMUM	FOOL CONTENT-EOM (1000AC.FT)

TOTAL	227.9	257.1 286.8	33.00 28.45 -4.55				TOTAL	257.0 359.8	337.7	35.48 32.66 -2.82		•
SEP	15.10	3.17	4.03 0.88 -3.15	947,98 948,51 947,96	20.70		SEF	14.88 10.88	5.97	4.33 4.63 0.30	795.96 796.52 793 97	45.98
AUG	6.26	5.15	3.10 4.73 1.63	948.51 949.11 948.51	21.95		AUG	5,05	9.53	3.15 2.67 -0.48	794.31 794.53 793.93	39,58
JUL	18.32	20.01	3,69	949.00 949.08 948.44	23,10		JUL	21.54	46.98	3.63 4.98 1.35	794.30 794.33 793.57	39.54
NUC	37.93	41.81	4,86 0,97 -3,89	948.44 948.81 948.40	21.78		NUC	42.54 1.53	47.52	5,10 0,86 -4,24	793.65 794.01 793.65	37,12
¥ ¥	33,38 11,11	31.77	1.57	948.81 949.68 948.57	22.65		æ ¥	40.68	34.68	4:71	793.95 794.55 793.95	38.23
AFF	36,26 128,28	45.54	3.11 5.63 2.52	949.61 968.37 949.17	24.66		AFR	41.73	42.42	3,45	794.26 815.47 794.03	39,39
ÄAŘ	23.68 51.47	34.51	2.17 2.46 0.29	949.54 953.63 948.57	24.48	BASIN	MAR	25.74	42.51 56.16	2.33 3.10 0.77	796.40 799.45 793.94	46.58
FEB	10.09 B.46	16.18 8.08	1.04	948.77 949.08 948.47	22.56	RIVER	FER	9,80 6,88	16.93	1.17	793.97 794.24 793.95	36.29
JAN	9.31 25.21	9.26	0.95	948.70 952.06 948.53	22.39	ARKANSAS	JAN	10.18	16.02	1.23 0.37 -0.86	794.24 797.83 794.00	37,37
DEC	8.25 49.45	12.42	1.23	952,06 956.85 948.62	31,58		DEC	8.53 .42	15.99	1.35	797.83 803.05 796.06	53,31
NO N	14.09	16.51	1.76 2.88 1.12	949.76 949.90 948.49	25.04		20%	17.90	20.20	2,22 3,47 1,25	796.56 796.64 793.77	47.31
OCT	15.23	20.74	2.61 2.68 0.07	948.86 948.86 948.62	22.77		OCT	18.46 0.88	40.25	2.81 1.46 -1.35	793.87 794.05 <b>793.77</b>	35.90
FALL RIVER LAKE	INFLOWS(1000AC.FT.) AUG 1922 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AVG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF MONTH MAXIMUM MINIMUM	FOOL CONTENT-EOM (1000AC.FT)	VII-9	ELK CITY LAKE	INFLOWS(1000AC.FT.) AVG 1922 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AVG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF MONTH MAXIMUM MINIMUM	FOOL CONTENT-EOM (1000AC.FT)

TOTAL	19.4	14.4	39,13 39,24 0,11				TOTAL	1906.8 2529.0	2172.7 2478.0	37.89 29.82 -8.07		•
<u>ه</u> ص	1.33	0.57	4.80 5.86 1.06	856.99 856.99 856.20	25.94		SEP	107.14	42.77	4.59 5.29 0.70	635.69 635.72 634.43	487,95
AUG	0.27	0.00	3.33 2.86 -0.47	856.57 857.02 856.57	25.55		AUG	51.80	47.81	3.31 2.50 -0.81	634.86 635.47 634.84	465.67
JUL	1.73	0.30	3.84 0.24	857.02 857.32 857.02	26.06		JUL	163.74 26.35	228.86 0.80	3.61 3.22 -0.39	635.47 635.53 634.95	482.03
NO.	3.60	1.29	5.67 2.20 -3.47	857.23 857.57 857.12	26.31		JUN	290.68 6.72	255.48 5.37	5.22 0.59 -4.63	635.30 636.17 635.29	477.46
¥A¥	3.13 0.08	2.61	1.46	857.57 857.90 857.57	26.71		¥ A Y	289.73 57.42	218.48 158.05	5.03 1.19 -3.84	636.10 640.01 636.00	499.13
APR	2.30	3.41	3.80 8.02 4.22	857.90 862.52 857.90	27.10		APR	276.30 1061.16	356.89 1051.01	3.70 5.52 1.82	640.01 649.34 640.01	614.47
HAR	1.69	3.39	2.4.4 2.1.5 3.1.5 5.4.5 5.4.5	860.45 860.45 857.82	30.20	RASIN	MAR	179.83	319.12 390.28	2,58 3,44 0,86	640.08 643.46 637.74	616.69
77 73 74	0.67	2.70	1.33	857.83 857.92 857.70	27.01	RIVER	FEB	84.20	120.24	1,33 0,41 -0,92	638.05 641.50 638.01	554.92
NAU	1.05	0.62	1.48 0.55	857.85 858.24 857.83	27.04	ARKANSAS	JAN	91.90	111.15	1.45	641.48 646.57 641.35	661.62
DEC	0.75	1.22	3.24 4.75 4.75	858.24 858.85 857.71	27.50		DEC	80.40 407.70	131,19	1.51	646.57 646.57 637.92	840.66
20 %	1.19	1.52	2.50	857.82 857.91 856.95	27.00		>0x	138,22	157.95 28.44	2.42 3.69 1.27	640.93 641.26 637.34	643.74
00.1	1.69	4.43	3.15 1.46	857.13 857.48 857.10	26.19		001	152.90	182.79	3,14 1,78 -1,36	637.58 638.07 637.38	541,34
BIG HILL	INFLOWS(1000AC.FT.) AUG 1929 THRU 1978 FY 1988	RELEASES(1000AC.FT.) AUG 1984 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF HONTH HAXIMUM HINIMUM	POOL CONTENT-EOM (1000AC.FT)	VII-10	OOLOGAH LAKE	INFLOWS(1000AC.FT.) AUG 1923 THKU 1981 FY 1988	RELEASES(1000AC.FT.) AUG 1974 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION ENT OF HONTH MAXIMUM MINIMUM	FOOL CONTENT-ECH (1000AC.FT)

TOTAL	36.5	31.7	34.93 30.89 -4.04				TOTAL	133.0 212.3		34.74 :8.80		
SEP	1.95	0.30	4.25 7.82 7.57	750.78 750.87 748.22	19.50		SEP	12.37		4.19 7.68 3.49	703.19 703.31 702.20	A7.500
AUG	0.02	0.29	3.29 1.43 -1.86	749.38 750.80 749.38	17.93		AUG	4.09 0.38		3.25 1.37 -1.88	702.83 704.31 702.63	110,81
JUL	1,78	1.05	3.16	750.80 750.86 749.15	19.52		JUL	10.64		3.24 2.85 5.69	704.31 704.37 703.50	00.585
NUL	3,12	3.79	1,22	749.69 750.52 749.69	18.27		NOC	16.19		4.38 0.66 -3.72	704.35 705.55 704.35	232,34
¥A¥	5.61	5.29	5.00	750.29 750.63 750.29	18.95		Æ	28.43		4.83 1.19 4.64	705.55 706.16 705.55	
A A A	3.18	3.86	. 4	750.63 758.04 750.50	19.33		AFR	15.35 69.11		3,30 3,98 0,68	706.16 711.99 706.16	247.85
MAR	3.02	5.22 5.82	2.43 2.74 0.31	752.20 753.38 750.07	21.16	FASIN	HAR	12.59 41.22		2.37	706.72 708.52 705.92	252.79
F E	0.96	2.14	1.33	750.52 750.82 750.51	19.21	RIVER	FER	4. 28		1.36 0.49 -0.87	706.08 706.33 705.92	247.14
JAN	0.96	1.62	1.27	750.57 751.62 750.50	19.26	ARKANSAS	NAU.	3.61		1.37 0.75 -0.57	706.07 706.11 704.56	246.61
pec	1.02	1.99	1.43 2.17 0.74	751.37 754.66 750.47	20.18		DEC	3.91		1.41 2.12 0.71	704.56 704.56 698.97	234.11
) 0 8	1.65	1.92	2.16 3.68 1.52	751.01 751.34 749.94	19.76		20%	8.09 10.96		2.21 4.07 1.86	699.76 699.98 698.59	195,82
100	2.40	5.42	2.78 1.00 -1.78	750.20 754.64 750.20	18.84		00.1	13.47		2.88 1.15 -1.73	698.80 760.79 698.73	188.66
BIRCH LAKE	INFLOWS(1000AC.FT.) AUG 1936 THRU 1979 FY 1988	RELEASES(1000AC.FT.) AVG 1979 THRU 1988 FY 1988	RAINFALL (INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF MONTH MAXIMUM HINIMUM	FOOL CONTENT-EOM (1000AC.FT)	V11-12	SKIATOOK LAKE	INFLOWS(1000AC.FT.) AUG 1935 THRU 1979 FY 1988	RELEASES(1000AC.FT.) LANE HAS NOT FILLED	FAINFALL(INCHES) AUG 1930 IHRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF MONTH MAXIMUM MINIMUM	FOOL CONTENT FOM

JOHN REDMOND DAM AND	RES OCT	) 0 2	DEC	NA N	FEB	æ Æ Æ	APR	¥ A ¥	NUC	JUL	AUG	SEP	TOTAL
INFLOWS(1000AC.FT.) AUG 1922 THRU 1981 FY 1988	71.02	55.44	38.04	36.84 48.10	40.33	87.60	126.29 248.13	136.01	165.24	118.01	39.59	70.27	984.7
RELEASES(1000AC.FT.) AUG 1976 THRU 1988 FY 1988	81.63	72.63	54.45	30.62 80.40	57.24 22.86	127.09 42.78	170.97 246.02	140.92 38.98	164.17 15.54	132.60	36.06	39.98	1108.4
RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	2.53 -0.42	1.69	1.18	0.90	0.96	2.06	2.99 3.11 0.12	4.44 1.66 -2.78	4,89	3.82 3.04 -0.78	Б 4 н 4 6 4 4	1.35	33.00 20.08 -12.92
POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	1040.29 1040.29 1038.97	1042.77 1042.85 1040.29	1042.05 1047.12 1041.51	1039.08 1042.23 1038.89	1039.11 1039.19 1038.87	1039,43 1039,91 1038,90	1039.23 1052.08 1038.91	1039.18 1039.64 1038.98	1039.05 1039.18 1038.68	1039,26 1039,73 1039,05	1038.22 1039.26 1038.22	1037.73 1038.22 1037.56	
POOL CONTENT-EOM (1000AC.FT)	83.63	110.04	101.94	72.04	72.32	75.34	66.50	66.01	64.74	66.80	56.75	52,21	
VII-15				ARKANSAS	RIVER	BASIN							
FENSACOLA LAKE	100	NON	DEC	NA.	FER	MAR	AFR	MAY	NOC	JUL	AUG	SEP	TOTAL
INFLOWS(1000AC.FT.) AVG 1923 THRU 1981 FY 1988	322.60 62.28	323.22 622.91	236.46 1363.74	249.34 467.90	281.52 298.11	462.47 861.82	648.79 1519.93	692.47 162.05	729.00	403.86 160.46	171.64 56.13	260.79	4782.2 5766.1
RELEASES(1000AC.FT.) AVG 1976 THRU 1988 FY 1988	405.14 59.07	428.53 335.93	416.84	293.84 820.07	368,34 342,29	652.83 618.58	781.33	499.27	502.91	443.36	211.13 80.79	191.48	5195.0
RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	3.39 2.12 -1.27	2.71 4.25 1.54	1.89	1.73 0.37 -1.36	1.73	2.0 3.34 3.4 3.4	4.02 3.73 -0.29	5.15 0.97 -4.18	5.26 1.51 -3.75	3.58	3.39	4.64 5.36 0.72	40.40 30.42 -9.98
FOOL ELEVATION END OF MONTH MAXIMUM MINIMUM	740.17 740.34 739.90	746,44 747.83 739.80	749.47 750.96 742.39	741.87 749.47 741.87	740.70 741.87 740.63	745.86 746.10 740.46	744.00 749.57 744.00	742.66 744.00 742.37	742.29 742.83 742.17	742.49 742.83 742.29	741.44 742.49 741.41	742.58 742.80 741.00	
FOOL CONTENT-EDM (1000AC,F1)	1459.14	1459.14 1740.12	1889.97	1531.41	1481.40	1712.42	1626.00	1566.04	1549.76	1558,56	1512.92	1562.52	

. TOTAL	1 5351.4 3 6439.3	5999.0	42.40 3 30.06 2 -12.34	p 10-01	<b></b>		YOTAL	5937.3	6443.3	41.36 34.94 -6.42		
SEP	292.51 92.53	205.87 92.13	4.66 4.98 0.32	619.17 620.15 618.92	202.18		SEP	323.89 88.07	197.67 88.70	4.39 5.49	554.18 554.89 553.80	368.67
AUG	232.23	214.65	3,42 1,87	619.49 619.93 619.21	205.71		AUG	248.96 70.26	206.42 52.14	3.21 1.68 -1.53	554.56 554.87 553.82	376.01
300	469.55	470.24	3.23 1.49 -1.74	619.71 619.93 619.09	208.15		JUL	507.86 124.58	514.73	3.05	554.10 554.97 553.94	367.13
חחר	797.85 74.18	616.78 66.60	5.21 0.51 -4.70	619.51 619.83 618.97	205.94		NDC	880.74	636.67	5.12 0.88 -4.24	554,11 554,70 553,85	367,32
¥	798.60 220.17	588.92 212.43	5.47 1.13 -4.34	619.41 619.58 618.92	204.83		¥A¥	887.79 224.13	637.25 214.24	5.40 1.54 -3.86	554.04 554.36 553.06	365.97
APR	703.76 1784.63	945.43 1802.38	4.26 3.23 -1.03	619.14 626.91 618.92	201.85		AFR	797.48 1895.11	1032.30	4.26 2.52 -1.74	554,00 568,63 554,00	365.20
# 4 %	493.77	7 <b>64.</b> 89 764.11	3.16 4.89 1.73	621.08 621.71 614.31	223.68	ASIX	ች ያ	546.77 969.52	858.74 904.22	2.32 4.45 2.32	558.30 559.21 553.56	453.72
FER	316.68	424.89	2.08	619.63 620.19 618.93	207.26	RIVER BASIN	FEB	355.69 407.21	393.29 412.27	2.13	555.51 555.90 553.32	394.70
247	277.65	346.02	1.94	618.93 626.03 618.53	199,55	ARKANSAS	247	312.54 1042.11	407.43	1.97 0.77 -1.20	555.90 570.08 554.04	402.50
DEC	276.23	489.36	3.22	626.03 627.32 618.80	285,63		DEC	305.41	543.71	2.16 4.47 2.31	570.08 571.95 553.68	780.27
> 0 X	326.50 428.83	494.14	3.02 5.03	619.82 621.57 618.52	209.36		NON	377.51 524.73	514.58 430.44	2.90 2.95	558,35 559,02 553,51	454.84
100	366.07	437.79	3.78 2.45 -1.33	619.47 619.58 618.63	205.49		100	392.66	500.51	3.63 2.40 -1.23	553.94 554.51 553.12	364.08
LAKE HUDSON	INFLOWS(1000AC.FT.) AVG 1923 THRU 1981 FY 1988	RELEASES(1000AC,FT,) AVG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	PGOL CONTENT-EOM (1000AC.FT)	VII-16	FORT GIRSON LAKE	INFLOWS(1000AC.FT.) AUG 1923 THRU 1980 FY 1988	RELEASES(1000AC.FT.) AUG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AVG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF MONTH HAXIMUM MINIMUM	FOOL CONTENT-EOM (1000AC.FT)

UN JUL AUG SEP TOTAL	12 1593.36 687.71 627.23 14837.0 17 313.59 181.29 346.31 21651.6	63 1342.10 477.21 483.24 17353.7 05 307.67 189.89 340.69 21615.7		09 3.01 2.94 4.21 39.61 19 4.58 1.65 5.65 33.92 90 1.57 -1.29 1.44 -5.69	9 3.01 2.94 4.21 39.6 9 4.58 1.65 5.65 33.9 0 1.57 -1.29 1.44 -5.6 8 489.96 488.77 488.84 1 490.71 490.27 490.33 4 489.50 488.77 487.32	9 3.01 2.94 4.21 39.6 9 4.58 1.65 5.65 33.9 0 1.57 -1.29 1.44 -5.6 1 490.71 490.27 490.33 4 489.50 488.77 487.32 8 169.65 156.25 157.01	9 3.01 2.94 4.21 39.6 4.58 1.65 5.65 33.9 0 1.57 -1.29 1.44 -5.6 1 490.71 490.27 490.33 4 489.50 488.77 487.32 - 169.65 156.25 157.01	9 3.01 2.94 4.21 39.6 4.58 1.65 5.65 33.9 0 1.57 -1.29 1.44 -5.6 1 490.71 490.27 490.33 4 489.50 488.77 487.32 8 169.65 156.25 157.01	9 3.01 2.94 4.21 39.6 4.58 1.65 5.65 33.9 0 1.57 -1.29 1.44 -5.6 8 489.96 488.77 487.32 4 489.50 488.77 487.32 8 169.65 156.25 157.01 N JUL AUG SEP TOTA 9 53.49 40.27 35.47 1129. 3 21.03 10.74 12.46 1442.	9 3.01 2.94 4.21 39.65 9 4.58 1.65 5.65 33.99 1.57 -1.29 1.44 -5.65 1 490.71 490.27 490.33 4 489.50 488.77 487.32 8 169.65 156.25 157.01 N JUL AUG SEP TOTA 9 53.49 40.27 35.47 1129. 3 21.03 10.74 12.46 1442. 5.22 31.89 7.27 1425.	9 3.01 2.94 4.21 39.65 4.58 1.65 5.65 33.99 1 489.96 488.77 488.84 1 490.71 490.27 490.33 4 489.50 488.77 487.32 8 169.65 156.25 157.01 8 169.65 10.74 12.46 1442. 9 53.49 40.27 35.47 1129. 9 53.49 40.27 35.47 1129. 9 53.49 40.27 35.47 1425. 9 53.29 41.98 26.61 933. 9 3.15 3.29 4.32 43.6 1.79 1.91 2.79 24.56. 1.79 1.91 2.79 24.56.	9 3.01 2.94 4.21 39.4 4.58 1.65 5.65 33.1 1.57 -1.29 1.44 -5.3 1.490.71 490.27 490.33 4.489.50 488.77 487.32 4.489.50 488.77 487.32 8 169.65 156.25 157.01 8 169.65 156.25 157.01 9 53.49 40.27 35.47 1129 9 53.49 40.27 35.47 1129 9 53.49 40.27 35.47 1429 1.79 1.91 2.79 24.32 1.79 1.91 2.79 24.32 1.79 1.91 2.79 24.39 1.79 1.91 2.79 24.39 1.79 1.91 2.79 24.39 1.79 1.91 2.79 24.39 1.79 1.91 2.79 24.39 1.79 1.78 -1.53 -19.30 1.70 6.29.10 629.14 1.70 6.29.10 629.15 1.70 6.29.10 629.15
HAY JUN	50.06 1996.12 1	053.92 2089.63 1 168.50 284.05	5.28 5.09	.73 -3.9	3,73 -3,90 0,02 489,98 0,35 490,31 8,78 468,34	-3.73 -3.90 90.02 489.98 90.35 490.31 88.78 488.34 70.35 169.88	-3.73 -3.90 90.02 489.98 90.35 490.31 88.78 488.34 70.35 169.88	70.35 169.88	70.35 169.88 70.35 169.88 70.35 169.88 70.35 169.88	HAY JUN 119.59 43.83 20.83 92.94 9.89	90.02 489.98 90.35 490.31 88.78 488.34 70.35 169.88 70.35 169.88 92.94 119.59 92.94 72.93 92.94 9.89 1.10 0.69	90.02 489.98 90.35 490.31 88.78 488.34 70.35 169.88 70.35 169.88 43.83 20.83 92.94 72.93 92.94 9.89 1.10 0.69 -4.55 -4.20 330.08 630.4H
AFR	1905,47 23 6346.71 11	2630.88 20 6343.41 11	4.26 2.18 -2.08		490.17 490.84 489.88	90.17 90.84 89.88 72.17	90.17 90.84 89.88 72.17	90.17 90.84 89.88 72.17	90.17 90.84 89.88 72.17 72.17	90.17 90.84 89.88 72.17 72.17 74.34 02.91	90.17 90.84 89.88 89.88 72.17 72.17 74.34 02.91 66:19 4.59	900.17 90.17 90.84 89.88 90.84 72.17 72.17 72.17 66.19 66.19 66.19 66.19 66.19 66.19 66.19
# AAR	1291.80 3682.51	2336.13	2.12		490.24 490.51 488.92	490.2 490.5 488.9	490.2 490.5 488.9 173.0	490.5 488.9 173.0 173.0	490.2 488.9 173.0 173.0 136.7	490.2 488.9 173.0 173.0 136.7 337.7	8ASIN 173.03 173	490.2 488.99 173.00 173.01 136.7 337.7 337.7 337.7 3 337.7 110.2 2 2 8 .8 6 3 9 .1 6 3 9 .1
FEB	751,95	985.61	2.12 0.80 -1.32		489.67 490.56 488.85	489.6 490.5 488.8 166.3	489.67 488.85 488.85 166.35	489.67 490.56 488.85 166.35 RIVER	489.67 490.56 488.85 166.35 FER FER 68.92	489.67 490.56 488.85 166.35 166.35 68.92 56.36	489.67 490.56 488.85 166.35 97.10 68.92 56.36 105.22 105.22	489.67 490.56 488.85 166.35 97.10 68.92 56.36 105.22 105.22 5.66 631.35 631.35
JAN	668.85 3522.05	3517.86	1.41		490.07 490.74 489.57	490.0 490.7 489.5 170.9	490.0 490.7 489.5 170.9					
DEC	732.82 3218.18	3216.27	3.72		499.88 450.85 468.97	489.8 450.8 468.9	4899.88 458.9 458.9 168.7	4 5 8 9 9 8 8 8 9 9 8 8 9 9 8 8 9 9 9 8 8 9 9 9 8 8 9 9 9 8 9	489.8 468.9 168.7 168.7 76.1	469.88 458.97 168.77 76.11 96.8	4 4 3 5 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	46.99 46.98 44.3.5 46.93 46.99 5.00 6.00 6.00 6.00 6.00 6.00 6.00 6.00
20.2	1067.84 875.31	1299.28 871.81	2.83 3.93 1.10		489.90 490.54 489.13						क्रक न	8 4 4 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
10CT	1163.75	1524.88 555.06	3.41 2.66 -0.75		489.81 490.54 488.95	489.81 490.54 488.95 167.95	489.81 490.54 488.95 167.95	489.81 490.54 488.95 167.95	488.95 488.95 167.95 167.95 22.66	विवर न	444 -	444
WERRERS FALLS LED	INFLOWS(1000AC.FT.) AUG 1940 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AVG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AVG 1930 THRU 1980 FY 1988 DEVIATION		POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	POOL ELEVATION END OF MONTH MAXIMUM MINIMUM FOOL CONTENT-EOM (1000AG.FT)	FOOL ELEVATION END OF MONTH MAXIMUM HINIMUM FOOL CONTENT-EOM (1000AC.FT)	POOL ELEVATION END OF MONTH MAXIMUM PIOL CONTENT-EOM (1000AC.FT) L1 L1 TENKILLER LAKE	FOOL ELEVATION END OF MONTH MAXIMUM FOOL CONTENT-EOM (1000AC.FT) L1	.FT .19	.FT. 198 198 198	.FT. 198 198 198

		SCI	NO.	DBC	JAN		5	<b>A</b>	AFR	H	JUN	JOE	AUC	<b>2</b> 28	TOTAL
Avg 1940 thru 1988 FY 1988		9.70	3.84	3.66	3.80		4.18	4.30	15.69 5.29	3.85	24.06 12.72	8.23 13.88	27.67 14.82	20.94 17.35	170.64 87.82
Releases (1000 Ac-Ft) Avg 1941 thru 1988 FY 1988		8.28 10.25	1.89	1.61	æ. æ.		1.05	2.39	14.5 <b>8</b> 7.42	18.42 10.29	15.57 6.44	17.64 10.32	18.08 15.51	19.82	119.98 66.19
Rainfall (Inches) Avg 1940 thru 1988 FY 1988		1.07	.98 .90	<b>3</b> . 8.	*; 13		0 0		.86	1.63	1.67	2.38	2.42	1.33	13.66 19.26
Pool Elevation (BCM) Maximum Minimum	4197.98 4199.40 4197.98		4197.75 41 4197.73 41 4197.72 41	4197.98 4197.99 4197.75	4198.20 4198.18 4197.98	4198.43		4198.18 4198.46 4198.18	4197.27 4198.20 4197.27	4195.90 4197.21 4195.90	4196.07 4196.34 4195.51	4195.97 4196.65 4196.05	4195.68 4195.90 4195.39	<b>4196.78</b> <b>4196.84</b> 4195.70	
Pool Content (BDM) (1000 Ac-Ft)	301	301.90 29	299.84 3	301.90	289.71		291.78	289,53	281.49	269.66	271.10	270.25	267.80	277.18	
VII-18				ARKANSAS		RIVER BA	BASIN								
SANFORD RESERVOIR	100	202	DEC		NAU	FER	H RAR	AFR	MAY	NOL	Jul.	AUG	SEP	TOTAL	
INFLOWS(1000AC.FT.) AUG 1923 THRU 1981 FY 1988	21.36	3.42	1.97		3,18 3,25	2.09	2.58	11.47	35.88 15.20	38.51 35.76	37.66	35.93 5.93	30.86 36.81	224.9 151.2	
RELEASES(1000AC,FT.) LAKE HAS NOT FILLED															
RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 REVIATION	1.32 0.96 -0.36	0.60 0.22 -0.38	0.49 0.31 -0.18	0.45	45 33 -	0.48	0.68	1.14	2.52 2.83 0.31	2.36 2.98 0.62	2.68 2.46 -0.22	2.48 1.66 -0.82	1.62 4.36 2.74	16.82 17.37 0.55	
POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	2898.25 2899.04 2898.25	2897.63 2898.27 2897.62	2897.34 2897.63 2897.33	4 2897.10 3 2897.34 3 2897.10		. 11 . 68	2896.35 2896.77 2896.35	2896.39 2896.60 2896.27	2896.75 2896.75 2895.79	2899.14 2899.19 2896.75	2901.25 2901.62 2899.10	2900.37 2901.25 2900.27	2903.05 2903.06 2900.1%		
FOOL CONTENT-EOM (1000AC.FT)	339.33	333.49	330,77	7 328.52		324.63	321,59	321.95	325.28	347.82	368.47	359.77	386.72		

TOTAL	56.5 89.4	54.7	33.67 32.77 -0.90				TOTAL	31.2		16.52 10.92 -5.60		
SEP	2.40	00.0	3.48 3.00 0.00	1037.15 1037.19 1036.53	108.67		SEP	3.30		1.62 2.92 1.30	2717.40 2717.55 2715.82	2.71
AUG	0.70	0000	2.60	1036.97 1 1037.77 1 1036.97 1	107.63		AUG	3.36		2.41 0.94 -1.47	2715.85 2716.70 2715.80	1.82
JUL	4.40 0.56	1.54	2,70	1037.77 1038.54 1037.77	112.27		10L	3.77		2.18	2716.70 2717.05 2712.05	2.28
אַחר	3.89	6.76	4.35 3.51 -0.84	1038.54 1038.85 1038.35	116.84		NOC	6.75		2,25 0,88 -1,37	2712.30 2712.95 2712.30	09.0
# Y	13.70	2.63	5.50 0.52 -4.98	1038.75 1039.44 1038.73	118,10		¥ Æ	5.60		2.64 1.98 -0.66	2712.95 2713.50 2712.90	0.75
APR	9.50	6.69	3,48	1039.44 1044.36 1039.44	122.28		APR	1.57		1,23 0,87 -0,36	2713.50 2713.50 2712.90	0.91
HAR	4.20	6,15	2,23 5,19 2,96	1040.85 1041.05 1039.01	131,22	RASIN	MAR	1.05		0.77	2712.90 2712.90 2712.80	0.74
FEB	2.10	2.11	1.54	1039.17 1039.40 1039.00	120.64	RIVER	FEB	1.05		0.42	2712.80 2712.80 2712.80	0.71
NAU	1.10	2.68	1.32	1039.39 1039.39 1039.05	121.98	ARKANSAS	NAL	0.89		0.37 0.20 -0.17	2712.80 2712.80 2712.80	0.71
DEC	1.60	1.44	1,51 3,13 1,62	1039.05 1039.05 1037.72	119.90		DEC	0.96		0.40	2712.80 2712.85 2712.80	0.71
NO N	0.90	4.0	2.07	1037.75 1037.78 1037.55	112.15		20%	0.82		0.59 0.28 -0.31	2712.85 2712.95 2712.85	0.72
100	3.80	3.91	2,89 1,88 -1,01	1037.75 1038.21 1037.30	112.15		OCT	2.10		1.13	2712.95 2713.35 2712.95	0.75
NORMAN RESERVOIR	INFLOWS(1000AC.FT.) AUG 1926 THRU 1961 FY 1988	RELEASES(1000AC.FT.) AUG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	FOOL CONTENT-EOM (1000AC.FT)	VII-19	OPTIMA LAKE	INFLOWS(1000AC.FT.) AUG 1939 THRU 1981 FY 1988	RELEASES(1000AC.FT.) LAKE HAS NOT FILLED	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	FOOL CONTENT-EOM (1000AC.FT)

TOTAL	58.8 56.9	29.0	20.87 14.42 -6.45				TOTAL	179.7	81.5	20.00 11.63 -8.37		
SEP	3.59	0.66	1.82 2.73 0.91	2004.00 2004.29 2003.88	13.89		SEP	11.25	5.72	1.79 2.09 0.30	1611.10 1611.55 1610.80	80.02
AUG	3.50 1.55	0.47	2.45 1.75 -0.70	2004.12 2004.14 2003.91	14.12		AUG	9.76	5.62	2.49 1.31 -1.18	1610.98 1611.58 1610.98	79.22
JUL	4.28	2.53	2.44 1.62 -0.82	2003.98 2004.31 2003.93	13.85		JUL	27.60	8.34 38.34	2.56 1.89 -0.67	1611.58 1615.86 1611.58	83.27
Nac	11.42	3.28	3.06	2004.26 2004.65 2003.82	14.39		NOC	36.74 12.21	14.01	2.80	1615.71 1615.73 1615.29	113.91
¥	12.05	8.25 4.20	3.66 0.19 -3.47	2004.21 2004.21 2003.79	14.30		¥ & #	34.74	5.63	3,37 0,87 -2,50	1615.66 1615.72 1615.32	113.42
<b>A</b> R	4.63 8.90	3.27	1.73	2004.00 2004.23 2003.82	13.89		APR	13.59 28.55	12.85	1.64	1615.45 1616.49 1615.36	111.75
r A A	3.01	3.20	1.13 2.21 1.08	2003.99 2004.50 2003.77	13.87	BASIN	MAR	8.35 30.86	7.21	1.13	1615.72 1616.07 1615.21	113.89
FER	3.26	2.22	0.80 0.01 -0.79	2003.81 2004.08 1003.81	13.55	RIVER	FEB	5.63	3.63	0.71	1615.42 1615.65 1615.27	111.51
L AN	1.92	1.81	0.57 0.42 -0.15	2003.91 2004.21 2003.79	13.73	ARKANSAS	247	4.22	4.14	0.54	1615.57 1615.90 1615.25	112.70
DEC	1.83	1.33	0.67 0.64 -0.03	2004.21 2004.37 2003.85	14.30		DEC	3.94	5.94	0.60 0.38 -0.22	1615.38 1615.78 1615.38	111.19
20%	3.34	1.29	0.94 0.18 -0.76	2003.88 2004.19 2003.71	13.67		NON	5.83	5,08	0.91 0.24 -0.67	1615.50 1615.50 1615.29	112.15
0CT	5.96	1.72	1.60 0.84 -0.76	2004.10 2005.19 2003.85	14.08		120	18.09 8.49	3.30	1.46	1615.48 1616.05 1615.42	111.99
FORT SUPPLY LAKE	INFLOWS(1000AC.FT.) AUG 1923 THRU 1981 FY 1988	RELEASES(1000AC,FT.) AUG 1976 THRU 1988 FY 1988	RAINFALL (INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	POOL CONTENT-EOM (1000AC.FT)	VII-20	CANTON LAKE	INFLOWS(1000AC.FT.) AVG 1923 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AVG 1976 THRU 1988 FY 1988	RAINFALL (INCHES) AVG 1930 THRU 1980 FY 1988 REVIATION	FOOL ELEVATION END OF MONTH MAXIMUM HINIMUM	FOOL CONTENT-EOM (1000AC.FT)

TOTAL	28.1		32.48 31.57 -0.91				TOTAL	4122.4 5117.9	3476.7	37.37 29.71 -7.66		•
SEP	3.94		3,38 5,08 1,70	1002.61 1002.79 1001.99	21.79		SEP	212.12 82.71	60.58 22.80	3.90 4.80 0.90	583,35 583,36 582,72	2145.74
AUG	1.03		2.55 2.53 -0.02	1002.10 1002.20 1001.97	20.98		AUG	144.26	147.83	2.80 1.67 -1.13	583.12 584.50 583.12	2122.74
701	2.06		2.12	1002.18 1003.22 1001.83	21.11		JUL	252.71 155.70	237.64	3.76	584.47 584.48 583.59	2259,56
אחר	3,08		4.25 2.67 -1.58	1003.17 1003.27 1001.82	22.69		JUN	603.75	540.48 21.59	4 4.4.2 10.01	583.61 583.78 583.61	2171.76
Æ	7.60		3.32	1001.89 1002.31 1001.81	20.65		# A A	766.88 125.16	493.25 294.35	70.00 4.00 4.00 7.00 7.00	583.64 585.86 583.49	2174,76
A R	3.60		3.22 4.23 1.01	1001.92 1005.31 1001.85	20.70		APR	526.38	397.49	3.83 8.4.0 1.4.2	585.77 590.57 585.75	2397,20
MAR	2.43		2.16 5.11 2.95	1003,34 1005,36 1001,90	22.97	SASIN	A A	353.60 1095.87	430.07 882.75	2.72 4.33 1.61	586.40 587.68 584.60	2466.24
FER	1.39		1,45 0,43 -1,02	1002.01 1002.13 1001.92	20.84	S RIVER BASIN	FEB	262.49 204.89	220.25 359.98	1.98 0.70 -1.28	584.68 586.30 584.68	2281,35
29%	1.36		1.24 1.16 -0.08	1002.13 1002.13 1000.23	21.03	ARKANSAS	JAN	218.39 494.08	308.74 1146.92	1.64 0.89 -0.75	586.29 591.89 586.29	2454.04
DEC	0.96		1.47 1.85 0.38	1000.23 1000.23 997.98	18.17		DEC	202.92	235.70	1.89 3.15 1.26	591.89 592.99 585.14	3118.64
NON	1.63		1.93	998.19 998.60 997.91	15.37		NON	246.54 286.21	249.26	2.45 2.88 0.43	585,66 585,68 583,67	2385.39
100	1.91		2.74	998.60 998.69 997.99	15.91		100	332,38 45,22	155.41 84.86	3,15 2,04 -1,11	583.87 584.60 583.84	2197.77
ARCADIA LAKE	INFLOWS(1000AC.FT.) AVG 1938 THRU 1982 FY 1988	RELEASES(1000AC.FT.) LAKE HAS NOT FILLED	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF HONTH MAXIMUM HINIMUM	PODL CONTENT-EDM (1000AC.FT)	V <sub>I</sub> I-21	EUFAULA LAKE	INFLOWS(1000AC.FT.) AUG 1923 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AVG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AVG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF MONTH MAXIMUM MINIMUM	FOOL CONTENT-EDM (1000AC.F1)

TOTAL	20484.9 28489.8	2519.7 8344.2	42,75 32,88 -9.87				TOTAL	0680.3	2975.1 8365.9	42.66 35.96 -6.70		
SEP	79.80 20 97.09 28	3.38 2	4.19 3.78 -0.41	459.20 460.23 459.04	91.21		SEP	53.55 2	596.42 23 416.34 28	4.09 3.18 -0.91	412.33 413.27 411.53	14.70
AUG	.93 12 .77 3	2.53 56	3,15 1,80 -1,35	459.95 4 460.40 4 458.96 4	23.53 49		AUG	74.74 12 07.44 4	697.15 5 306.29 4	2.99 1.91 -1.08	412.60 4 413.06 4 412.03 4	15.13
JUL	170.09 986. 347.90 339	602.81 663 330.96 32	3,16	460.05 4: 460.37 46 459.93 4	27.94 52		JUL	122.46 9 310.81 3	635,94 6 310,37 3	3.16 2.83 -0.33	412.30 4 413.11 4 411.93 4	14.66
אחר	57.85 2 34.21	781.44 16 299,10 3	4.69 1.14 13.55	460.18 4 460.25 4 459.70 4	533.81 5		NUC	710.16 21 287.80	843.18 16 287.00 3	4.32 0.91 -3.41	412.57 413.06 410.09	15.09
HAY.	3141.04 27: 1600.07 3	2805.80 27 1584.22 2	5.61 1.18 4.43	459,89 460.25 458.20	520.95		# *	3157.14 2 1564.36	763.39 2 563.32	14.65 14.65 88.53	412.34 413.08 412.06	14.72
APR	2466.04 3: 7676.43 1	3285.93 20 7615.94 1	4.54	460.00 460.60 458.30	525.69		APR	2575.19 3 7642.91 1	3308.96 2 7641.64 1	4.46 3.59 -0.87	412.24 415.08 410.91	14.56
A A A	1963.52 2 4943.80 7	2970.04 3 4963.68 7	3.43 4.28 0.85	459.00 460.80 458.98	482.59	FASIN	MAR	2018.50 4949.95	3042.76	3.65 3.99 0.34	411.56 412.90 410.89	13.56
FE	1176.02 1	322.17 648.23	2.61 0.94	459.69 460.38 458.72	512,33	RIVER B	FER	1200.22	1363.58 1660.89	2.80 1.19 -1.61	412.42 413.02 411.78	14.85
JAN	964.67 1 5035.83 1	1414.17 1 5046.16 1	2,13 0,78 -1,35	459,30 460.41 458,25	495.52	arkansas	N N N	1000.13	1466.24 5100.34	2.24 0.61 -1.63	412,58 414,42 411,29	15.10
DEC	1064.24	1618.68 1 4335.18	5.81	459.67 461.16 458.80	511.46		DEC	1072.34	1661.71	2.71 6.71	414,30 416.46 411.06	17.90
20%	1231.74 1	1671.76	3.07	459.78 460.60 459.20	516.20		201	1308.95	1703.37	3.32	412.43 413.66 408.99	14.86
100	1283.00	1815.64	3.60 2.54 -1.06	460.14 460.38 458.62	532,00		M OCT	1286.93 664.46	1892.39 663.43	3.39 0.0	412.82 413.17 411.89	15,48
R.S.KERR LOCK AND DAM	WS(1000AC.FT.) 1943 THRU 1981 988	L .ASES(1000AC.FT.) AVG 1976 THRU 1988 1 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	POOL CONTENT-EOM (1000AC.FT)		. MAYD LOCK AND DAM	INFLOWS(1000AC.FT.) AUG 1943 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AUG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF MONTH MAXIMUM HINIMUM	FOOL CONTENT-EOM (1000AC.FT)
.s.	INFLO AVG FY 1	RE AUG	RAIN AUE FY DEU	POOI ENI #A)	P009 (1)	VII-22	4.b.	N A H	REL AV FY	RAI AU FY		F00

WISTER LAKE	100	NON	DEC	N A	FER	A A R	AFR	H Y	NOC	JUL	₽Ne	SEP	TOTAL
INFLOWS(1000AC.FT.) AUG 1938 THRU 1981 FY 1988	18.76	53.40	65.96 350.88	67.53	93.38 61.94	126.43	132.44	134.46 5.39	60.21	21,41	9.21	17.46 5.28	797.7 814.5
RELEASES(1000AC,FT.) Avg 1976 thru 1988 FY 1988	17.62	39.88 36.26	109.74	83.19	73.70	114.86 90.54	88.70 157.52	103.30	91.51	15.97	4.85	3.51	746.8 817.2
RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	3.43 2.36	3.36	3.15	2.71	3.16 0.98	4.00 2.06 -1.94	4.65 1.89 -2.76	5.87 1.25 -4.62	4.08 1.33 -2.75	3.55 2.41 -1.14	3.28 2.04 -1.24	4.16 2.26 -1.90	45.60 24.36 -21.24
POOL ELEVATION END OF HONTH MAXIMUM MINIMUM	477.68 477.89 477.61	479.73 480.19 477.58	479.73 496.98 480.19 497.46 477.58 477.90	475.43 496.98 475.43	474.93 478.05 474.48	476.67 478.27 474.71	475.98 485.75 475.98	474.49 475.98 474.45	473.89 474.59 473.89	473.81 473.89 473.40	475.08 475.49 473.58	474.69 475.31 474.46	
POOL CONTENT-EOM	60.12	75.99 311	311.42	45.73	42.87	53.27	48.90	40.53	37.40	37.01	43.70	41.59	

Pelesses (1 000 AC ET )	8	MON	DEC	NAL	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	TOTAL
Avg 1971 thru 1988 LY 1988	1965.4	2466.5	2261.8 4856.0	1884.7 5665.6	1818.3	3638.8	3584.4 7922.8	3263.7 1602.2	3256.4 275.9	1588.1 272.5	701.2 337.0	729.4	27158.7 30635.8
Project Rainfall (inches) Avg 1972 thru 1988	4.1	8.4	3.1	1.7	2.5	4.5	ы 4.	4.	3.7	F.	2.5	7.5	2.13
ur 1988	3.5	8.4	10.9	'n.	1.9	7.9	8.0	1.3	2.2	9.	7	2.1	45.1
Deviation	9	o,	7.8	-1.2	9	3.4	9.4	-3.1	-1.5	-1.5	-2.1	-1.3	3.9
Pool Elevation	;												
End of Month	392.03	391.93	389.98	391.78	391.50	389.11	389.76	392.14	392.33	391.75	391.98	392.69	
Max im.m	392.25	392.30	393.47	391.78	392.13	391.92	391.40	393.01	392.46	392.50	392.54	394.22	
Nioima	391.31	390.01	388.73	388.66	391.18	388.75	388.46	389.65	391.59	391.37	391.07	390.47	
Pool Content ECM (1,000 AC. FT.)	59.3	58.6	46.3	57.6	55.8	41.6	45.1	60.1	4.14	57.5	59.0	63.9	
- I I A - 1 I A	Ę	Š	,	3		2	Ş	3		:	•	;	
	3		אנר	2		Ĭ	¥	¥	5	<b>₹</b>	¥	SEP	TOTAL
	2019.2	2805.6	2616.4	2004.0	2010.8	4072.8	4017.2	3555.4	3451.2	1665.1	738.9	756.8	29713.4
LY 1988	0.689	1265.5	97,525	5645.8	2172.8	5231.3	8119.7	1696.4	328.0	370.0	362.2	438.7	31584.0
Project Reinfall (inches) Avg 1973 thru 1988	0.4	 L	¥	·	0	4 7	<b>*</b>	c	•		č	ì	;
LY 1988	1.3	5.4	M.	•	200	. 4	; -	3.6		y 0	9.7	9 6	• •
Deviation	-2.7	9.	4.5	1.1	6.	7	-1.2	-2.8	-2.8	, eó	-1.2	4.1-	-9.2
Pool Elevation													
End of Month	371.85	371.37	372.06	32.8	370.80	371.80	371.86	372.31	372.49	371.16	371.47	372.21	
Minimum	369.98	370.20	372.36 370.20	372.36 370.90	372.45 370.42	372.40	372.19 371.32	372.58 370.99	372.64 371.24	372.49 371.00	372.22 370.38	372.21 370.32	
Pool Content ECM (1,000 AC. FT.)	146.9	142.3	149.1	137.7	136.8	146.5	147.0	152.0	154.1	140.3	143.3	150.9	

DARDANELLE LAKE	130	MON	DEC	JAN	FEB	¥	APR	MAY	<b>101</b>	707	AUG	SEP	TOTAL
Releases (1,000 AC. FT.) Avg 1966 thru 1988 VT 1988	1822.8 731.5	2360.4	2385.5	1917.8	1955.8 2318.9	3485.8 5555.0	3698.2 8229.1	3489.0	3567.3 304.2	1616.6 345.8	330.3	785.5	27896.4 32845.0
Project Rainfall (inches) Avg 1971 thru 1988 WY 1988 Deviation	4.6 2.2 -2.4	5.0 5.7	4.7 6.5 1.8	2.3 8. 1.5	3.1 1.8	4.9 3.9	4.4 L. 0. 80	5.5 1.8 -3.7	4.1 1.1 -3.0	2.6 2.0 2.0	2. 1.5 3.	3.7 2.6 -1.1	47.4 37.4 -10.0
Pool Elevation End of Month Maximum Minimum	337.51 338.17 337.35	338.00 338.34 337.06	338.37 338.37 337.06	337.76 338.21 337.62	337.78 338.31 337.44	337.87 338.29 337.39	337.60 338.13 337.50	337.62 338.20 337.37	337.57 338.05 337.22	337.98 338.27 337.24	337.68 337.98 337.10	337.70 338.06 337.06	
Pool Content ECH (1,000 AC. FT.)	8.69.8	486.2	473.5	478.2	8.87	481.8	472.8	473.5	471.8	485.5	475.5	476.2	
PLUE MOUNTAIN LAKE	001	MOV	DEC	JAN	FEB	FAR	APR	MAY	5	700	AUG	SEP	TOTAL
Inflows (1,000 AC. FT.) Avg 1948 thru 1988 Wr 1908	7.11	24.5	37.2	41.8	46.1	63.2	55.3 67.2	53.9	16.4 1.8	9.9	4.8	4.4 8.	369.4
Releases (1,000 AC. FT.) Avg 1948 thru 1968 MY 1988	5.6	14.7	35.7	40.3	43.1	49.5	45.0 65.2	50.3	35.9 22.8	17.1	11.1	6.2	355.1
Basin Rainfall (inches) Avg 1948 thru 1968 LY 1966 Deviation	3.6 7.1- 9.1-	N. W. O. W. C. W.	N. 80 .0.	2.5	W W.	4.0 3.9	4.2 4.1	5.3 1.6 -3.7	3.5 1.5 -2.0	9.8 6.4 7.	3.3 2.1 -1.2	N. 80 Y.	44.0 41.8 -2.2
Pool Elevation End of Month Maximum Minimum	384.10 384.58 384.04	385.20 385.40 384.06	406.48 406.96 384.22	385.98 406.48 385.98	384.44 388.09 384.22	387.36 387.72 384.22	387.64 393.64 387.26	387.08 387.64 387.08	379.00 387.08 379.00	377.10 379.00 376.66	373.24 377.10 373.24	370.73 373.24 370.33	
Pool Content ECM (1,000 AC. FT.)	24.9	28.3	139.6	30.7	26.0	35.3	36.3	**	12.2	7.9	æ.	2.2	

ARTHUR V. CHYCHO L & D	20	<b>6</b>	DEC	7	FEB	MAR	APR	**	3	'n	AUG	SE	TOTAL
Avg 1970 thru 1968 MY 1968	2081.4 680.6	2767.7 1405.2	3126.4 5917.7	2204.1	211 <b>8.6</b> 2334.0	4039.2 5830.3	4180.4	3755.0 1685.7	3492.1	1635.9	768.7 327.8	823.8 421.2	30993.3
Project Rainfall (inches) Avg 1971 thru 1968 ur 1968	3.2	5.1	4.7	2.3	3.6	8.8 8.6	3.4	1.2	4.2	2.6 7.8	2.9	3.6	45.3
Deviation	e.	2.8	4.5	-1.3	۲.		۸.	-3.6	-2.8	2.5	-2.2		1.5
Pool Elevation End of Month	285.06	285.98	286.93	285.05	286.36	284.59	284.56	286.10	284.96	286.85	286.54	286.46	
Minimum	28.5 28.03 28.03	286.83 284.26	284.45	286.73	28.24 28.24 28.24	26.52 264.06	264.14	284.14	%: /% %: /%	284.48	284.28	284.47	
Pool Content EOM (1,000 AC. FT.)	54.2	58.9	\$.2	54.2	61.1	51.8	51.7	59.7	53.7	8.3.8	1.29	61.6	
TOWN SUCK FERRY L & D	28	<b>NON</b>	DEC	748	<b>F</b>	Ž	APR	¥	JUM	'n	AUG	35	TOTAL
Merenses (1,000 AL. FL)  Avg 1970 thru 1988  LY 1988	2006.9	2815.3	2942.6 5987.0	2379.5	2260.9	4280.2 5816.4	4373.7	3862.8 1637.4	3563.3 337.3	2066.5 395.4	7.7.8 3.89.2	839.9 445.3	32167.4 35361.5
Project Rainfall (inches) Avg 1971 thru 1988	7;	5.5	6.4	2.5	3.2	4.5	4;	6.4	7.7	2.4	2.7	3.4	6.9
WY 1988 Deviation	2.0	7.4	10.1 5.2	6. ç.	3.0	3.1	1.4 1.	1.1	 3.5	4.3	2.0	2.0	41.6
Pool Elevation End of Wonth Maximum	265.21 265.80 264.86	264.90 265.82 264.05	272.35 276.32 264.62	264.48 272.35 264.17	265.39 265.43 264.28	265.54 270.50 264.27	264.43 271.77 264.25	265.36 266.15 264.31	265.38 266.00 264.92	265.36 265.72 264.97	265.42 265.64 264.82	265.40 265.64 264.83	
Pool Content ECH (1,000 AC. FT.)	33.9	32.6	90.0	30.9	¥.7	35.3	30.7	<b>%</b> .5	¥.6	34.5	¥.	¥.7	

HIMROD LAKE	8	MON	DEC	JAK	FEB	MAR	APR	MAY	*Or	TOP*	AUG	SEP	TOTAL
Inflows (1,000 AC. FT.) Avg 1944 thru 1988 WY 1988	19.0	40.3	72.3	64.9 76.7	65.8	102.4	89.8 85.1	93.2 4.8	36.6	12.4 2.5	٠. و. ه.	8.9 v.	629.4 583.2
Releases (1,000 AC. FT.) Avg 1944 thru 1968 WY 1968	9.6 8.	30.6	67.2 65.8	67.9	76.1	95.3	%.5 72.7	93.8 14.8	50.5	23.6	10.5 3.8	9.0	628.6 568.6
Basin Rainfall (inches) Avg 1944 thru 1988 WY 1988 Devlation	3.5 2.0 8.1	4.0 7.6 3.6	6.0 9.5 5.5	3.0 1.8 -1.2	3.5 -1.3	9.4.4 8.	7.4.	5.8 1.8 0.4-	4.1 2.5 -1.6	4.0 8.7	3.2	3.7 8.9	48.7 45.1 -3.6
	342.11 342.11 341.57	346.20 347.59 341.51	366.13 366.13 342.03	353.49 366.41 353.49	342.27 353.49 341.93	345.45 347.01 342.25	347.56 352.23 345.45	345.25 347.56 345.07	344.71 345.43 344.71	344.07 344.81 344.07	342.95 344.07 342.95	342.33 343.01 342.15	
12-71 Pool Content ECM (1,000 AC. FT.)	27.5	46.9 FO	225.3 DEC	93.1 JAN	30.0	43.2 HAR	54.1 APR	42.3 HAY	40.0	37.1 JUL	32.4 AUG	30.2 SEP	TOTAL
Releases (1,000 AC. FT.) Avg 1970 thru 1988 LV 1988	2121.5 690.1	2855.7 1606.0	3224.0 6262.1	2466.8 7190.9	2371.4	4422.5 5780.2	4578.4 8782.0	4190.4	3654.3	1634.5	728.4 299.2	814.9 365.1	33062.8 35987.4
Project Rainfall (inches) Avg 1971 thru 1988 LY 1988 Deviation	3.7 1.5 -2.2	5.5 11.0 5.5	4.8 14.3 9.5	2.7 2.4 .3	w w £. ≈ 4.	4. W	5.0 1.4 9.	5.1 1.2	3.6 1.3	2.6 6.7 4.1	2.4	3.4 1.3	46.1 51.8 5.7
Pool Elevation End of Month Maximum Minimum	250.54 250.67 250.30	248.95 250.94 248.43	246.91 250.24 246.91	248.79 248.81 246.76	250.26 250.52 248.72	248.04 250.27 247.03	248.42 248.42 247.03	250.48 250.75 248.33	250.55 250.60 250.28	250.45 250.73 250.02	250.54 250.70 250.00	250.35 250.68 250.10	
Pool Content ECM (1,000 AC. FT.)	103.4	<b>8</b> 6.6	88.9	85.2	100.3	7.82	8.18	102.7	103.5	102.4	103.4	101.3	

DAVID D. TERRY L & D	8	NO.	DEC	TAN	8	¥	APR	<b>K</b>	#OF	ij	AUG	SEP	TOTAL
Avg 1969 thru 1968 VY 1968	2027.2 703.0	2744.0 1628.2	3291.7 6295.3	2632.9 7276.3	2555.9	4477.8 5852.1	4654.5 8769.0	4234.0	3735.6	1747.0 321.9	7.1.7	821.3 374.8	33693.6 36195.9
Project Rainfall (inches) Avg 1971 thru 1988	7.5	5.1	 7. H	¥.2	м 0.0	4.4	7.4	5.0	ю •0	5.0 5.0	2.4	3.0	0.94
Wr 1990 Deviation	-3.2	M 9.	3.0	-1.2	-1.0	-2.4	5.9 -2.1	 2.4-	.3.3 .5.5	; ;		-2.1	-14.3
Pool Elevation End of Month	231.46	230.82	232.31	231.31	231.27	229.96	230.53	231.34	231.11	230.85	231.02	231.12	
Meximum	231.63	231.69	236.18 230.39	232.31	231.62	231.64	231.11 229.38	233.12 230.53	231.55	231.76 230.65	231.59	231. <b>84</b> 230.65	
Pool Content EOM (1,000 AC. FT.)	51.6	48.8	55.8	50.9	50.7	45.5	7.72	51.1	50.0	48.9	49.6	50.1	
LOCK AND DAM NO. 5	001	MON	DEC	NYT	£8	KA	APR	K	<b>*</b> 51	104	AUG	SEP	TOTAL
25 Avg 1970 thru 1968 LV 1968	2135.0	2890.7	3205.9 6022.9	2556.3 7227.9	2350.0	4452.0 5787.8	4667.8 8943.9	4182.8	3728.1	1709.1 382.1	772.3 333.7	6.00.6	33510.6 36335.1
Project Reinfall (inches) Avg 1972 thru 1968	4.3	6.4	6.4	2.9	3.3	4.3	4.7	5.5	3.6	3.1	5.6	3.5	47.6
ur 1968 Deviation		<b>6.1</b> 1.2	5.7	.3	 7.5-	1.7	1.6 -3.1	1.0	1.5	3.3	 	.9 -2.6	24.3 -23.3
Pool Elevation End of Month Maximum Minimum	213.01 213.75 212.81	212.80 213.25 211.82	212.48 215.52 211.29	212.90 212.90 211.01	213.06 213.24 211.92	211.96 213.15 211.00	212.02 212.66 210.97	213.58 213.88 212.02	213.86 213.99 213.39	213.79 213.98 213.40	213.71 213.89 213.44	213.89 214.02 213.54	
Pool Content ECM (1,000 AC. FT.)	4.14	60.0	58.0	60.7	61.7	54.7	55.0	65.5	67.5	0.79	38	2.79	

LOCK AND DAM NO. 4		NON	DEC	JAN	FEB	MAR	APR	¥	NOT	J.	AUG	<b>SE</b>	TOTAL
Avg 1970 thru 1968 Mr 1968	2147.6	2949.3	3266.5 6096.9	2614.4	4098.2 2963.6	4577.9 5918.4	4878.5	4340.1	3863.4	1727.0 365.5	761.9	850.8	36075.6
Project Rainfall (inches)													
Avg 1972 thru 1988	4.2	5.5	5.4	3.4	3.5	4.4	4.3	5.4	3.4	3.5	2.7	3.8 8.8	49.5
W 1968	1.4	12.6	7.6	1.9	1.6	2.5	5.4	'n	=	5.1	'n	1.8	41.1
Deviation	-2.8	7.7	4.3	-1.5	6.1.	-1.9	-1.9	6.4-	-2.3	1.6	-2.2	-2.0	-8.1
Pool Elevation													
End of Month	186.19	195.41	1%.66	5.3	196.06	195.13	195.51	18.11	196.12	196.50	196.08	196.50	
Haximum	186.58	18.39	199.26	38.86	196.31	196.26	1%.68	197.00	196.55	38.86	18.87	38.68	
Minimum	195.93	195.41	194.83	194.13	195.25	194.02	194.21	195.51	195.86	195.54	195.78	195.70	
Pool Content EOM													
(1,000 AC. FT.)	7.17	67.2	74.8	8.8	70.8	65.7	8.79	7.1	71.2	7.27	70.9	73.7	
IN LOCK AND DAM NO. 3	901	<b>M</b>	DEC	TY	FEB	ž	APR	MAY	3	3	<b>V</b> CC	SEP	TOTAL
T Releases (1,000 AC. FT.)	3 2746	0 1000	27.74	0 1276	0 0756	3 2077	3 0207	C 0777	1014	• 12.	7 072	7 728	72072
	73.2	1761.2	6176.8	7649.6	3055.9	5953.8	9262.4	1859.1	330.6	305.5	6.952	339.6	37676.6
Project Rainfall (inches)	4		* 1	*	<b>K</b>	¥ 7	6.7	•	<b>V</b>	-	, .	7 1	2 27
LY 1988	۰	12.9	6.3	4.2	6:	2.8	3.2	÷.	9.	9.4	1.2	2.3	43.5
Deviation	-3.4	7.8	3.5	9.	-1.4	-1.5	-1.0	-4.1	-2.9	1.5	-1.8	-1.1	-3.8
Pool Elevation													
End of Month	182.02	181.49	184.99	182.06	181.99	181.05	181.92	181.89	181.97	182.12	181.88	182.30	
Mex i mum	182.51	182.58	187.51	184.9	182.40	182.45	184.34	182.97	182.47	182.53	182.35	182.41	
Hinimum	181.85	181.47	181.22	180.49	181.21	180.64	180.65	181.49	181.72	181.71	181.74	27.181	
Pool Content EOM													
(1,000 AC. FT.)	46.5	7.73	59.8	9.97	4.6.4	42.7	46.1	46.0	<b>66.3</b>	6.94	42.9	47.6	

VILDUR D. MILLS DAM	50	<b>10</b>	DEC	JAN	FEB	MAR	APR	MAY	3	IJ	AUG	SEP	TOTAL
Ketesses (1,000 AE. FI.) Avg 1970 thru 1966 WY 1968	2059.2	3022.8 1826.7	3526.7 6306.3	2701.2 7775.7	2617.4	4763.9 5864.8	\$123.1 9305.0	4160.0	3918.7	1733.2 314.9	752.4 249.6	1359.9	35738.5
Project Rainfall (inches) Avg 1971 thru 1988	5,4	5.8	5.4	£.3	4.2	6.0	4.7	5.0	3.7	3.2	3.0	3.7	53.5
W 1988	4.	7.7	5.8	5.9	2.2	3.7	5.9	4.	s.	5.5	<u>:</u>	2.8	35.8
Deviation	-3.9	1.9	<b>4</b> .	<b>-1.6</b>	-2.0	-2.3	-1.8	9.4-	-3.2	2.0	-1.9	<b>6.</b>	-17.7
Pool Elevation	•	93	5	57	01 271	71 171	77 171	71 271	142 10	01 531	5 6	55	
Meximum	162.48	162.57	162.36	161.67	163.19	163.19	3. 151	163.44	163.45	162.61	162.62	162.65	
Hinima	161.97	161.36	160.70	160.30	161.31	160.95	160.48	161.56	162.04	161.74	161.71	161.83	
Pool Content EON	123	Š	š	Š	7 7 5	9	Ş	122 0	111.2	111.2	100.0	115.7	
1.1. JK 000, 1		2		3	;	2	3		:	•		:	

(No besic data collected) VII-30

ALTUS LAKE	100	NON	DEC	NAL	FER	HAR	APR	MAY	AUV.	Jul	AUG	SEP	TOTAL
INFLOWS(1000AC.FT.) AUG 1938 THRU 1981 FY 1988	7.13	2.75	3.44	3.77	5.05	5.93	9.57	29.65	20.95	8.39	3.01	3.01	102.7
RELEASES(1000AC.FT.) AUG 1976 THRU 1988 FY 1988	0.22	3.19	1.46	1.84	2.80	5.72	2.60	17.10 8.46	6.25	7.72	5.25	0.38	54.5
RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	1.99	0.88 0.14 -0.74	0.77	0.63 0.19	0.83 0.03 -0.80	1.19	1.99	4.09	3.19	2.21 1.26 -0.95	1.01	2.30 4.58 2.28	22.57 13.32 -9.25
POOL ELEVATION END OF MONTH MAXIMUM HINIMUM	1555.66 1555.66 1555.29	1555.66 1556.02 1557.56 1555.66 1556.03 1557.56 1555.29 1555.66 1556.02	1557,56 1557,56 1556,02	1559.19 1559.19 1557.56	1559.32 1559.34 1558.98	1559.18 1559.91 1558.94	1555.66 1556.02 1557.56 1559.19 1559.32 1559.18 1559.43 1558.93 1556.70 1552.90 1544.\$7 1550.02 1555.66 1556.03 1557.56 1559.19 1559.34 1559.91 1559.48 1559.43 1559.12 1556.77 1552.90 1550.02 1555.29 1555.66 1556.02 1557.56 1558.98 1558.94 1558.86 1556.59 1552.90 1544.57 1544.38	1558.93 1559.43 1558.86	1556.70 1559.12 1556.59	1552.90 1556.77 1552.90	1544.57 1552.90 1544.57	1550.02 1550.02 1544.38	
FOOL CONTENT-EDM (1000AC.FT)	112.96	112.96 114.99 120	124.03	134.04	134.86	133.98	4.03 134.04 134.86 133.98 135.56 132.40 118.93	132.40	118.93	98.03	61.10	83.94	

18.5 52.5	14.6	26.64 27.03 0.39				TOTAL	189.4	88.4 78.4	22.80 10.68 -12.1"		
1.77	0000	2.87 8.43 5.56	410.39  410.59  408.14	85.14		SEP	33.49	9.55 4.89	2.92 3.08 0.16	1137,24 1137,34 1134.06	179.10
0.73	0.00	2.26	408.21 409.03 408.21	72.30		AUG	18.91	13.41 21.06	2.22 0.25 -1.97	1134.75 1137.87 1134.75	155.13
1.28	0.00	2,15	409.03 409.88 409.03	76.97		70,	15.57	15.56 12.89	1.99 1.76 -0.23	1137.87 1139.04 1137.87	185.31
4.07	2.95	3.37 2.04	1409.86 1410.42 1409.83	81.87		רמא	25,28	13.73	2.73 2.13 -0.60	1138.84 1140.11 1138.75	196.44
5.73	3.08	4.82 0.97 -3.85	1410.41 1410.91 1410.40	85.27		¥A¥	38.02	5.06	3.66 0.16 -3.50	1140.07 1141.46 1140.03	211.83
1.38	0.26	2.43 4.16 1.73	1410.91 1411.20 1410.86	88.41		APR	12.78	3.94	1.88 1.15 -0.73	1141.46 1141.98 1141.46	230.64
0.66	1.88	1.55	1410.88 1412.50 1410.25	88.22	NISH	MAR	7.68	5.29	1.10 0.34 -0.76	1141.90 1142.15 1141.76	236.80
0.33	1.37	1.18	1410.25 1410.42 1410.25	84.27	RIVER	FEB	5.59	1.67	1.00	1141.77 1141.84 1141.70	234.98
0.25	0000	1.03	1410,40 1410,42 1409,32	85.21	RED	7 Y	3.73	1.94	0.83	1141.76 1141.82 1141.43	234.84
0.36	0.70	1.14	1409.33 1409.37 1409.07	78.74		DEC	6.74	2.23	0.98 0.50 	1141.47 1141.56 1141.14	230,78
0.45	2.68	1.35	1409.23 1409.60 1409.23	78.15		NON	8.94 80.0	8.21	1.08	1141.20 1141.84 1141.20	227.00
1.51	1.14	2.49	1409.60 1409.99 1409.45	80.34		001	22.20	7.86	2.41 1.06 -1.35	1141.80 1142.75 1141.80	235,40
INFLOWS(1000AC.FT.) AUG 1926 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AUG 1981 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF MONTH MAXIMUM	PDDL CONTENT-EOM (1000AC.FT)	VII-32	LAKE KEMP	INFLOWS(1000AC.FT.) AUG 1924 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AUG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	POOL CONTENT-EOM (1000AC.FT)
	1.51 0.45 0.36 0.25 0.33 0.66 1.38 5.73 4.07 1.28 0.73 1.77 18. 0.31 0.06 2.27 7.89 0.80 17.29 5.21 0.97 0.96 0.00 0.52 16.15 52.	1.51 0.45 0.36 0.25 0.33 0.66 1.38 5.73 4.07 1.28 0.73 1.77 18. 0.31 0.06 2.27 7.89 0.80 17.29 5.21 0.97 0.96 0.00 0.52 16.15 52. 15.15 18. 1.14 2.68 0.70 0.00 1.37 1.88 0.26 3.08 2.95 0.55 0.00 0.00 14. 0.00 0.00 0.00 0.00 10.29 1.85 0.00 0.00 0.00 0.00 12.	1.51     0.45     0.36     0.25     0.33     0.66     1.38     5.73     4.07     1.28     0.73     1.77     18       0.31     0.06     2.27     7.89     0.80     17.29     5.21     0.97     0.96     0.00     0.52     16.15     52       1.14     2.68     0.70     0.00     1.37     1.88     0.26     3.08     2.95     0.55     0.00     0.00     14       0.00     0.00     0.00     0.00     10.29     1.85     0.00     0.00     0.00     0.00     0.00     12       2.49     1.35     1.14     1.03     1.18     1.55     2.43     4.82     3.37     2.15     2.26     2.87     26.       2.14     0.33     3.03     0.77     0.02     1.85     4.16     0.97     2.04     1.59     1.70     8.43     27.       -0.35     -1.02     1.89     -0.26     -1.16     0.30     1.73     -1.33     -0.56     -0.55     5.56     0.	1.51 0.45 0.36 0.25 0.33 0.66 1.38 5.73 4.07 1.28 0.73 1.77 18 0.51 0.05 0.00 0.52 16.15 52 0.31 0.06 1.27 0.06 0.00 0.31 0.05 0.00 0.05 0.00 0.00 14 0.05 0.00 0.00 0.00 0.00 0.00 0.00 0.0	1.51         0.45         0.45         0.66         1.38         5.73         4.07         1.28         0.73         1.77         18           0.31         0.06         2.27         7.89         0.80         17.29         5.21         0.97         0.96         0.00         0.52         16.15         52           1.14         2.68         0.70         0.00         1.37         1.88         0.26         3.08         2.95         0.55         0.00         0.00         12           0.00         0.00         0.00         10.29         1.85         0.00	1.51 0.45 0.36 0.25 0.33 0.66 1.38 5.73 4.07 1.28 0.73 1.77 18 0.51 0.045 0.05 0.30 0.80 17.29 5.21 0.97 0.96 0.00 0.52 16.15 52 0.51 0.06 2.27 7.89 0.80 17.29 5.21 0.97 0.96 0.00 0.52 16.15 52 0.00 0.00 0.00 0.00 1.37 1.88 0.26 3.08 2.95 0.55 0.00 0.00 1.00 1.00 0.00 0.00 0.00 0.00	1.51 0.45 0.05 0.36 0.25 0.33 0.66 1.38 5.73 4.07 1.28 0.73 1.77 1.15 0.05 0.00 0.52 16.15 1.14 0.06 0.00 0.00 1.37 1.88 0.26 3.08 2.95 0.00 0.00 0.00 1.37 1.88 0.26 3.08 2.95 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0	1.51 0.45 0.36 0.36 0.25 0.33 0.66 11.38 5.73 4.07 11.28 0.73 11.77 181.5  1.14 2.68 0.70 0.00 11.37 11.88 0.26 3.08 2.95 0.55 0.00 0.00 14.6  1.00 0.00 0.00 0.00 11.37 11.88 0.26 3.08 2.95 0.55 0.00 0.00 14.6  2.49 11.35 11.14 11.03 11.18 11.55 2.43 4.82 3.37 2.15 2.26 2.87 2.06 1.20  2.14 0.33 3.03 0.77 0.02 11.85 4.16 0.97 2.04 11.59 1.70 8.43 2.70  2.14 0.33 1.03 0.77 0.02 11.85 4.16 0.97 2.04 11.59 1.70 8.43 2.70  2.14 0.33 1.03 0.77 0.02 11.85 4.16 0.97 2.04 11.59 1.70 8.43 2.70  2.14 0.33 1.03 1.04 14.10.25 1410.88 1410.91 1410.41 1409.86 1409.03 1408.21 1410.39 1409.42 1409.23 1409.03 1410.42 1410.25 1410.25 1410.86 1410.91 1410.41 1409.83 1409.03 1408.21 1410.39 1409.73 1409.73 1409.72 1409.25 1410.25 1410.25 1410.86 1410.40 1409.83 1409.03 1409.03 1409.73 1409.73 1409.73 1409.72 1410.25 1410.25 1410.86 1410.40 1409.83 1409.03 1409.83 1409.03 1409.73 1409.73 1409.73 1409.32 1410.25 1410.25 1410.40 140.40 1409.88 1409.03 1409.83 1409.03 1409.83 1409.73 1409.73 1409.32 1410.25 1410.25 1410.25 1410.40 1409.83 1409.03 1409.33	1.51  0.045  0.35  0.35  0.433  0.666  1.38  5.73  4.07  1.28  0.73  1.77  181.5  52.5	1.51	11.14 2.68 0.70 0.00 11.37 1.88 0.26 5.21 0.97 0.96 0.00 0.00 12. 12. 12. 12. 12. 12. 12. 12. 12. 12.

TOTAL	38.0 58.3	16.9	27.59 28.37 0.78				TOTAL	60.9	40.2	37.17 24.76 -12.41		
SEP	2.41	0.20	3.07 6.29 3.22	341.43	77.71		SEP	3.74	0.23		869.52 870.07 869.52	66.73
AUG	1.85	0.14	2.47	340.47 1 341.15 1 340.47 1	73.91		AUG	2.12	0.22	2.78 0.46 -2.32	869.99 870.87 869.99	67.78
JUL	2.86	0.86	2.28 2.41 0.13	1341.08 1 1341.69 1 1341.08 1	76.30	•	JUL	2.94	0.39	2.48 2.01 -0.47	870.87 871.58 870.87	86.98
208	3.89 2.97	7.29	3.67 2.58 -1.09	1341.62 1341.83	78.48		אחר	1.44	90.0	3.90 2.24 -1.66	871.58 871.92 871.48	71.42
¥ ¥	6.26 2.04	6.31	4.78 0.55 -4.23	1341,81 1343,58 1341,76	79.24		MAY	12.49	90.0	5.65 0.64 -5.01	871.85 872.11 871.84	72.05
AFR	4.10	5.78	2.64 2.85	1343.57 1343.58 1341.97	86.62		AFR	8.07	5.01	3.86 1.27 -2.59	872.03 872.85 871.99	72.47
MAR	3.09	1,25	1.62	1342.20 1343.48 1341.97	80.84	BASIN	MAR	5,63	5.05	2.92 3.03 0.11	872.21 875.19 872.00	72.90
FER	3.38	0.66	1.12	1342,38 1342,38 1342,17	81,59	RIVER	FER	4.90	2.82	2.21 0.77 -1.44	872,26 872,41 871,99	73.02
JAN	2.27	0.83	1.00	1342.17 1342.53 1342.00	80.72	RED	JAN	3.07	3.02	1.75	872.39 873.68 871.95	73,33
DEC	2.05	3.58	1.18	1342.00 1342.57 1342.00	80.01		DEC	3.29	3.38	2.06 3.94 1.88	873.68 876.58 872.01	76.43
NON	1.88	2.56	1.39	1342.17 1342.17 1341.91	80.72		) 0 2	3.24	0.69	2,33 0,23	872.99 873.06 871.98	74.76
100	2.34	1.79	2.37	1341.99 1341.99 1341.69	19.97		DCT	3,80	1.42	3.48 2.64 -0.84	872.24 872.26 871.70	72.97
FORT COBB RESERVOIR	INFLOWS(1000AC.FT.) AUG 1926 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AUG 1976 1HRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF HONTH MAXIMUM HINIHUM	POOL CONTENT-EDM (1000AC.FT)	VII-34	ARBUCKLE RESERVOIR	INFLOWS(1000AC.FT.) AUG 1926 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AVG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AVG 1930 THRU 1980 FY 1988 DEVIATION	FOOL ELEVATION END OF HONTH MAXIMUM	FDDL CONTENT-EDM (1000AC.FT)

LAKE TEXOMA	96.1	NO.	DEC	NAU	FEB	HAR	AFR	¥ V	NOC	JUL	AUG	SEP	TOTAL
INFLOWS(1000AC.FT.) AUG 1906 THRU 1981 FY 1988	366.34	199.55	180.83 858.84	140.89	166.47	227.04 813.26	413.04	812.92 176.73	688.44 145.19	214.49	177.99 26.18	240.90	3828.9 4185.2
RELEASES(1000AC.FT.) AVG 1976 THRU 1988 FY 1988	360.68 207.25	297.11 175.97	185.49 288.56	248.88 799.44	180.54 395.40	349.73	280.41	365.59 263.06	886.11 120.43	352.65 120.30	145.89	109.53	3762.6 3820.3
RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	2.49	1.39 0.48 -0.91	1.22	1.13	1.28 0.06 -1.22	1.55	2.48 2.10 -0.38	4.39 0.38 -4.01	3.30 2.47	2.20 1.40 -0.80	2,33	2.89 4.53 1.64	26.74 16.89 -9.85
FOOL ELEVATION END OF MONTH MAXIMUM MINIMUM	614.44 615.65 614.39	614.52 614.56 614.02	620.81 620.81 614.14	617.52 620.81 617.52	615.31 617.52 615.31	617.19 617.86 615.27	616.55 618.47 616.55	615.00 616.55 615.00	614.69 615.25 614.68	613.87 614.69 613.87	612.22 613.87 612.22	615.61 615.61 612.03	
POOL CONTENT-EOM (1000AC.FT)	2433.12	2439.36	2999.03	2690.10	2501,60	2660.40	2604.37	2476.80	2452.62	2388.89	2264.64	2525.60	
VII-35				RED	RIVER	RASIN							
HCGEE CREEK	OCT	NOC	DEC	NAU	FER	MAR	APR	MAY	NO.	JUL	AUG	SEP	TOTAL
INFLOWS(1000AC.FT.) AUG 1938 THRU 1976 FY 1988	5.37	6.61	5.69	4.84 4.84	9.67	11.89	18.50	17.98	10.32	4.03	1.97	4.72	102.1
RELEASES(1000AC.FT.) LAKE HAS NOT FILLED	_												
RAINFALL(INCHES) AVG 1930 THRU 1980 FY 1988 DEVIATION	0.00 4.03 4.03	1.72 4.93 3.21	1,18 5,38	2.17 0.58 -1.59	3.05 2.12 -0.93	3.38 3.05 -0.33	5.02 1.91 -3.11	6.08 0.70 -5.38	4.00 4.00 4.04	3.45 3.47 0.02	2.99 3.85 0.86	3.40 1.14 -2.26	36.88 32,16 -4.72
POOL ELEVATION (1) END OF MONTH MAXIMUM HINIMUM	165.40 165.40 165.11	167.86 167.86 165.36	174.80 174.80 167.86	175.54 175.54 174.80	175.91 176.03 175.54	175.89 176.52 175.84	175.89 176.00 175.89	175.72 175.90 175.72	175.55 175.73 175.55	175.40 175.55 175.40	175.26 175.40 175.26	175.12 175.26 175.12	
FOOL CONTENT-EOM (1000AC.FT)	28.09	40.94	100.79	109.58	114.07	113.83	113,83	111.77	109.70	107.89	106.19	104.49	
(1) ELEVATIONS ARE ]	IN METERS												

JAN FEB MAR AFR MAY JUN	.38 11.78 12.30 16.04 15.77 10.14 .81 14.16 12.09 9.58 1.77 0.48	.23 7.16 12.93 9.38 9.78 11.79 .65 10.09 8.02 11.59 2.67 0.08	2,76 3,09 3,74 4,71 5,30 4,01 0,57 1,94 2,45 1,73 0,92 0,79 2,19 -1,15 -1,29 -2,98 -4,38 -3,22	.05 452.41 452.66 451.89 451.09 450.55 .36 453.19 452.66 453.00 451.89 451.09 .05 451.60 451.69 451.89 451.09 450.55	.91 133.14 134.69 129.93 125.05 121.84	RED RIVER BASIN	JAN FER MAR APR MAY JUN	1.79 26.99 30.93 39.85 39.52 19.88 7.31 15.86 37.75 20.65 2.92 2.86	8.21 14.98 37.59 29.69 27.68 30.40 8.70 13.41 29.49 21.90 0.00 0.00	.50 3.01 3.63 4.78 6.03 4.34 .65 1.01 2.52 2.35 0.84 1.17 .85 -2.00 -1.11 -2.43 -5.19 -3.17	.04 599.08 599.40 599.00 598.72 598.37 .73 599.38 599.76 599.72 599.00 598.72 .96 598.97 598.95 598.95 598.72 598.37	.16 275.44 279.88 274.33 270.58 265.90
OCT NOV DEC	4.89 7.23 7.99 6. 2.18 18.89 34.24 7.	0.28 2.94 6.28 4. 0.00 4.77 19.04 20.	3.55 3.39 3.21 2. 2.73 3.86 3.09 0. -0.82 0.47 -0.12 -2.	450.15 452.22 454.36 452.00 450.17 452.40 455.05 454.3 449.76 450.08 451.95 452.0	119.48 131.96 145.57 130		OCT NOV DEC	9.07 15.39 20.38 21 0.75 38.22 92.33 17	10.48 53.52 39.99 28 0.00 27.53 38.66 68	3.44 3.40 2.78 2 1.92 5.39 4.82 0 -1.52 1.99 2.04 -1	598.52 599.15 602.73 599.04 598.74 600.06 603.46 602.73 598.39 598.49 598.94 598.9	267.90 276.41 328.25 275
PAT MAYSE LAKE	INFLOWS(1000AC.FT.) AUG 1937 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AUG 1976 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	POOL ELEVATION END OF MONTH MAXIMUM MINIMUM	FOOL CONTENT-EOM (1000AC,FT)	VII-36	SARDIS LAKE	INFLOWS(1000AC.FT.) AUG 1926 THRU 1981 FY 1988	RELEASES(1000AC.FT.) AUG 1985 THRU 1988 FY 1988	RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 REVIATION	FOOL ELEVATION END OF MONTH HAXIMUM HINIMUM	FOOL CONTENT-EOM (1000AC.FT)

### RED RIVER BASIN

H A K	130	2	1 1 1 1	2	رم ند ند	ŭ đ X	0 0	X A	2	=	9114	ŭ	TOTAL
INFLOWS(1000AC.FT.) AUG 1926 THRU 1964 FY 1988	40.79	74.01	117.34	160.37	177.57	171.23	257.85	250.16	114.02	56.90	19.14	49.05	1485.4
RELEASES(1000AC,FT.) AUG 1976 THRU 1988 FY 1988	54,72	114.88	132.54	112.86	150.30	214.23	212.94	208.25	149.36	43.02	20.17	15.13	1428.4
RAINFALL(INCHES) AUG 1930 THRU 1980 FY 1988 DEVIATION	3.65 2.42	3.75 3.58 -0.17	3.19 3.27 0.08	20 0 . 0 0 . 4 0 . 6 0 . 6 0 . 6	3.27 0.91 -2.36	3.92 2.31 -1.61	0.0 0.09 44.69	6.09 0.49 -5.60	4.24 1.68 -2.56	3.54 2.61 -0.93	3.31 1.88 -1.43	4.55	47.39 22.80 -24.59
FOOL ELEVATION END OF MONTH MAXIMUM MINIMUM	404.07 404.07 403.32	408.10 409.90 404.03	419.63 420.15 406.40	404.60 419.63 404.60	404.52 408.07 404.50	405.56 405.90 404.40	404.63 408.12 404.43	404.12 404.63 404.10	403.10 404.20 403.10	404.18 404.48 402.52	404.81 405.16 403.66	404.20 404.90 403.87	
FOOL CONTENT-EOM (1000AC.FT)	151.74	209.21	438.26	158.90	157.82	171.91	159,30	152.42	139.64	153.23	161.73	153.50	
VII-37				RED	RIVER	BASIN							
PINE CREEK LAKE	DCT	NOV	DEC	200	FEB	HAR	APR	MAY	אמר	Jul	AUG	SEP	TOTAL
INFLOWS(1000AC.FT.) AUG 1929 THRU 1981 FY 1988	22.63	38.04 129.58	56.04	63.77	78.03	82.93 84.40	95.41 130.81	104.78	42.28	17.51	8.38 31.08	22.66	628.7 750.4
RELEASES(1000AC,FT.) AUG 1976 THRU 1988 FY 1988	24.53 14.93	54.94 98.27	66.93	53.99	66.05	86.90 47.38	81.93	86.03 4.24	64.11	14.04	9.19	9.39	618.0 732.5
RAINFALL(INCHES) AVG 1930 THRU 1980 FY 1988 DEVIATION	3.76 2.98 -0.78	3.89 4.28 0.39	3.09 3.04 3.05	3.12 0.39 -2.73	3.48 1.46 -2.02	4.25 2.71 -1.54	5.15	6.21 0.61 -5.60	4.28 0.82 -3.46	3.87 2.22 -1.65	3.53 2.42 -1.11	1.22	49.80 23.54 -26.28
FOOL ELEVATION END OF MONTH MAXIMUM MINIMUM	438.86 440.00 437.17	445.29 451.39 437.75	460.35 460.44 438.15	438.10 460.35 438.02	438.06 443.54 437.90	44 50.08 50.08 60.75 60.75	442.54 453.81 442.38	441.72 442.60 441.72	440.25 441.72 440.25	442.02 442.03 439.75	440.11 445.35 440.11	438.79 440.15 438.79	
FOOL CONTENT-EDM (1000AC,FT)	57.07	87.03	200.73	54.13	53.98	90.10	73.05	22.69	62.75	70.58	62.15	56.80	•

INFLOWS(1000AC.FT.) AVG 1930 THRU 1981 34.81 58.40 FY 1988 145.86		בייים הייים	1	É	: E	-		!			
	40 95.11 86 315.11	1 111.71	114.40	140.87	130,36	138.16	52.17	26.71 14.58	14.15	23.55	940.4 897.8
RELEASES(1000AC.FT.) AVG 1976 THRU 1988 26.91 53.26 FY 1988 9.23 29.86	26 94.42 86 103.16	2 79.00 6 286.61	72.22	99.67	115.65	94.57	84.02	48.04	34.09	22.40	824.2
RAINFALL(INCHES) AVG 1930 THRU 1980 4.14 4.08 FY 1988 5.37 DEVIATION 0.95 1.29	08 4.15 37 5.55 29 1.40	3.72	3.83 1.84 -1.99	4.89 3.22 -1.67	5,28 1,69 -3,59	6.29 1.75 -4.54	4,31 2,13 -2,18	4.23 0.73	3.69 4.69	1.54	53.21 38.26 -14.95
POOL ELEVATION 592.50 600.76 (END OF MONTH 592.51 601.17 (MAXIMUM 591.62 592.41)	76 614.51 17 614.94 41 599.44	1 600.23 4 614.51 4 600.09	599.56 600.67 599.09	600.38 600.38 598.20	598.37 603.48 598.32	597.10 598.41 597.10	596.0 597.10 596.00	596.24 596.72 595.97	596.56 597.06 595.81	5°4.91 596.56 594.84	
FDDL CDNTENT-EDM (1000AC.FT) 822.07 936.00	936.06 1146.68	8 928.47	918.94	930.62	902.15	884.42	872.01	872,56	876.97	854.37	

DEQUEEN LAKE	8	W	DEC	JAN	FE8	MAR	APR	MAY	3	Ą	AUG	SEP	TOTAL
Inflows (1,000 AC. FT.) Avg 1930 thru 1988 kV 1988	7.5	14.6	22.4 67.9	23.1	24.6	30.4	28.8 16.9	29.2	10.6 5.	6.0	3.9 8.0	6.0	207.1
Releases (1,000 AC. FT.) Avg 1979 thru 1968 LY 1988	10.0	18.4 25.6	30.8	19.2	20.2	27.2 23.1	27.1	26.2	19.3 8.	10.4 5.4	5.1	3.6	217.5
Basin Rainfall (inches) Avg 1930 thru 1968 WY 1988 Deviation	1.4	4.4 9.5 5.1	4.4 9.9 6.8	3.6 2.5 -1.1	9. N 0. N 9. O	6.3	5.3 2.9 -2.4	6.4 1.2 5.2	1.8	4.4 6.1 1.7	3.5 3.5	4.3 1.8 -2.5	53.2 56.0 2.8
Pool Elevation End of Month Maximum Minimum	426.5 <b>8</b> 427.81 425.97	438.69 439.09 426.02	451.98 452.38 427.29	426.45 451.98 426.18	425.97 430.34 425.90	431.37 432.69 425.97	437.01 438.23 431.37	436.73 437.07 436.73	436.17 436.73 436.17	436.82 438.47 436.13	436.97 438.61 436.43	436.37 438.24 436.29	
Pool Content EOM (1,000 AC. FT.)	20.2	37.8	8.2	20.0	19.5	26.3	34.9	7.5	33.5	74.0	¥.9	33.9	
G	8	<b>M</b> O <b>M</b>	DEC	JAN	FE8	MAR	APR	M	NOT	JOI.	AUG	SEP	TOTAL
Inflows (1,000 AC. FT.) Avg 1930 thru 1988 LY 1988	13.8	26.5 7.7	42.0	44.1	43.8	55.8 56.8	48.9	3.0	19.4 7.	10.7	5.0	9.6 3.3	367.6 387.8
Releases (1,000 AC. FT.) Avg 1977 thru 1988 ur 1988	10.1	30.9 62.8	\$0. <b>8</b> 72.5	36.3 106.8	33.8 25.6	50.1	59.1 37.0	5.0	30.1	12.4	5.0	3.9	368.1 386.0
Basin Rainfall (inches) Avg 1930 thru 1986 WY 1986 Deviation	3.5.	4.6 10.2 5.6	4.4 9.9 8.8	3.7	4.0 2.4 -1.6	5.2 6.3 1.1	5.3 3.0 -2.3	6.3 1.3 -5.0	4.6 9.5 8.5	4.4	3.4 6.3	4.6 2.0 2.6	54.7 54.9 .2
Pool Elevation End of Month Maximum Minimum	504.50 505.59 501.79	514.71 520.19 502.24	535.36 536.72 502.74	500.40 535.36 500.24	502.28 507.07 500.40	506.67 508.33 502.28	502.35 507.44 501.98	500.52 502.78 500.52	498.35 500.52 498.35	501.95 503.97 498.32	502.06 502.96 490.74	501.22 502.88 501.22	
Pool Content EOM (1,000 AC. FT.)	36.6	53.3	8.	30.9	33.4	35°8	33.5	31.0	28.3	33.0	33.1	32.0	

DIERKS LAKE	56	AON	DEC	JAN	FEB	MAR	APR	Ħ	<b>30</b>	JOF.	AUG	SEP	TOTAL
Inflows (1,000 AC. FT.) Avg 1930 thru 1988 ur 1988	4.7	9.9	16.9	18.7 17.6	17.6 13.5	22.0 20.3	19.4	20.5	2.	4.2	-:- 8:	3.1	145.2 145.8
Releases (1,000 AC. FT.) Avg 1977 thru 1988 WY 1988	7.4	3.0	16.6 28.9	16.1	12.7	18.3 18.7	18.6	15.8	9.6	1.1	2.0	20 1	129.8 130.5
Basin Rainfall (inches) Avg 1930 thru 1988 WY 1988 Deviation	4.7 3.7	4.7 10.9 6.2	4.6 10.2 5.6	3.9 2.0 -1.9	4.1 8.3	5.1 6.3 1.2	5.3 3.4 -1.9	6.1 4.8	4.8	4, 4 6, 6 7, 5	5. 5. 5. 5. 6. 5.	3.9	54.5 56.1 1.6
Pool Elevation End of Month Maximum Minimum	515.50 515.50 513.94	533.93 533.99 515.50	543.09 543.51 528.56	526.85 543.09 526.85	526.12 528.66 526.07	527.08 529.69 525.99	526.19 529.55 526.03	526.04 526.30 526.04	524.92 526.04 524.92	525.09 525.52 524.73	524.69 525.09 524.54	524.98 525.58 524.64	
Pool Content EOM (1,000 AC. FT.)	17.6	41.9	59.8	30.8	29.8	31.1	8.8	28.7	28.2	28.4	27.9	28.3	
MILLWOOD LAKE	8	<b>NO</b> ₩	DEC	NY	A B	MAR	APR	MAY	<b>10</b>	JUL	AUG	SEP	TOTAL
Intlows (1,000 Ac. Fl.) Avg 1929 thru 1968 AY 1968	119.8	259.5 521.2	409.6	437.9	4.89.8 4.36.9	578.9 488.0	602.0 575.9	644.5	287.0	124.9 56.0	70.3 105.1	%.1 30.2	4120.3
Releases (1,000 AC. FT.) Avg 1976 thru 1968 WY 1968	120.6 38.9	263.9	461.7 369.2	371.0 1387.9	369.0	529.1 473.5	508.3	453.4	337.8	169.8 24.3	63.1	85.9 120.5	3753.6 3721.0
Intervening Basin Rainfall (inches) Avg 1930 thru 1968 3 WY 1968 4. Deviation	inches) 3.9 4.1 .2	4.4 9.1 7.4	0.4 8.6 8.8	3.4 1.7	3.8 3.1 7	5.4 5.1	4.8 3.2 -1.6	5.7	3.9 2.3	3.5 6.0 2.5	2.9 5.7 2.8	5.5 7.6 5.2	48.5 52.2 3.7
Pool Elevation End of Month Maximum Minimum	256.95 256.95 256.17	259.19 260.26 256.36	269.73 270.30 <b>258.</b> 20	257.94 269.73 257.94	257.60 258.91 256.01	257.98 258.52 256.75	259.32 261.20 257.98	259.34 259.46 259.17	259.13 259.40 259.12	259.00 259.61 258.99	259.17 259.84 258.95	255.31 259.17 255.21	
Pool Content EOM (1,000 AC. FT.)	14.7	204.8	9.529	169.9	161.2	170.9	208.7	209.3	203.1	199.2	204.2	107.9	

AUG SEP TOTAL		15 9 33 1 3124 1 9 1 2 9 3475 8	다 (1 mm) 1 mm) 1 mm 1 mm 1 mm 1 mm 1 mm 1	60 60 60 60 60 60 60 60 60 60 60 60 60 6	253, 63 254, 18 253, 29 27, 29	្រ (a) (d) (d) (d) (d) (d) (d)	AUG SEP TOTAL		4.6 11.2 506.5 0.0 0.1 623.1	9.9 11.7 452.7 1.5 1.5 559.2	1, 64 2 09 42 56 1, 29 1, 39 41, 59 -0, 37 -0.70 -1.00	227. 05 226. 56 227. 69 227. 06 227. 05 226. 50	
JUN JUL		74 B 52 0 0 0 62 6	21 1 210 1 0.6 0.5	3 52 2 69 0.54 3 59 2.98 0.90	2, 51, 224, 18 3, 27, 224, 25 2, 51, 232, 25	1.60 235.14	JUN JUL		32.0 10.7 3.6 4.6	34 5 13.7 2.0 1.5	4, 50 1, 73 0, 91 2, 48 3, 59 0, 75	8.09 227.69 8.54 278 10 8.09 277.69	
γν		377 6 17	337 1 28	60 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	200 200 200 200 200 200 200 200 200 200	220,77 201	<b>λ</b>		24. R.	40 4 (j	4, 0 6, 7, 0 6, 0 1, 0	228.54 228 228 91 228 328.54 228	
APR		275. 6 168. 2	210-2 124, 4	4, 03 1, 43 10	224, 29 225, 07 223 13	248, 19	A R		75.3 44.0	53.9 46.1	3.05 1.49 -1.56	228. 33 229. 35 228. 52	
A A B		292.0 154.7	252 0 268 8	9 9 9 8 8 8	22.0.13 22.13 22.36 23.36	217.15	ИАЯ		90.2 79.8	75. 0 168. 5	3.04 4.77 8.88	229 26 233, 74 229 26	•
8 1 1 1		229 6 158.9	216 1 526 7	2, 91 3, 31 0, 40	757 00 736 08 727 36	342 948 88	FEB		70.9	01.8 139.5	4 . 38 8. 38 8. 0 . 0 . 33	203.74 203.79	
NAU		159, 5	521 S 607 0	1, 93 0, 53	206.08 241.85 3.556.08	710.31	NAC		S 49.9 5 59.0	5 54.8 8 125.5	4 2 03 9 0 36 5 -1, 67	1 236.20 1 238.92	
) DEC		6 275 5 0 963 4	2 221 2 7 535 0	8 B 29 39 9 10 B 39 17 17 17 17 17 17 17 17 17 17 17 17 17	2 240, 18 2 250, 18	936. 57	) DEC	*	7 57.9 3 289.5	3 81.6	12.5 2.3 3.3	2 238,84 1 238,84 1 229,55	
YON .		169. 523	155 260.	0.00 68 6.00 69 19.00 61		3 517 17	NDV -		27.	5 14 S	4 5.16 3 8.32 3.16	7 230, 12 3 200, 31 5 228, 71	
DCT		9.50 8.80 8.00	96 0 12 9	8 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	ा स्व स्व स्व स्व स्व स्व स्व स्व स्व स्व	256, 43	DCT		12. 0 6. 6	0.01	5, 14 3, 18 -1, 95	228, 77 228, 98 229, 59	
	WRIGHT PATMAN LAKE	Inflows(1000 AC.FT) Avg 1957 thru 1988 WY 1988	Releases(1000 AC.FT) Ava 1957 inru 1938 WY 1988	Painfall (inches) Avg 1958 thru 1908 WY 1988 Deviation	Foot Elevation End of Month Maximum Minimum	Fool Content EDM (1903 AC. FT.)		LAKE U THE PINES	Inflows(1000 AC.FT) Avg 1958 thru 1988 WY 1988	Releases(1000 AC FT) Avg 1958 thru 1903 WY 1988	Rainfall (inches) Avg 1980 thru 1988 WY 1988 Deviation	Pool Elevation End of Month Marimum Minimum	Popl Content FOX

	OCT	>0 N	DEC	NAU	834	MAR	APR	¥Υ	<b>N</b>	JUL	AUG	SEP	TOTAL
SAM RAYBURN RESERVOIR												·.	
Inflows(1000 AC.FT) Avg 1908 thru 1988 WY 1988	42.8 4.0	96, 5 241, 3	187. 6 376. 5	251. 2 324. 6	264.0 151.9	282, 6 292, 2	274. 1 156. 1	302.7 22.2	138.0 14.3	56. 6 37. 2	34. 2 35. 1	32. 6 2. 3	1963. 0 1657. 7
Releases(1000 AC FT) Avg 1966 thru 1988 WY 1988	70, 2• 161, 0	48.8 79.0	57. 1 7. 8	112.1 133.6	128 <b>ම</b> රූප ස	193.4 252.6	158.1 183.0	184.9	192 3 170 3	159.6	144. 1 170. 6	101.0	1550.1 1699.1
Rainfall (inches) Avg 1970 thru 1988 WY 1988 Deviation	නු වන 1. පිනි 1. පිනි 1. පිනි	5, 96 14, 42 8, 46	. የ የ ዓ የ	4.55 3.70 0.85	4. 53 2. 01 5. 53	.4 98 7.05 2.07	4.05 3.01 -1.04	6. 07 0. 63 44. 44	5, 44 1, 03 4, 41	4.82 8.87 0.5	3, 81 1, 63 -2, 18	3, 89 2, 15 -1, 74	59 88 55 18 12 30
Pool Elevation End of Month Maximum Minimum	158. 37 160. 37 158. 37	159, 76 159, 76 157, 50	163.0± 163.06 159.76	164, 59 165, 06 163, 06	164, 97 164, 97 164, 37	165, 05 165, 32 164, 70	164, 48 165, 16 164, 38	163, 11 164, 50 163, 11	161, 16 163, 11 101, 16	159, 42 161, 16 159, 42	157, 55 159, 42 157, 55	155, 40 157, 55 155, 40	
Pool Content EDM (1000 AC. FT.)	2256. 88	2396.00	2747, 17	2919.98	2963, 91	2973, 21	2907.34.2	2752.72	2541 39	2351, 48	2177. 25	1977. 10	
	ť		, ()	Z <u>4</u>	<u>u</u> u	Ω 4 Σ	α 0 4	> 4 1	Z	Š	O O O	<u>១</u> ភ	TOTAL
B. A. STEINHAGEN LAKE	- - -						:	•	•				
Inflows(1000 AC.FT) Avg 1908 thru 1988 WY 1988	80.8 181.4	155. 6 226. 1	286. 6 299. 2	430.3 442.3	435, 9 234, 0	504. 0 533. B	498. 4 376. 3	579. 9 186. 3	295.2 208 1	148.9 214.1	87. 7 208. 5	72. 7 192. 5	3576.1 3302.7
Releases(1000 AC.FT) Avg 1952 thru 1988 WY 1988	102 1 172.6	142. 6 225. B	250.9 287.7	322. 6 446. 5	231.8 233.1	421. 5 524. 5	375. 6 375. 1	547. B 185. B	306.8 203.7	188.9 207.4	129. 6 198. 6	114. 4 186. 0	3274. 6 3246. 9
Rainfall (inches) Avg 1970 thru 1988 AY 1988 Deviation	3.87 0.78 -3.09	5, 34 9, 67 4, 33	5, 54 8, 27 2, 73	4, 35 0, 19	3.86 2.41 -1.45	4.22 6.74 5.52	4, 15 2, 85 -1, 30	6. 42 1. 91 -4, 51	5. 69 4. 67 -1. 02	3.17 5.31 2.14	3.04 2.17 -0.87	4. 17 2. 00 -2. 17	53, 82 51, 32 -2, 50
Pool Elevation End of Month Maximum Minimum	82, 19 82, 19 81, 40	81, 96 83, 19 81, 67	82, 55 83, 66 81, 82	82, 22 82, 89 81, 86	82, 15 83, 00 83, 12	82. 63 82. 96 81. 80	82, 43 82, 96 81, 98	82. 04 82. 99 81. 67	81. 96 82. 34 81. 44	82, 04 82, 77 81, 31	82.35 82.99 82.04	82, 49 82, 60 81, 10	
Pool Content EDM (1000 AC. FT )	69 '68	80. 79	90, 47	84.00	83, 13	89, 28	89 98	81.77	80, 79	81 77	85 65	87. 45	

	DCT	NOV	DEC	NA S	FEB	ደ ልል	APR	MAY	NOS NOS	JUL	AUG	SEP	TOTAL
BENBROOK LAKE												·.	
Inflows(1000 AC.FT) Avg 1924 thru 1989 WY 1988	C; 0	2. 4 1. 0	4.5. 4.6.	2.8 0.7	5.7	6.9 1.4	8.8 0.7	11, 5 0, 3	6.4 8.0	1.7	# 83 # 0	નું લ્ ઇ 4	53.8 14.4
Releases(1000 AC_FT) Avg 1993 thru 1988 UY 1993	# n = =	က် လ ကိုလ်	9 Ei	# 0 6 4	ଷ ପ ଅ ପ	0 0 0	4.0 E. 4	80	11.2 0.8	2 0 1 1 1	₩. 19.19	9.9 7.7	ਜ਼ਾਜ਼ ਦੇ ਇੱ ਬਾਜ਼
Rainfall (inches) Avg 1953 thru 1983 WY 1988 Deviation	ର ପ୍ରମୁ ଫୁଲ୍ଟ ୟୁନ୍	2 10 3.06 0.96	1 83 2 11 23	11.55 0.53 -1.02	1,80 0,62 -1,18	. 2. 37 1. 23 -1. 14	3.59 1.55 -2.04	4.33 1.00 -3.38	6. 6. 0 4 5. 0 4 5. 0	2, 29 1, 46 -0, 83	2 00 1,17 -0.83	9.5.93 8.83	31, 53 7, 04
fooi Elevation End of Month Maximum Minimum	691, 40 692, 15 691, 40	691, 24 691, 40 691, 22	690, 73 691, 24 690, 57	690, 64 690, 73 690, 64	690, 57 690, 64 690, 57	690, 48 690, 66 690, 48	690, 05 690, 48 690, 05	689, 26 690, 05 689, 26	689 60 690 10 <b>6</b> 89 26	558, 70 659, 62 688, 70	687. 06 688. 70 687. 06	685, 65 687, 06 685, 52	
Pool Content EDM (1000 AC. FT.)	ව. වැ.	78 19	76. 41	76 09	75, 85	75.54	74. 06	71.40	72. 54	69. 54	64. 교육	62.96	
	OCT	>0 N	DEC	NA N	FEB	MAR	APR	₩ }	NOO	JU.	AUG	SEP	TOTAL
JOE POOL LAKE			•.,										
Inflows(1000 AC.FT) Avg 1987 thru 1988 WY 1988	0.9	ក ជល់	4, Q ≒ N	0,0 4 p	4 . T	n m in in	ਜ਼ ਜ ਲ ਲ	8. <del>1</del> . 1	6. 1 1. 1	1.8 1.7	## 8 K	os es esi esi	42.3 20.5
Relasses(1000 AC_FT) Avy 1987 thru 1988 WY 1988	m m o o	ტ <b>ტ</b> ტ ტ	0 0 0 0	0 0 0 0	0 O	ო <b>ო</b> ი ი	ი <b>ი</b>	თ თ 0 <b>0</b>	00	0.0 4.4	ო დ 0 <b>0</b>	6 6 6 6	បុ
Rainfall (inches) Avg 1986 thru 1983 WY 1988 Deviation	3.00 0.45 3.53	3. 12 4. 85 1. 73	2, 53 3, 58 1, 05	0.36 0.71 -0.15	2.94	1, 15 1, 50 0, 35	2. 09 1. 59 -0. 50	4, 49 0, 75 -3, 74	4. 55 41. 41.	5.00 44.00 7.40	0.96 0.51 -0.45	3.56 3.17 -0.39	32, 16 23, 51 -8, 55
Pool Elevation End of Month Maximum Minimum	508, 42 508, 93 508, 42	508, 49 508, 53 508, 32	508, 92 508, 94 508, 38	508, 88 508, 92 508, 83	508.92 508.96 503.75	508, 97 509, 00 508, 92	508. 77 509. 02 508. 77	508, 36 508, 77 508, 34	507, 98 508, 52 507, 98	507, 38 507, 98 507, 38	506, 62 507, 38 506, 62	506. 24 506. 70 506. 09	
Pool Cantent EDM (1000 AC. FT.)	91.80	92 16	94, 37	94, 17	94.37	94. 63	93. 60	91. 49	89. 57	8 <b>6. 5</b> 8	82 87	81.05	

oov conscors	001	NON	DEC	J. A.	FEB	A A	APR	¥ ¥	NOO	JUL	AUG	SEP	TOTAL
Inflows(1000 AC. FT) Avg 1987 thru 1988 WY 1988	0 O	49.49 10.10	77.1	17.5 17.7	11.0 11.5	9 6 8 6	ม ช.ช.	9.6	4. E.	, vị vị s - a		13.7	153.8 154.6
Peleases(1000 AC.FT) Avg 1987 thru 1988 WY 1988	<b>0</b> 0	0 0	0 0	0 0	0 0	0 O	0 0 11 11	<b>н</b> н ф б	0.0	00	0.0.1	0.0	1. 4. 1. 10.
Rainfall (inches) Avg 1987 thru 1988 WY 1988 Deviation	2.09 1.40 -0.69	4 82 6. 10 1. 28	3, 33 5, 00 1, 67	1,76 1,25 -0,51	3, 14 0, 60 -2, 54	2. 14 2. 50 0. 36	1, 57 3, 10 1, 53	5, 55 1, 90 -3, 65	4 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2, 13 2, 60 0, 47	1.85 0.50 1.35	3. 73 9. 50 5. 57	36, 26 28, 85 +6, 41
Pool Elevation End of Monto Maximum Minimum	571. 50 571. 55 571. 33	573, 40 573, 40 571, 50	588, 90 588, 80 573, 40	591, 06 591, 06 553, 80	592, 29 592, 29 591, 06	593, 15 593, 15 592, 29	593. 37 593. 41 593. 15	593, 16 593, 37 593, 07	593, 05 593, 50 593, 05	592, 63 593, 63 59 <b>2, 63</b>	591, 95 592, 63 591, 95	593.03 593.04 591.93	
Pool Content EOM (1000 AC. FT.)	19. 10	24.63	100, 95	117.36	126.86	133, 75	135, 55	133, 83	132. 94	129, 56	124, 19	132.78	
	001	202	DEC	J A N	FEB	T A A	A R R	F A	S S S S S S S S S S S S S S S S S S S	JUL	AUG	SE	TOTAL
LEWISVILLE LAKE Inflows(1000 AC.FT) Avg 1924 thru 1988 WY 1988	0.04 0.0	29.5 27.8	27. 1 65. 3	24.7 20.3	44 13. 6 13. 6	57.9	70.6 8.6	9 9 (4) 40 (2)	54. 4 11. 9	17.6 8.4	01 4 0	27.7	500. 6 187. 7
Releases(1000 AC.FT) Avg 1955 thru 1998 WY 1988	26. t 5. 2	38.1 5.1	38 5 15.4	25.2 13.8	28 15.7	35 5 13.1	35. 4 13. 5	66. 6 15. 9	78. <del>9</del> 11. 0	39. 5 10. 6	28. 6 10. 1	เก.ก. ต.4	461.7 134.8
Rainfall (inches) Avg 1955 thru 1988 WY 1988 Deviation	3. 52 0. 14 3. 38	2, 50 6, 16 3, 66	4, 99 2, 05	1. 62 0. 83 -0. 79	2, 22 0, 78 ±1, 44	2, 91 1, 86 -1, 05	3, 97 1, 55 -2, 42	5, 07 0, 59 -4, 48	3, 30 4, 46 1, 16	3. 52 1. 47	2.06. 0.52 -1.54	6.00 6.44 6.00	35, 13 27, 88 -7, 25
Pool Elevation End of Month Maximum Minimum	512,04 512,75 512,04	512, 75 512, 75 511, 89	514, 74 514, 74 512, 19	514, 79 514, 95 514, 73	514, 34 514, 79 514, 34	513, 85 514, 39 513, 80	513, 13 513, 88 513, 13	511,85 513,13 511,81	511.21 512.23 511.21	510, 24 511, 21 510, 24	508.89 510.24 508.89	508, 48 509, 10 508, 38	
Pool Content EOM (1000 AC. FT.)	391.80	406. 99	451.60	452. 75	442, 42	431. 32	415, 29	387 82	374, 79	356. 23	332. 36	325, 38	

	001	S C N	DEC	NAS	FEB	A A	A R	ΑĀ	200	JUL	AUG	SEP	TOTAL
GRAPEVINE LAKE												·.	
Inflows(1000 AC.FT) Avg 1924 thru 1988 WY 1988	11.0	6.0 5.6	6.9	9.9	13.0	16.0 5.7	22. <b>5</b> 5. 0	29.7	16. 0 9. 1	. v. c. • a	 4.44 8.40	ခောင် ကိုက်	142.3 64.8
Releases(1000 AC.FT) Avg 1953 thru 1988 WY 1988	4 () 4 ()	4 0 4 0	10.1 2.0	(1) (1)	5.6	1.5	9, ±4 4 to	ઇ ઉત્ત ઉતા	16.8 2.4	អ ស៊ីស្ ស ផ	10.1 6.8	O 0 10 d	107. 7 36. 3
Rainfall (inches) Avg 1953 thru 1988 WY 1988 Deviation	6 0 E	2 38 5 03 5 65	1, 95 3, 53 1, 58	1, 57 0, 61 -0, 76	1, 93 0, 85 -1, 08	2. 63 1. 62 ~1. 01	3.72 1.26 -2.46	4, 89 1, 13 -3, 75	3. 02 1. 5. 5. 1. 5. 5.	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	1, 97 0, 57 -1, 46	E. 20. 1 60.44 80.44 40.44	មាន ១៣ ១៣ ១៣
Pool Elevation End of Month Maximum Minimum	501, 62 532, 23 531, 62	531, 29 531, 30 530, 82	532, 80 532, 80 531, 24	533, 17 533, 17 532, 80	533 43 533 48 533 17	533, 73 533, 73 533, 48	533, 80 533, 82 533, 72	533, 51 533, 80 533, 41	533. 89 534. 33 533. 51	503.96 503.89 502.96	531, 50 532, 46 531, 50	530, 46 531, 57 530, 45	
Pool Content EDM (1000 AC. FT.)	153. 41	155, 20	165. 45	168,03	170, 20	171.97	172. 47	170. 41	173. 11	1cá. 56	156. 60	149, 74	
·													
	DCT	NOV	DEC	NAU	FEB	MAR	APR	¥ ¥ ¥	NOS.	JUL	AUG	SEP	TOTAL
LAYUN LAKE Inflows(1000 AC.FT) Avg 1924 thru 1988 WY 1988	13.7 1.8	19.2 27.6	24 6 67 1	24. 7 33. 1	36. 2 24. 1	38.8 8.8 4	50. 7 24. 6	9.69 9.09 9.03	37.5 11.1	12. 5 11. 2	မ. ၅ ၀ 4	11.6 8.8	339. 1 4. 255. 4
Peleases(1000 AC FT) Avg 1954 thru 1988 WY 1988	0.0	11.8 0.0	21 1	17.8 0.0	4. 40 Ø 10	23 10. 4	16.0 6.8	50.5 0.0	36. 0.0	9.4° 0.0	6.0	H 0	(4) (4) (5) (6) (6)
Rainfall (inches) Avg 1954 thru 1988 WY 1988 Deviation	3.66 0.73 -2.93	2.87 5.78 2.91	2.50 3.88 1.28	1.91 3.15 1.24	2, 49 1, 08 -1, 41	3, 25 2, 12 -1, 13	4 26 3 92 -0.34	5, 59 0, 86 -4, 73	3.39 5.77 2.38	0.23 0.23 0.28 0.28	1, 99 1, 13 -0, 86	4 4 0 4 4 0 8 0 8 0	38.93 35.68 25.25
Pool Elevation End of Month Maximum Minimum	487, 52 488, 64 487, 52	488. 14 488. 14 467. 27	490, 93 490, 93 488, 10	491.86 491.86 450.93	492, 05 492, 28 491, 78	492, 09 492, 33 492, 01	491.94 492.33 491.94	491.04 491.94 491.02	490, 14 491, 14 490, 14	489, 00 490, 14 489, 00	487, 42 489, 00 497, 42	486. 74 487. 59 485. 69	
Podl Content EDM (1000 AC, FT.)	367, 15	378.87	434. 07	453, 54	457, 60	458.45	455 <u>.</u> වූප	436.34	417, 99	395, 45	365, 28	352. 68	

Inflavation AC FT)  Any 1888 thru 1888	NAVARRO MILLS LAKE	100	NO.	DEC	N N	FEB	МАВ	APR	¥	N S S	JUL.	<b>0</b> 00 √	SEP	TOTAL
Charles   Color AC, FT   Color AC,	Inflows(1000 AC.FT) Avg 1907 thru 1988 WY 1988			0. 1		0,4	<b>~</b> i ∙i	7.6		4 (4				8 6
Continue	Releases(1000 AC.FT) Avg 1963 thru 1988 WY 1988	% o <b>4</b> o			90				က်ဝ	6.0				
March   422 55 422 59 426 50	Rainfall (inches) Avg 1963 thru 1988 WY 1988 Deviation			はころ	~ ~ 0		લંભ૭	ര് ച്ച്	च छ ज क्षानी		00.0-00	ના ના છે. લો છે નો	W O 4	ம் எர்
AC. FT.)  Ab. 38	Pool Elevation End of Month Maximum Minimum				व संबं	ក្រុសូស ភេសស	មាល់ មាល់ ស្លាល់	ता के ता वा वो वो	ដូម្មី ភូមិ	αωω ωπω	0 <b>00</b> 0	เมอก	നനത്	
OCT   NOV   DEC   JAN   FEB   MAR   APR   MAY   JUN   JUL   AUG   SEP	Posl Content EOM (1000 AC. FT.)				<b>7</b>	4	in.	6.0	4	က်	6. 0.			
1000 AC.FT)  8 thru 1988  9 7 3.0 4.9 4.0 6.4 6.7 10.3 12.6 7.3 1.7 0.7 1.9 63.  11000 AC.FT)  11000		001	NON	DEC	J MA	FEB	AA AR	4 8 8	MA Y	NOO	JUL	AUG	SEP	TOTAL
FT)	DARDWELL LAKE			٠										
FT)  11.5	Inflows(1000 AC.FT) Avg 1938 thru 1988 WY 1988		0 m											
41.56       2.83       2.63       1.69       2.65       2.88       3.37       5.33       3.60       2.23       1.90       3.79       37.4         0.43       6.02       3.94       0.68       2.72       3.40       1.47       1.85       2.56       2.26       0.90       4.26       30.5         -4.13       6.02       3.94       0.68       2.72       3.40       1.47       1.85       2.56       2.26       0.90       4.26       30.5         -4.13       3.19       1.01       -1.01       0.13       0.52       -1.90       -3.48       -1.04       0.03       -1.00       0.47       -6.9         419.26       419.89       421.28       421.28       421.17       421.05       420.96       420.47       419.78       419.64         419.26       419.26       421.18       421.14       421.14       421.05       421.05       421.04       420.96       420.47       419.78       419.34         46.26       49.40       55.48       53.29       52.90       52.90       52.15       50.42       480.02       47.54       47.54	Peleases(1000 AC FT) Avg 1965 thru 1998 WY 1988		4.0							00				ei e
419. 26 419. 89 421. 88 421. 28 421. 28 421. 17 421. 05 420. 96 420. 47 419. 78 419. 419. 70 419. 70 421. 83 421. 98 421. 78 421. 31 421. 22 421. 37 421. 02 420. 47 419. 78 419. 25 419. 18 419. 63 421. 18 421. 14 421. 05 421. 05 421. 04 420. 96 420. 47 419. 78 419. 78 419. 78 419. 78 419. 78 419. 78 419. 78 419. 78 419. 78 419. 78 42. 48. 02 47.	Rainfall (inches) Avg 1966 thru 1988 WY 1988 Deviation	4. 56 0. 43 -4. 13	2.83 6.02 3.19	4000	404	9 12 12		ल संस	മ. ല. ല വ ത 4	ற் வ் ⊶்		404		4 10 0
, 46. 26 48. 40 55. 48 53. 29 54. 78 53. 29 52. 90 52. 47 52. 15 50. 42 48. 02 47.	Pool Elevation End of Month Maximum Minimum	419, 26 419, 70 419, 25	419, 89 419, 90 419, 18	ជាយលា	21. 2 21. 8 21. 1	21. 6 21. 6	22.22	421. 17 421. 31 421. 05	421.05 421.22 421.04	ውጠው	420, 47 421, 02 420, 47	419. 78 420. 47 419. 78	0.0.0	
	Pool Cantent EUM (1000 AC. FT.)	46. 26			က်	4.7	က်	αi			50. 42			

### Risus dinijer Nos

BAKKER RESERVOIR	0CT_82_M	NOV 87	VEC 87		କଞ୍ଜିନ୍ଦି କଥା ଓଟ ଆଧାର	ав Эо́ы	AHR 188	MAY BE	HA NOT	11.1 SB	F8 90 <del>8</del>	68 4 <del>1</del> 5	년 된
Inflowerrows Ac.Ft., Aug 1945 thru 1968 FY 88	ે . • •	ភ្ល ទំនា	47. 4.31	n 9 n	% <del>-</del>	No.	၁ ခု ၁ စိ	5 <b>m</b>	2 N 2 N	- n	05 29	173 - 4 1. 0j	កា ស មា ៩ មា ៩
Felgases(1000 Ac.Ft.) Aug 1964 thiu 1982 E7 88	0.0 1.1	t. 2	- J	01 <del>-</del> 1	û: ~ Gi < .	ងក្ មាំដ	÷ ñ	, n 4	6 B	e. D	መን ጠን	Ť ~; 35 ni	90 m 12 m 20 m
ainfall(Inches) Aug 1945 thru 1988 FY 88	3.71	3.67	9, 11 111	ਲ • ਦ ਹੈ ਹੈ ਹੈ ਹੈ	0.00	m 0	8.03 88.03	4.44	m m O ~. ⊅ (u	7.18 1.50	9.50 9.20 9.20	4.17 1.50	5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
	74.84 74.84	74.27 77.41 77.48	74.38 89.68 99.66	73.70 76.41 76.41	79.67 74.01 74.61	m m + 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	73.65 95.03 73.65	5 M A B B B B B B B B B B B B B B B B B B	28.87 28.18 28.82	73.79	200 m	
ნების ეგიონეთა 8,0.16. ფილენ მეგანას	:	·C	ē	æ	<b>5</b> -	1.7.	ā: -	<u>5</u> ,	2	+29	9	Þ	
4 <u>000(F9 RESERVOIR</u> Inflows(1000 Ac.Ft.) Aug 1948 thru 1989 EY 88	1.5	<b>.</b> 0 11 0 €	7.1	១ ហ ហ	an r×.	w. <b>1</b> 4.0	71 0 10 TO	ტუ (- ი.	3 0 5 m	ភព ភព	3) 4 > 0.4	યાં <del>ન</del> વ્યા∵	4.27
Re]easms(1000 Ac.Ft.) Aug 1954 thru 1938 ' FY 63	) ". !	@ ŋ 	n o	(ير. ما • • نه. العا	X 2	% <del>=</del> = %	00 70 Jr	0.1	ភ្.ក ភ.ក	ធី ។ ១ ៤	NI TO	কা ক কুল কুল	en or En I
Painfall(Tuches) And 1948 thro 1983 Er st	\$ 6 3	ල <u>් 1</u> උදි <del>ද</del> ල ව	3.35	91 9 - 1 1 - 1 10 - 1	No.	S. H.	1 h	4. 4.7. 4.7. 4.7. 4.7. 4.7. 4.7. 4.7. 4	हा क १ म १ जिल्ला १ जिल्ला	\$ 1 * 0 0 0	را بر برا بر برا	4.000	20 mm
	71.81	1.50 1.38 1.64	71.97	71.79 70,00 71.69	2. T. S. T.	85,13 86,13 71,65	46.02 46.07 76.16	73 . 85 85 . 56 7 . 59	71.79 94.95 91.75	78.75 8.75 1.75	80.17 80.17 81.78	74.04 78.78 71.68	
Pro) Centent E.D.M. (1998 Ac.Ft.)	Ť)	7	ç.	<del>:</del>	ē.	1.30		ţ	;	₫ł	Ξ	î	

		DC F	20%	DEC	NA N	FEB	MAR	APR	M Y	<b>N</b>	JUL	AUG	SEP	TOTAL
WHITNEY LAKE	LAKE													
ū	Inflows(1000 AC.FT) Avg 1899 thru 1988 WY 1988	115.8 4.6	64, 6 17, 6	<b>4 ១</b> <b>3</b> ១១	<b>54.8</b> 18.5	58.6 12.1	68.1 17.0	129. 9 8. 9	263.9 10.1	168.7 67.1	94.1 7.3	67.7	103. 0 14. 6	1254. 8 210. 3
œ.	Releases(1000 AC.FT) Avg 1952 thru 1988 WY 1988	63 E	51, 4 21, 3	0 7 KO	4.0 9.0 10.0	4. (A (y, C) (b, u)	56. 50.50 50.50	60. 4 19. 9	189. 3 1. 5	173.4 26.3	7 6.6 6.6 7.0	49.6 3.1	63.7 8.7.8	9 4 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
e. •	Rainfall (inches) Avg 1953 thru 1988 WY 1988 Deviation	9 55 0 45 54 6	6. 6	2 01 1.59	1,59	4. G. G. A. G. G. A. G. G. A. G. G. A. G. A. G. A. G. A. G. A. G. A. G.	ф 8 4 4 8	3.58 1.39 -2.19	4 20 00 10 10 10 10 10	3. 49 7. 64 4. 15	2.34 0.41 -1.93	2 8 9 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	3. 37 62. 53 255	33.41 35.27 1.85
e G	Pool Elevation End of Month Maximum Minimum	523 75 529 20 527 75	507, 17 507, 84 507, 17	525, 43 527, 17 526, 38	515 43 526, 42 525, 41	524 73 525, 45 524, 73	524, 89 524, 74 524, 43	523, 47 524, 60 523, 47	523. 41 523. 47 523. 28	525, 18 526, 35 523, 41	523, 53 513, 18 513, 18	55.5 55.3 54.5 52.88	522, 56 522, 88 522, 04	٠
ñ.	ool Cantent EOM (1000 AC. FT.)	513, 19	501.00	486. 75	468.75	456, 52	4 60 64	435, 25	434, 26	464.34	436. <b>2</b> 5	425. 31	421.91	
<b>UTT</b>							٠							
** 0		100	202	DEC	SAN	FEB	E A E	APR	MAY	255	JUL	AUG	SEP	TOTAL
AGUILLA LAKE	LAKE													
11	Inflows(1000 AC.FT) Avg 1982 thru 1988 WY 1988	4 0 4	1. 6 5. 6	11.0 13.8	ω. 4. Ο Ο	9, 9 9, 0	9.20 0.00	យ ⊶ ÷	0.0	10. 3.2 5.	0.0	0.0 4 w	69 m	51. 6 42. 7
فّ	Paleases(1000 AC.FT) Avg 1982 thru 1935 WY 1988	9 0 4 0	0.0	12 €.	0, či 0, ¢	ស់ មេ ០១	ણ. 4. હાલ	2 H	0.7	0.1	1. 0. 1.	0 0 0 H	0 <del>0</del>	5. 20 7. 30 7. 30
ά	Rainfall (inches) Avg 1982 thru 1988 WY 1988 Deviation	7.55 0.35 -7.20	2. 99 6. 08 3. 09	4, 18 3, 84 -0, 34	1.00 0.60 -0.40	년 83 84 84	2, 28 3, 70 1, 42	1, 74 1, 05 -0, 69	0, 0, 5, 5, 5, 6, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5, 5,	6. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.	0.73 0.82 -0.51	4. 9. 4. 4. 6. 4. 6. 4. 6. 4. 6. 6. 6. 6. 6. 6. 6. 6. 6. 6. 6. 6. 6.	5, 46 4, 73 -0, 73	40, 43 29, 57 -10, 86
ă.	Pool Elevation End of Month Maximum Minimum	536, 99 537, 41 535, 99	538, 38 538, 38 536, 92	541, 07 541, 40 538, 33	537, 51 541, 07 537, 47	537, 93 538, 50 537, 47	538, 33 538, 33 537, 56	537, 43 538, 06 537, 42	537, 01 537, 43 537, 00	537, 35 537, 74 537, 01	536, 61 537, 35 536, 61	535, 89 536, 61 535, 89	535, 86 535, 89 535, 36	
<u>r</u>	Fool Content EOM (1000 AC. FT.)	50, 71	라 라 31	65, 67	52 33	53. 79	54, 22	52 13	50.77	51.87	49, 50	47.27	47. 18	

		001	NON.	DEC	NA.	FEB	MAR	APR	¥ ¥	S C N	JUL	AUG	SEP	TOTAL
3	MACO LAKE											•	·.	
	Inflows(1000 AC.FT) Avg 1907 thru 1988 WY 1988	73.9 1.3	15.3 7.8	20.5	17.0	23. 6 11. 0	25. 6 11. 4	43.8 7.1	65.6 3.6	33.0 49.3	. 0. 0 . 0. 0	7.6	16.0 7.2	304. 9 124. 4
	Releases (1000 AC.FT) Avg 1966 thru 1988 WY 1988	7.4	11.1	0.0 0.0	15.0 0.04	16.9 5.1	26. 0 8. 1	28.3 9.6	57.3 0.1	37. 2 39. 8	12.2 0.1	0.0 10.41	4. <b>7</b> 0. 1	230.8 63.0
•	Rainfall (inches) Avg 1963 thru 1988 Wy 1988 Deviation	3 75 1.27 -2.49	2, 65 2, 75 2, 11	23. ±44 1. 46 1. 46	b. 67 0 58 -1, 09	2, 23 1, 93 -0, 30	9. 4. 4. 9. 9. 9. 9. 9. 9. 9. 9. 9. 9. 9. 9. 9.	3.31 1.34 -1.97	4.80 1.07 -3.73	ଲ ନ୍ଧ୍ର ଓଡ଼େଖ ଓଡ଼	2.24 1.07 -1.17	2, 28 0, 92 -1, 36	6.4.0 6.4.0 8.6.0 8.00	34, 21 30, 47 -3, 74
	Pool Elevation End of Month Maximum Minimum	452, 94 453, 36 452, 84	453, 28 453, 29 452, 74	454, 83 454, 83 453, 25	455, 08 455, 38 454, 88	455, 39 455, 79 455, 08	455, 18 455, 39 455, 05	454.96 455.22 454.94	454. 32 454. 96 454. 52	454, 96 459, 44 454, 52	453, 80 454, 96 453, 80	452, 66 453, 80 452, 66	452. 64 452. 66 451. 84	•
95. 80. 10.	Fool Content EDM (1000 AC. FT.)	133. 89	136. 95	148.32	149, 77	152,02	150, 49	1.48.90	145. 73	148.90	140. 61	132. 65	132. 51	
VII-49		001	NOV	DEC	CAN	FEB	AAR	APR	AA Y	NO	חטר	AUG	<b>d</b> <b>3</b> 5	TOTAL
E)	PROCTOR LAKE			٠.										
	Inflows(1000 AC.FT) Avg 1922 thru 1988 WY 1988	ы о 4 н	1.9	++ ++ RD 55	6.0 4.0	4 B 6 C	4. t. 0. ti	8) ±	8.74 8.4	9.0	11.0 11.0	1.1	νι ο ® 4	51. <b>4</b> 92. 3
	Releases(1000 AC_FT) Avg 1964 thru 1988 WY 1988	0.0 8	01 O	0 0 0 0	เว o. 4 เก	\$ G 6	4.0 8.5	8.0 0.4	9.7	13. 7 32. 4	13.9 26.3	សុស្ ព 4	യ സ സ് സ്	10 4-0- 0-4
·	Rainfall (inches) Avg 1964 thru 1988 WY 1988 Deviation	2. 90 0. 17 -2. 73	1, 97 2, 13 0, 16	1, 40 1, 29 -0, 11	1, 42 0, 23 -1, 19	1.70 0.33 -1.37	2, 12 1, 23 -0, 89	2. 93 1. 54 -1. 39	4.78 3.21 -1.57	8.9.8 8.9.7 7.9	1.61 3.25 1.64	2. 21 0. 20 -2. 01	3. 64 2. 48 -1. 16	30,09 25,44 14,65
	Pool Elevation End of Month Maximum Minimum	1161. 07 1161. 70 1161. 06	1160, 99 1161, 07 1160, 90	1161.00 1161.03 1160.87	1160.94 1161.01 1160.92	1160. B6 1160. 94 1160. B6	1160, 61 1160, 90 1160, 59	1160. 19 1160. 63 1160. 19	1160.35 1160.39 1159.61	1166. 90 1170. 29 1160. 35	1163. 13 1166. 90 1163. 13	1160.96 1163.13 1160.96	1159.85 1160.96 1159.75	
	Pool Content EDM (1000 AC. FT.)	55, 20	54.85	54.89	54. 63	54. 28	53.20	51. 42	52.09	84. 72	64. 74	54, 72	20.00	

	OCT	NOV	DEC	JAN	FEB	MAR	APR	A ×	א	JUL	AUG	SEP	TOTAL
BELTON LAKE											•	·.	
Inflows(1000 AC.FT) Avg 1908 thru 1988 WY 1988	30. 4	20.8 4.8	30.2	29.7	34. 9 7. 3	37.0	60. 4 5. 0	97. 1 5. 4	<b>51.6</b> 70.8	, 4, 4, 4, 4,	13.9	64 10 10 10 10 10 10 10 10 10 10 10 10 10	455.0 145.3
Releases(1000 AC FT) Avg 1995 thru 1988 WY 1998	22. 4• 1. 5	20.7	18.1 1.2	25.6	24.B	34, 7 5, 5	29.8	5.0 7.0 0	61.0 39.8	49.6 27.3	17.5 44.8	# Cd	368.0 137.4
Rainfall (inches) Avg 1954 thru 1988 WY 1988 Deviation	9 9 9 9 9 8 8 8	2 55 4.17 1.62	1, 95 3, 26 1, 31	1,68 0.41 -1.27	2, 30 1, 23 -1, 07	2. 11 2. 60 0. 49	3. 26 0. 98 6. 28	4, 46 1, 50 -2, 85	3.56 5.39 1.83	1.94 3.61 1.67	2, 29 0, 98 -1, 31	84 .0. 84 .0. 84 .0.	8 8 1 1 6 8 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Pool Elevation End of Month Maximum Minimum	593, 31 593, 96 593, 96	593.53 593.53 593.13	594, 63 594, 03 593, 35	554, 02 594, 05 593, 99	594, 23 594, 23 593, 98	594, 09 594, 35 594, 06	593, 78 594, 09 593, 77	592, 89 593, 78 592, 87	594, 64 596, 03 592, 89	593, 49 594, <b>64</b> 593, 49	589, 65 593, 49 389, 65	589, 04 589, 65 588, 87	
Pool Content EOM (1000 AC. FT.)	433, 47	435, 93	442, 36	442. 23	444. 85	443.10	439, 26	428.3\$	449, 99	435. 68	350, 17	363, 23	
	OCT	<b>N</b> 00	DEC	S N	FEB	MAR	A R	¥	N O	JJ.	AUG	S E B	TOTAL
STILLHOUSE HOLLOW LAKE													
1410WS/1000 AC.T.) Avg 1924 thru 1988 WY 1988	13.5 1.6	9. 4 4 V	12.9	15.72	21.2	5. 9 4. 6.	24.5	43. 1 2. 9	16. 4 4.9	10.1	4.4	10.0	203. 1 53. 5
Releases(1000 AC.FT) Avg 1968 thru 1988 WY 1988	1.7.0	7.7	93.4 14.4	14.8 4.9	12. ±	15.6	17.3 1.8	29.7	23.9	25.8 48.7	ы о в- о	ν. ν. ο	1. 6.9.0 8.9.8
Rainfall (inches) Avg 1967 thru 1988 WY 1988 Deviation	9.71 0.35 -3.36	2.50 4.77 2.27	1, 95 3, 47 1, 52	1.56 0.41 -1.15	2. 43 1. 13 -1. 30	2.45 0.91 0.06	2.94 1.41 -1.53	4, 54 1, 07 -3, 47	3.71 3.36 -0.35	9.4.5. 10.00 10.00	2. 40 0. 61 -1. 79	3.52 1.04 84	33.87 24.28 -9.59
Pool Elevation End of Month Maximum Minimum	621, <b>85</b> 622, 07 621, 34	622, 32 822, 32 821, 82	622, 53 622, 60 622, 16	622, 26 622, 53 621, 98	622. 59 622. 59 522. 36	622. 22 622. 72 622. 09	622.09 622.31 622.04	619, 67 622, 09 619, 67	620.25 620.27 619.60	612.00 620.25 612.00	611. 47 612. 00 611. 47	610.99 611.47 610.94	
Pool Content EOM (1000 AC, FT.)	234, 74	237, 77	239, 13	237, 38	239. 52	237. 12	236. 28	221. 02	224. 62	177, 33	174, 58	172, 12	

	00.1	)CN	DEC	S N N	FEB	MAR	A P	¥ ∀	NOS	JUL	AUG	SEP	TOTAL
GEORGETOWN LAKE											•	·.	
Inflows(1000 AC FT) Avg 1980 thru 1988 WY 1988	12.1	B. 0 1. 3	17.9 1.3	₽, ± 4 Ω	19. 0 1. 0	16.5 1.0	7. s	22.3 0.7	4. 6. 9. 9.	15,7 1.3	ю о <b>9</b> 4	<b>6</b> 00	182.1 12.3
Releases(1000 AC, FT) Avg 1980 thru 1988 WY 1988	1.6 0 5	1. 4.0	4.0 ± 10	0 0 6 1/2	8 C 8 C	7. 0. 3	ମ ୦ ଅଧ	4, O U W	V 0 E	ы. 6. о. 6. б.	9.0 9.0	# @ # @	54.0 5.6
Painfall (inches) Avg 1981 thru 1983 WY 1988 Deviation	.ଅ. ୧୦.୨ ୧୯.୩ ୧୯.୩	3.89 7.38 3.39	원 (연 (Q ) 84 : 1 (Q ) 87 : 1 (Q )	1: 02 0 47 -0. 55	2, 69 0, 74 -1, 95	2. 44 1. 79 -0. 65	1, 99 2, 15 0, 16	3.110 3.11 4.59	9.03 7.03 7.07	1, 50 1, 25 -0, 25	1.82 2.17 0.35	1.39	36.83 87.83 84.84
Pool Elevation End of Month Maximum Minimum	790, 10 790, 61 790, 10	790, 33 790, 35 789, 97	798, 70 790, 70 790, 10	750, 76 790, 78 750, 70	790, 73 790, 76 790, 70	790, 70 790, 75 790, 63	790.31 790.71 790.31	789, 97 790, 31 789, 97	791, 23 791, 63 789, 97	791, 07 791, 51 790, 85	790, 00 791, 07 790, 00	783. 79 790. 00 788. 7 <b>6</b>	
Paol Content EDM (1000 AC. FT.)	35, 92	36. 21	36. 69	36. 77	36 73	36. 69	36. 19	25.75	37, 38	37, 17	35, 79	34, 28	
·													
	0CT	ògN	DEC	SAN	FEB	ጸቀጽ	APR	МАҰ	25	λ	<b>₽</b> O¢	SEP	TOTAL
GRANGER LAKE			•										
Inflows(1000 AC.FT) Avg 1980 thru 1988 WY 1988	51 10:44 10:54	9.9 8.9	18.4 6.0	9.4	4.9. 4.19.	17.0	9.6 8.4	22. 7 4. 5	42. 6 9. 7	£.ี. ⊘. ⊞ ശ	9.4 6.4	Θ Ο	187.0 57.3
Releases(1000 AC FT) Avg 1980 thru 1998 WY 1988	कृष्यं कस	2.8	4.4.4.7.8	17. 5. 9	0 0 ≠ 0 ₹	19. 10.00	1; U	16. 0 1. 1	0.77 0.03	30.2	დ ო ი ი	4 O	163.6 40.4
Rainfall (inches) Avg 1981 thru 1988 WY 1988 Deviation	4, 33 1, 03 -3, 30	2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	2. 83 1. 89 -0. 94	1, 15 0, 48 -0, 67	1.94	2.31 1.80 -0.51	1. 31 0. 00	5. 23 3. 02 -2. 21	8.86 9.86 9.04	1.30 1.87 0.57	1. 19 0. 39 -0. 80	2. 17 0. 08 -2. 09	32.61 21.68 -10.93
Pool Elevation End of Month Maximum Minimum	504, 33 504, 36 504, 06	505, 23 505, 28 504, 28	504, 66 505, 23 504, 33	504, 28 504, <b>66</b> 504, 66	504, 17 504, 55 504, 17	504, 33 504, 55 504, 08	504, 11 504, 33 504, 05	504.37 504.40 504.11	504, 37 506, 15 504, 26	503, 99 504, 37 503, 99	503. 46 503. 99 503. 46	502. 98 503. 46 502. 93	
Paol Content EDM (1000 AC. FT.)	66. 97	71. 01	68. 44	66.74	66. 26	, 66. 97	62.99	67. 14	67.14	65. 46	63. 18	61. 18	

.

	CANYON LAKE	Inflows(1969 AC.FT) Avg 1915 thru 198 WY 1988	1 ) sesses ( 1 d s	Painfall (inches) Avg 1963 thru 1988 WY 1988 Deviation	Pool Elevation End of Month Maximum Firminum	A Paol Content EDM
		flows(1969 AC.FT) Avg 1915 thru 1988 WY 1988	Paleases (1000 AC, FT) Avg 1959 shru 1959 WY 1988	infall (inches) Avg 1963 thru 1998 WY 1988 : Deviation	inth inth	ol Content EDM
007		31.0 21.9	4 () () ()	0.000 000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.	900, 98 900, 98 900, 98	
202		16 6 25.1	6 0 6 0	5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5	902, 45 902, 45 900, 94	() () ()
DEC		18.5 21.7	4 W 4 0	1. SB 1. 53 1. 11	904, 55 904, 55 902, 48	
NAU		20.7	:- <del></del>	1. 81 0. 72 -1. 09	906, 09 906, 09 904, 55	ָ ני ני
rea		21.2 15.0	ल हिंद स्टेस्स	0,43	907, 27 907, 27 905, 39	€ 8 ± 7 €
MAR		23 5 16.6	7, 02 0.04 0.00	1 34 0. 46	908, 45 908, 45 907, 27	277 40
A R		30. 1 13. 3	21.6 5.3	1.63	909, 01 509, 04 908, 45	980 086
MAY		39.0	24. 8 12. 8	4 55 50.34 0.83	909, 73 909, 77 908, 78	388.05
NOS		35.6 17.3	ದ ಚಿ. ಚಿ.	60 00 00 00 00 00 00 00 00 00 00 00 00 0	909, 09 909, 77 908, 93	382. 74
JUL		53.7	6. 6. 6. 6.	2. 1. 2. 7.9 32. 33	# 11 m	405.65
AUG		18. 2 23. 6	5 m 5 m 64 m	6. 9. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0. 0.	909, 14 911, 81 909, 14	383.15
9 9		(A 44 (A 44 (A 44)	60 de	4 (4 (4)	908, 36 905, 14 908, 76	381. 67
TOTAL		304.2 204.2 204.2	កាត់ ជាតា ពាត	ស្ពេក ១៤៦ ១៤៤ ១៤៤		

## COLORADO RIVER BASIN

		0CT	у О	DEC	JAN	FEB	R AA	APR	¥ ¥	N O O	JUC	AUG	SEP	TOTAL
ğ	HORDS CREEK LAKE													
4	Inflows(1000 AC.FT) Avg 1942 thru 1989 WY 1988	т о о о	0.0 1.0	0.0	00	00	0.0	<b>o</b> o	0.0	0 0 0	00	0.0	<b>0</b> 0 0	4.0 4.0
••	Releases(1000 AC.FT) Avg 1952 thru 1988 WY 1988	0.0	0.0	00	0 0 0 0	00	(၃ ဝ ဝ ဝ	0 0	0.0 4.0	00	00	00	00	K 0 0 0
	Fainfall (inches) Avg 1949 thru 1988 WY 1988 Deviation	2. 63 0. 16 12. 44	1, 46 0, 42 -1, 04	1, 01 1, 49 0, 48	1. 15 0. 10 -1. 05	1, 09 0, 51 -0, 58	0. 34	2. 47 0. 91 -1. 56	3.74 1.50 1.54	3. 10 3. 10 9. 03	1, 89 1, 98 0, 06	2, 13 0, 28 -1, 85	E 4 7 0	0.44 0.40 40.00 40.44
	Pool Elevation End of Month Maximum Minimum	1896, 17 1896, 76 1396, 17	1895, 76 1895, 17 1895, 76	1895, 60 1895, 76 1895, 57	1895.34 1895.60 1895.34	1895, 12 1895, 34 1695, 12	1894, 68 1895, 12 1894, 68	1894, 18 1894, 68 1894, 18	1893, 70 1894, 18 1893, 70	1893, 50 1894, 05 1893, 45	1892.84 1893.50 1892.84	1891, 97 1892, 84 1891, 97	1891, 41 1891, 97 1891, 41	
	Poil Cantent EDM -1000 AC. FT.)	6. 35	6. 18	6. 11	6.01	5. 92	5. 75	5, 56	5.38	5.31	5.07	4. 78	4. 59	
VII-53														
		OCT	>0 <i>N</i>	DEC	24 5	ਸ਼ ਬੁਹ ਬੁਹ ਬੁਹ ਸ਼	E A A A A	APR	AA Y	מסק	اناد	§ N•	Ş	TOTAL
MAP	MAPSHALL FEBD LAKE											•	;	
	Inf.cws(1000 AC.FT) Avg 1941 thru 1988 W' 1988	126.7 24.1	6 E 6 E 6 G	58.0 53.1	77.1	78 03 4	85.8 42.4	114. 0 40. 1	221. 2 50. 6	180. 0 108. 2	95.0	0 9 8 8 8	100 20.64 3.64	1286. 4 77.3. 3
	Meleases(1000 AC, FT) Avg 1944 thru 1988 MY 1953	+ 0 ⊕ 0 € 0 € 0 € 0 € 0 € 0 € 0 € 0 € 0 €	61.3 5.4	<b>6</b> 00,44 4.45	96	in a	70.5	9.50 9.50 5.00	164.9	188. 4 109. 2	129.0	115.0 100.5	(a) (a) (b) (a) (c) (d) (c) (d) (d) (d) (d) (d) (d) (d) (d) (d) (d) (d) (d) (d) (d) (d)	11 10 10 10 10 10 10 10 10 10 10 10 10 1
	Painfall (inche)) Avg 1952 thru 1950 WY 1988 Deviation	0.00 0.40 8	1, 9,7 8,00 6,03	1, 40 0, 68 -0, 72	10.00 10.93 14.00	1, 27 1, 33 1, 44 44	1.54 0.42	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	4, 18 3, 09 -1, 09	3.26 1.53 -1.73	1.85 2.82 0.97	9.01.0 7.00.01	40 M	6 6 4 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
	Dool Elevation End of Month Meximum Minimum	676, 55 673 55 670 59	573.15 673.18 670.59	675.79 673.79 13.18	677, 85 677, 85 679, 79	679-01 679-05 677-25	575 42 679, 01 675, 42	673.98 675.52 673.88	670, 40 673, 88 670, 40	659, 73 671, 72 669, 78	575.67 572.63 557.70	629, 23 670, 70 <b>6</b> 69, 23	888.23 869.23 668.67	
	Pool Content EOM (1000 AC. FT.)	987, 42	987, 42, 1030, 31, 107	6. 16	1113.11	1:34, 36-1	1069. 63 1	1042.81	984. 30	974. 18	958.73	965. 25	949, 0 <b>3</b>	

	TWIN BUTTES LAKE Inflows(1000 AC.FT) Avg 1963 thru 1988 WY 1988	Relesses(1000 AC FT) Avg 1963 thru 1983 WY 1988	Rainfall (inches) Avg 1964 thru 1989 WY 1988 Deviation	Pool Elevation 19 End of Month 19 Maximum 19 Minimum 19	Pool Content EDM (1060 AC. FT.)		FISHER LAKE	Inflows(1000 AC.FT) Avg 1915 thru 1988 WY 1988	Releases(1000 AC.FT) Avg 1953 thru 1988 WY 1988	Rainfall (inches) Avg 1953 thru 1988 WY 1988 Deviation	Pool Elevation End of Month Maximum Minimum	
OCT	7.1 3.8	÷ 0	2. 10 0. 34 -1. 75	1935, 31 1935, 32 1935, 16	137. 64	001	!	M G	0.0	6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	1895, 03 1896, 66 1896, 05	
NON N	ယ <u>် 4</u> ဆ က	1.0	0 94 0 80 -0 14	1935, 59 1925, 59 1935, 31	139, 73	) ON		0.0	• 0	1.09 1.0.53 0.53	5 1895, 71 5 1896, 05 5 1895, 71	
DEC	ю 4 8 0	4.0	9.00 9.00 9.00	1935, 68 1935, 88 1935, 59	141.92	DEC		4 n	0 0 0 0	3 0 65 3 2.80 1.95	1 1895, 80 3 1895, 82 1 1895, 56	
OAN	6. 6 7 B	0 O	0.59 0.01 -0.58	1936, 56 1936, 56 1935, 88	147.16	O		4.ε. 0.0	0.0	0.00	1895, 7 1895, 8 1895, 7	
FEB	w. 4. ∠ w	4.0 0.0	1.03 0.43 -0.50	1936, <b>86</b> 1 1936, 86 1 1935, 56 1	147, 52	<u>ព</u> ម		7 0 0	0.0	4 0 94 2 0 27 2 -0 67	1 1895, 55 0 1895, 71 1 1895, 56	
A R	ພ 4 <u>.</u> ສະທ	1.7	0. BB 0. 95 0. 07	1936. 69 1 1936. 92 1 1936. 69 1	148.18	AA AA A		5 7 1.1 0	0.0	4 6. 43 7 -0. 59	1895.09 1895.56 1895.09	
APR	ણ. <del>4</del> છાછ	ന് ന്	1.37 1.36 -0.01	1936. 19 1 1936. 69 1 1936. 19 1	144, 29	~ APR		3.7	0.00	3 1.85 1.37 -0.48	1894 57 1895 09 1894 57	
A Y	თ. <b>.</b> დ 4	4. U. 4. **	2. 51 4. 34 1. 83	936, 14, 1 936, 19, 1 935, 83, 1	143.90 1	F A		₽, 1, 1, 4	<b>n</b> o	6.99 -0.35 35	1894, 16 1894, 57 1894, 14	
NO O	4. R.	9 O	20.01 1.04	935. 78 19 936. 15 19 935. 47 19	141.16 1	N N		() () ()	6 0 0 0	21 ± 0 22 ± 24 24 ± 24	1893, 50 1894, 18 1893, 50	
ا ا	ពុល 4.0	n, n, 4 ↔	1. 06 1. 87 0. 61	935, 02 19 935, 78 19 935, 02 19	35. 50 1	, JUL		6. t	0.0 0.0	1. 68 3. 87 2. 19	1892, 91 1893, 50 1892, 91	
900	4 74 4 74	4. ?. ± . 8	1. 53 0. 86 -0. 79	33.68.1 25.02.1 33.69.1	25.96 1	Ø∩ <b>∀</b>		4 9 9 9	0 0 0	2. 13 -1. 42	1891. 93 1892. 91 1891. 93	
SEP	၈ဝ လေးလ်	<b>® ®</b> ₽ Ø	9.86 0.25 25	934, 04 934, 05 933, 29	23. 47	S	; ∶.	7. S	<b>6</b> 0	3.02 9.08 0.06	1891, 92 1892, 13 1891, 40	
TUTAL	61. 4 58. 9	စ <b>်</b> ကို လို ကို လို	17.64 20.77 3.13			TOTAL	] 	00 ↔ 4 €	4,0 8,0	21. 12. 12. 12. 12. 12. 12. 12. 12. 12.		

Inflowed to Color			1001	NON	DEC	Z 7	FEB	MAR	APR	\ \ \ \ \ \ \ \	N N	JUL	Ø∩ <b>∀</b>	SEP	TOTAL
Principle   Prin	SOME	ERVILLE LAKE											•	•	
Releases(1000 AC FT)  Avg 1967 thru 1988  Rainfall (inches)  Avg 1967 thru 1988  Avg 1967 thru 1967 thru 1988  Avg 1968 thru 1988  Avg 1968 thru 1988  Avg 1968 thru 1988	•	Inflows(1000 AC.FT) Avg 1924 thru 1988 WY 1988	12.7 0 6	हुन <i>1</i> 3 स	17. 0 7. 2				26. ₹ 5. 2						(U
Rainfall (inches)       4 02       3.17       2.57       2.46       2.52       2.58       5.03       3.62       1.80       2.23       4.10         Avg 1967 thru 1983       0.15       3.44       3.29       0.93       1.25       2.33       2.46       2.13       1.97       0.64       2.04       2.04         WY 1988       -3.97       0.15       3.44       3.29       -1.64       -1.11       -0.19       -0.42       -2.95       -1.16       -0.19       -0.19       -0.42       -2.95       -1.16       -0.19       -0.19       -0.42       -2.95       -1.16       -0.19       -0.19       -0.42       -2.95       -1.16       -0.19       -0.19       -0.42       -2.95       -1.16       -0.19       -0	•	Releases(1000 AC FT) Avg 1967 thru 1988 uv 1983	<b></b> o დ0		9,0				19.8						
Pool Elevation Eur, 35 237, 95 237, 99 208, 03 208, 39 208, 39 209, 84 207, 97 207, 52 208, 82 208, 94 208, 94 208, 95 207, 52 208, 95 208, 97 207, 52 208, 98 208, 99 208, 43 208, 96 208, 28 207, 97 207, 52 208, 98 207, 97 207, 52 208, 99 208, 43 208, 43 208, 98 207, 98 207, 98 207, 94 208, 93 208, 11 208, 10 207, 83 207, 86 207, 52 208, 82 205, 82		Fainfall (inches) Avg 1967 thru 1983 WY 1988 Deviation	4 Q 4 G 4 B G 6 F		લાંભવ										1
Fool Content EOM 192, 77 154, 78 159, 54 160, 45 162, 41 164, 62 163, 92 158, 51 159, 77 154, 67 146, 93 130,		Pool Elevation End of Month Maximum Marimum	207, 35 207, 37 237, 35		2000 7000 7000							207, 52 237, 97 937, 52	23c. 62 237, 52 236. 82		
	V	Fool Content EOM (1000 AC. FT.)	152.77	154. 78	159.	160.		164, 62	163.92		159, 77	154, 67		130, 24	

## COLCIRADO RIVER BASIN

### NAVAJO DAM

	덩	ğ	280	JAN	<b>E</b>	MAR	AFR	MAY	Age.	JOE	AUC	Sign	TOTAL
Inflows (1000 Ac-Ft) FY 1988	32.65	32.65 46.28	20.93	20.11	26.78	61.98	96.11	124.19	116.38	46.18	74.67	47.31	713.58
Releases (1000 Ac-Ft) FY 1988	38.83	36.00	37.20	37.20	34.80	37.20	36.00	37.20	36.11	39.81	38.92	36.33	445.60
Rainfall (Inches)	Data Una	Data Unavailable											
Pool Elevation (ECM) Maximum Minimum	6037.42 6038.45 6037.30	6037.42 6038.33 6036.74 6035. 6038.45 6068.62 6038.29 6036. 6037.30 6037.51 6036.74 6035.	6036.74 6038.29 6036.74	6035.05 6036.65 6035.05	6034.21 6035.05 6033.88	6036.34 6036.34 6034.46	6040.73 6040.73 6036.34	60,46.69 60,46.69 6040.90	6051.10 6051.10 6046.81	6048.87 6051.20 6048.87	6049.88 6049.88 6048.65	6049.43	
Pool Content (BCM) (1000 Ac-Ft)	1082.30	1082.30 1091.90 1075.11 1057.53	1075.11	1057.53	1048.87	1070,93	1117.60	1183.77	1234.90	1208.82	1220.57	1215.32	

PLATORO RESERVOTR

	ESO.	NON	) Dec	JAN	<b>193</b>	MAR	AFR	MAY	JUN	JOE	AUC	SEP	TOTAL
FY 1988	57.	<b>38</b> .	45	8.	.32	67.	2.67	11.84	19.01	4.90	3.66	2.19	47.60
Releases (1000 Ac-Ft) FY 1988	67.	1.01	19. 1	19.	75.	8.	8.	12.10	20.24	12.83	<b>8.8</b>	2.81	61.63
Rainfall (Inches)	DATA IS	DATA IS NOT AVAILABLE	TABLE										
Pool Elevation(ECM) Marimm Minimm	10016.7 10016.8 10016.6	10016.5 10016.8 10016.4	10016.3 10016.4 10016.3	10016.14 10016.30 10016.14	10015.84 10016.19 10015.84	10015.96 10015.96 10015.76	10018.02 10018.02 10015.98	10017.95 10018.50 10017.86	10016.41 10017.82 10016.41	10006.23 10016.25 10006.23	9998.61 10005.65 9998.61	9997.47 9998.56 9997.47	
Pool Content (EDM) (1000 Ac-Ft)	73.96	. 43.79	43.62	43.49	43.24	43.39	45.08	45.02	43.72	35.55	29.99	29.19	
ABIQUIU, DAM	00 <u>T</u>	NO	Dec	JAN	EE	MAR	AFR	MAX	JUN	JUL	AUC	SEP	TOTAL
Inflows (1000 Ac-Ft) Avg 1926 thru 1988 FY 1988	12.0 <b>8</b> 13.44	13.79	12.17 10.79	5.43	9.73 10.93	19.69 21.32	51.02 50.00	96.77 73.16	52.75 25.20	25.82 22.34	25.63 23.84	18.01 16.54	342.90 290.60
Releases (1000 Ac-Ft) Avg 1963 thru 1988 FY 1988	13.37 75.21	22.81 42.39	21.71 3.19	10.70	12.59	22.85 27.12	46.35	67.53 66.28	55.40 30.00	31.97 19.30	24.02 19.48	17.70	346.99 350.97
Rainfall (Inches) Avg 1957 thru 1988 FY 1988	8, 3,	.52	.37	3 %	.27 .04	.55 .01	<b>%</b> . 8.	.82	4.1.34	1.66	1.97	1.17	9.99
Pool Elevation (ECM) Maximum Minimum	6222.04 6235.74 6222.04	6214.72 6221.54 6214.28	6216.52 6216.52 6214.77	6218.02 6218.02 6216.56	6219.89 6219.89 6218.08	6218.15 6220.76 6218.06	6218.06 6218.31 6217.93	6219.22 6220.38 6218.37	6217.50 6218.86 6217.45	6217.67 6217.78 6217.27	6218.29 6218.60 6217.51	6218.75 6219.04 6218.28	
Pool Content (ETM) (1000 Ac-Ft)	199.81	170.11	177.21	183.23	190,86	183.76	183.39	188.11	181.13	181.82	184.34	186.19	

1 Data for compiling averages unavailable

×
Ä
H
뫼
멎
81
•

Var. 4 (00)/ (3-1	OCT	NO.	DBC	JAN	<b>60</b> 4	MAR	AFR	MAY	JUN	<b>Jag</b>	AUC	<b>25</b>	TOTAL
Avg 1910 thru 1988 FY 1988	49.30 81.00	¥.71 67.04	48.96 38.18	41.50	47.60	80.91 84.74	138.87	272.08 112.74	204.19 67.71	82.68 48.60	57.41 56.74	44.32 54.71	1125.59
Releases (1000 Ac-Ft) Avg 1975 thru 1988 FY 1988	39.78 36.81	53.18 52.36	57.43 58.50	52.34 65.05	63.25 93.91	88.77 133.05	142.40 161.82	235.24 140.23	217.59	139.72	66.5 <b>8</b> 46.41	48.89 61.95	1205.17 972.55
Rainfall (Inches) Avg 1967 thru 1988 FY 1988	1.19	8.	62.	.61 .57	<b>3</b> . 2.	.65 .13	.72 1.97	.98 1.33	.79	1.79	3.30	1.61 3.23	12.33 15.91
Pool Elevation (BDM) Maximum Minimum	5408.39 5408.39 5398.38	5411.45 5413.34 5408.92	5406.71 5411.21 5406.71	5400.30 5406.50 5400.30	5386.95 5399.85 5386.95	5370.65 5386.69 5370.65	5354.15 5369.45 5354.15	5336.74 5353.67 5336.74	5331.24 5336.04 5331.24	5330.63 5331.48 5330.63	5338.25 5338.25 5330.64	5332.31 5341.50 5331.82	
Pool Content (BDM) (1000 Ac-Pt)	259.72	273.43	252.39	221.86	172.89	121.31	84.43	55.92	48.93	48.24	57.95	50.19	
CALISTED DAM													
Inflows (1000 Ac-Ft) Avg 1971 thru 1988 FY 1988	OCT	OCT NOV INFLOW - OUTFLOW	DBC	JAN	FEB	MAR	AFR	МАХ	JUN	Jul	ALC	ZES	TOTAL
Releases (1000 Ac-Ft) Avg 1971 thru 1988 FY 1988	.42 .0	8 3	<b>8</b> . 69.	8.6	.10	10.	.21 .14	.29	.25 .16	1.14	.97	.70 1.59	4.49
Rainfall (Inches) Avg 1971 thru 1988 FY 1988	1.12 .51	<b>%</b> 8	.41	.32	.55	26.	.73	78.	.63	1.47	1.69	1.27	10. <i>2</i> 9 14.63
Pool Elevation (ECM) Maximum Minimum	2	no end of month storage	CNTH STO		CURING THE YEAR								
Pool Content (BCM) (1000 Ac-Ft)	0	0	0	0	0	0	0	0	0	0	0	0	

### JEMEZ CANYON DAM

TOTAL	55.31 48.43	49.67	8.92 14.03			TOTAL	%.78 84.12	73.25 98.34	16.93 19.18		
SE	1.69 8.60	1.56	1.19	51%.77 51%.51 51%.79	26.75	SE SE	8.61 24.61	11.63	1.96	4738.23 4743.64 4738.23	78.82
AUC	2.44 5.40	2.79	1.58	5195.92 5195.92 5195.04	28.30	AUG	14.61 17.09	10.77 15.95	3.36 1.33	4743.55 4746.03 4743.55	8.79
JUL	1.29	2.98	1.30	5195.31 5196.39 5195.27	27.47	J0L	8.56 13.23	15.51 16.37	1.70	4743.65 4744.47 4742.38	97.06
N)	2.89 1.84	6.19	.57	51%.36 51%.85 52%.16	28.90	JIN	18.75 8.51	13.45 15.68	2.13 3.33	4745.12 4748.34 4745.12	102.44
MAY	15.04	12.69 10.17	.65	5197.00 5200.58 5197.00	29.79	MAY	20.36 7.57	13.51 6.85	1.72	4747.51 4748.02 4747.51	111.60
AFR	18.26 12.20	10.99	. 44 2. 44	5200.10 5200.10 5196.57	34.25	APR	9.22	2.12 .05	.98	4747.86 4747.86 4747.59	112.98
MAR	4.25	3.80	.01	5193.36 5196.36 5194.59	28.90	MAR	4.77	1.80	.57	4747.58 4747.62 4747.58	111.87
FE3	1.94	1.72	% %	5194.60 5194.78 5194.60	26.53	FEB	2.15 1.81	1.05	¥ 2	4747.59 4747.59 4747.46	111.91
JAN		vo 60	8. 19	<b>3</b> 8 36	26.63	NA.	1.75	<b>8</b> 9. 27.	6 <del>3</del> .	34. 8. 8. 8.	9.
	1.66	1.56	• •	5194.68 5194.84 5194.62	36	ר		1	• •		111
DBC	1.60	1.40	<del>4</del> . 75.	51%.64 51%.99 51%.63	26.58	DEC	1.77	.68 .86 .1	. 71	4747	111.67 111
NOV DEC						,		1		4747.53 4747 4747.55 4747 4747.45 4747	111
	1.60	1.40	<del>4</del> . 75.	51%.64 51%.99 51%.63	26.58	DEC	1.77	.88	17. 87.	4747.55 4747.53 4747 4747.55 4747.55 4747 4747.45 4747.45 4747	111.67 111

# TWO RIVERS RESERVOIR

	50	NON	DBC	JAN	<b>55</b>	MAR	APR	MAY	NOC	JUL	AUC	SEE	TOTAL
Inflows (1000 Ac-Ft) Avg 1964 thru 1988 FY 1988	1.12 .9.		.77 1.79	.82 2.06	.65	.88	1.15	છ. કર્	12. 0.	£ <del>,</del> 8.	1.41	1.79	11.37
Releases (1000 Ac-Pt) Avg 1964 thru 1988 FY 1988	1.12 .9.	g. 2	.77 1.79	.83 2.06	.66	.88	1.15	છ. જ	0.		1.41	1.79	11.35
Rainfall (Inches) Avg 1964 thru 1986 FY 1988	.91 Data Ur	.91 .38 Deta Unevallable	.17	.18	8.	2.	¥.	89.	1.55	1.7	2.77	1.89	10.82
Pool Elevation (ECM) Maximum Minimum	000	000	000	0 3984.58 0	000	000	000	000	000	•••	000	000	000
Pool Content (BDM) (1000 AC-FT)	0	0	0	0	0	0	0	0	0	0	0	0	0
SIMNER LAKE													
	<b>6</b>	NOV	DEC	JAN	<b>65</b>	MAR	AFR	MAY	NDC N	JUL	AUC	돲	TOTAL
Inflows (1000 Ac-Ft) FY 1988	Data U	Data Unavailable											
Releases (1000 Ac-Ft) FY 1988	13.25	8.	11.	.19	2.92	5.97	4.35	36.45	17.66	23.96	18.19	52.25	175.50
Rainfall (Inches) FY 1988	8.	9.	.24	.16	.07	.03	1.08	1.65	1.95	5.70	2.00	2.88	16.38
Pool Elevation (ECM) Maximum Minimum	4250.8 4255.3 4250.8	4253.4 4253.4 4250.8	4255.9 4255.9 4253.4	4258.5 4258.5 4255.9	4259.0 4259.2 4258.5	4258.0 4259.0 4258.0	4257.7 4258.2 4257.7	4245.6 4257.7 4244.1	4245.7 4247.1 4245.2	4247.9 4248.5 4245.7	4246.8 4247.9 4246.8	4244.5 4247.8 4241.3	
Pool Content (EDM) (1000 Ac-Ft)	27.45	32.62	38.20	44.63	45.94	43.34	42.58	19.03	19.17	22.44	20.74	17.44	

SECTION VIII - MINUTES OF THE ARKANSAS RIVER COORDINATING COMMITTEE MEETING AND THE ANNUAL RESERVOIR CONTROL CENTER MEETING

- 1. RESERVOIR CONTROL CENTER
- 2. ARKANSAS RIVER BASIN

### MINUTES

### 1988 ANNUAL RESERVOIR CONTROL CENTER MEETING SOUTHWESTERN DIVISION CORPS OF ENGINEERS 16 and 17 NOVEMBER 1988

I. <u>INTRODUCTION AND REMARKS</u>. The 1988 Annual Reservoir Control Center (RCC) meeting was held on 16 and 17 November 1988, in the Southwestern Division (SWD) office, Dallas, Texas. Mr. Charles Sullivan, Chief of the RCC started the meeting by asking each attendee to introduce themselves, to include the number of years involved in Reservoir Control. The agenda and attendance list are enclosed as attachments 1 and 2, respectively.

### II. DISTRICT STATUS REPORTS.

TULSA DISTRICT. Mr. Ross Copley reported flows on the Arkansas River were moderate at the start of this year, became progressively dry with time. Unable to provide water to sustain flows for navigation tapers. The first navigation emergency was declared by the Division Commander. declaration allowed the use of some conservation storage in Kaw, Keystone, Oologah, Hulah, Copan, Tenkiller, and Eufaula to flows to keep the navigation system open provide maintenance dredging could be completed.

Flows in the Red River Basin ranged from 140 percent of normal in the upper basin to about 50 percent of normal below Lake Texoma. No major floods occurred; but, did experience some isolated events. These isolated floods resulted in high pool levels in Hugo and Broken Bow Lakes. McGee Creek Reservoir (Section 7 project) filled for the first time in February 88.

Significant progress was made on the development of water control manuals for Keystone and Toronto Lakes. First draft Drought Contingency Plans (DCP) were submitted for priority river basins in September. The District plans to contract out works on several future DCPs. Funds for contract work are currently available. Also, the District plans to contract some work on water control manuals.

Mr. Carroll Scoggins also reported for the Tulsa District. His discussion centered on benefits that can be gained from major flood events. The October 1986 flooding in the Arkansas River has enabled the District to obtain funds to purchase additional hydrologic equipment, improve stream gaging equipment, i.e., replace gages on bridges with gages at higher ground locations, install DCPs, install staff gages, rain gages, etc., at critical station locations. Also, provided funds to have USGS to extend rating curves to include higher flows. Carroll showed slides of some of the equipment which has been installed at key stations.

b. FORT WORTH DISTRICT. The District installed 12 gages in

the Upper Trinity River Basin for model tests and development. The network is working well as reported by Mr. Arnold Escobar. Seven of the 24 projects were visted by Water Management personnel during the year. More projects will be visited after the Reservoir Control section is realigned. The realignment will provide for more project regulators; therefore, more personnel for project visitation. Fourteen out of the District's 24 projects stored water in their flood pools. However, by mid-May many parts of the state of Texas were experiencing well below normal rainfall and by the end of September the annual rainfall ranged from 68 percent of normal in the eastern part of the state to about 75 percent of normal in the Panhandle. In July the District began Drought Contingency Plan Development for their projects on a basin or sub-basin concept. The plans are scheduled to be completed in 1990.

- Mr. Escobar reported that the non-Federal hydropower activities for the past year consisted of the following:
- On 18 Nov 87, Canyon Lake was lowered eight feet below the conservation pool and the gates closed in order that relining of the flood control conduit could be started. In Sep 88 the District inspected the hydropower facility and the pressurization testing of the conduit and bypass system is scheduled for Oct and Nov 1988.
- Construction of the non-Federal facility at Town Bluff Dam continued during the past year and the completion date is scheduled in April 1989.
- License applications are under review for Lewisville, Ray Roberts. Wright Patman, and Lake O' The Pines.

Water quality reports for 15 of the 24 projects have been prepared and submitted to SWD. These studies have not surfaced any major water quality problems. Completed sediment resurvey report in Oct 88 for Stillhouse Hollow. No funding for sediment FY 88 flood damages prevented by Corps surveys for FY 89. projects exceded \$6 million. Arnold stated that the Ground Receive Station (GRS) equipment was transferred to the USGS The transfer is a part of the memorandum of Agreement between the Corps and the USGS for the USGS to provide operation and maintenance for the GRS. In July 88, sixteen employees took a course titled "Flood Forecasting: which was presented by HEC personnel. Contract work during the year included the completion of modeling for Brazos and Trinity River Basins by the SWT. Through an A-E contract portions of water control manuals were completed for Navarro Mills, Bardwell, and the Trinity River Basin master manuals. Arnold concluded his report by sharing information with the group concerning the project manager's capability to remotely operate the flood gates at Georgetown Lake. This raised concerns for the security of such operations, i.e., access to the controls by unauthorized personnel. Questions were also asked as to whether engineering had been in making such decisions. Dick Kreiner of the involved

Albuquerque District stated that their Abiqui project had been automated; however, the automation equipment has been abandoned due to the technical requirements for maintaining the operations. Mr. Sullivan requested that each District investigate activities concerning the automation of flood gate operation and provide feedback through their Branch Chiefs to SWDO.

c. <u>LITTLE ROCK DISTRICT</u>. Mr. Jim Proctor reported for the Little Rock District. He said the District experienced extreme conditions during the year, above normal rainfall in the early winter months and below average amounts during most of the summer months. Drought conditions were experienced in the spring and summer months; however, overall conditions were not as severe as published. Problems were experienced in navigation due to low flows on the Mississippi Riover and large volumes of material were dredged in order to maintain navigation depths. Had as many as 5 dredges working in the 10 mile entrance channel at one time during the summer.

The District requested 27 deviations during the past year. These deviations were required for shoaling problems along the Arkansas, hydropower, recreation, assist upstream District, project maintenance, fisheries, farming and drowning. Other items of interest include:

- Beaver Dam cut-off wall for seepage control. Bids are being taken with the target to begin construction in April 1989.
- Clearwater seepage control and spillway widening with a parapet wall across dam. Construction is approximately 60 percent complete.
- White River entrance channel problems. Possible solution is to construct an additional L&D near the mouth to overcome low stages on the Mississippi. A justification report is scheduled to be submitted to higher authority in September 1990.
- Non-Federal hydropower. Construction of power plants at L&D No. 13 and L&D No. 7 is nearing completion. Experiencing good coordination with L&D No. 13; however, not true at L&D No. 7. Jim recommends that these plants be automated so that the District can get data on a real-time basis.
- d. <u>GALVESTON</u> <u>DISTRICT</u>. The District experienced dry conditions for the entire year without flow into Addicks and Barker reservoirs as reported by Mr. Charles Scheffler. There were no sediment or water quality activities during the past year because of the dry conditions. Hurricane Gilbert did not produce the rainfall as expected. However, the District went into emergency operations where most of Corps personnel were evacuated. No problems with the USGS maintenance contract for maintaining data collection platforms (DCP). Some statons were vandalized. Work was continued on the hydrologic network, i.e., installation of DCPs.

e. <u>ALBUQUERQUE DISTRICT</u>. Mr. Dick Kreiner reported eleven projects were visited by reservoir regulation personnel. Watersheds within the District received well below normal snowmelt runoff.

Construction of the Abiquiu non-Federal hydropower project continued in 1988. The flood control conduit was closed from Dec through Feb 88 to allow for the installation of a steel liner While the liner was being installed, 50 cfs was in the conduit. pumped over the dam to meet downstream needs. The Plenum chamber installation will start in mid-Nov 88 and continue through The Bureau of Reclamation tested the automatic operation of the spillway gates at Sumner Dam (Section 7) where the reservoir regulation personnel participated. The gates open automatically when 60 percent of the flood storage is utilized which result large increased releases. The test showed that the gates open very rapidly; therefore, every effort will be made to limit the elevation from this range. On 6 Sep 88 the Bureau began initial filling of the newly completed Brantley Dam (Section 7). The primary purpose of the dam is for dam safety. Dam safety evaluations for McMillan and Avalon dams showed that they had inadquate spillway capacities. The old McMillan dam will be contained within the reservoir area of Prantley and the dam will be breached in 1989. Avalon is below Brantley and will be used primarily as a diversion structure.

The Rio Grande reevaluation study was started during the past year. The 2-year study, as authorized by Congress, directed the Corps to take the lead in evaluating the operation of Federal reservoirs in the Rio Grande basin above Ft. Quitman, Texas. The study will identify opportunities to provide flood protection and additional beneficial use of available water. The final report is scheduled for completion in FY 89.

III. SOUTHWESTERN DIVISION LAB, WATER QUALITY ANALYSES. Mr. William Tanner, Director of the Lab briefed the group on functions and activities of the Lab, i.e., testing of soils, concrete, environmental, etc. He stated, however, his specific reason for attending the meeting was to solicit help in the area water quality testing. Would like to have the Districts to have their water quality testing done through the Lab. Mr. Tanner explained that they were equipped to do the analyses could do them at competitive prices. At this point he introduced Cathy Hutchins. Chief of the Environmental Section. reiterated the Lab's capability of providing service in water quality testing. The Lab is capable of doing all metal tests inhouse with some work being contracted out. Also, has storage capacity with the necessary equipment to do the complete Also, can do BOD, but, recommends that these analyses be done on site. At the end of the presentation. Mr. Sullivan encouraged the District representatives to consider using the Lab if costs are competitive and if same results are the same as current analyses. Mr. Tanner added that costs are negotiable.

NEXRAD UPDATE. NEXRAD is the next generation of radar systems as stated by Mr. Clinton Word. The system is fully automated. The first stage of development will not include all features, such a precipitation stations. The second stage which to be complete in early 1989 will include expected precipitation stations. Water control activities should be enhanced by the use of NEXRAD because of its ability to measure and it provides ground spatically truth  $\mathsf{of}$ rainfall. Precipitation measurements will be received every 5 minutes and volumes every hour. Currently the accuracy of the system is however, the system has great potential being questioned; expecially with the ongoing development. In order to make the system work, support is needed from all. In closing, Mr. Word that a prototype should be up within the next year. stated Carrol Scoggins continued the discussion on the NEXRAD by reinforcing the need for support of the system. He said support is being sought through states, universities, etc. At this point, support is good. The District's data collection platforms (DCP) are expected to be included in the Rainfall Network. Need HEC and WES types involved to assist in developing both hardware and software. The Air Weather Service is the key element in design of the system and solicits the Corps' involvement. Carroll also requested the SWDO to emphasize the system to HEC so that they may get involved in developing software.

### V. BACK-UP PROCEDURES-WATER CONTROL DATA SYSTEM.

a. <u>General:</u> Mr. John Parks began his discussion by defining the WCDS and stressed it did not only consist of a computer but consists of other key elements, i.e., DCPs, software, etc. John commended the group for their input into developing the system. The SWDO WCDS is equal to any system in the country; however, we need to stay on top of things to stay ahead.

### b. <u>COOP Status:</u>

- (1) System Plan Complete
- (a) <u>Data Acquisition Procedures</u> was not included in plan, but is needed for back-up system.
- (b) <u>Data Base and Software</u> the data base is to handle all data within SWD; however, all of the software is not complete.
- (c) <u>Equipment</u> Complete except for the Albuquerque and Galveston Districts.
- (2) <u>Local Plans (Appendix to Plan)</u> Local plans should consist of notification procedures, procedures for bringing the system up and procedures for relocating.
- c. <u>Implementation</u> and <u>Testing of COOP</u> The plan has not been tested. At this point, a test is expected to surface some holes in the system.

At the end of John's presentation, a general discussion took place concerning the use of data bases (DSS vs. Total). After lengthy debates and no agreement as to what data base would be used in SWDO, and without an agreement on data base selection, SWDO requested that the COOP plan be revised to reflect the preferred data base.

- VI. WATER CONTROL MANUALS AND SCHEDULES. Mr. Charles Sullivan said this year's request for manual schedules asked for more details than in past years. SWDO will be doing a more thorough review of schedules and will provide each District feedback on their schedules. Projection for manual schedules has been extended from three years to five years. The Chief of Engineering Division, SWDO, places water control manual development as second highest priority in SWDO.
- VII. <u>SWDO (DALLAS SITE) DATA BASE DEFICIENCY.</u> Mr. John Parks gave a brief summary of deficiencies of Dallas site in the following areas:
  - a. Goes Data Retrieval back-up system.
- b. <u>Pertinent Data Files</u> Need updating by districts. A tool to do the updating is a program names "PERT", which extracts pertinent data from data base.
- c. <u>Maintenance of the MCF Files</u> currently being updated by SWDO.
- d. <u>Error Checking</u> Set extreme units in MCF to kick out obvious bad data; however, this procedure will not eliminate all errors.
- VIII. <u>WATER MANAGEMENT BUDGET</u>. From a series of slides and handouts, Mr. John Parks discussed some of the past year's budgeting activities. A serious error was made during the budget review, Engineering at SWDO was not given the opportunity for budget review. Consequently, SWD-ED was unable to defend activities related to water control. It is necessary that SWD-ED be representated to answer questions concerning level of funding of water control manuals, i.e., plan development may be in levels 1 and 2, but manual documentation is in a lower level.
- IX. <u>DROUGHT CONTINGENCY PLAN DEVELOPMENT.</u> Mr. Ralph Garland gave an update on plan development. The 18 and 19 October 1988, meeting allowed for ajoint review of first draft DCPs along with concurrent review of the "SWD Framework". The DCPs were reviewed mainly for consistency in format and content. Upon completion of DCP reviews, it became obvious that major inconsistencies existed from District to District even between reports developed within the same District. Therefore, the committee made the decision to revise the framework in order to achieve the consistency in all reports. Revisions consisted of:

- Standardizing the table of content.
- Standardizing paragraph 1 "Purpose of Document".
- Require the use of drought severity index as published by NOAA/USDA.
- Editorial changes throughout the framework. The framework would be revised by SWDO with above changes and provided to the Districts for continuing development of their DCPs.
- X. <u>AFOS DATA EXCHANGE</u>. Mr. John Parks stated that the VUENWS current capabilities include graphics enhancements that have been made over the last two years. Nineteen to 20 products have been selected for use; however, there are still some problems with the RFC in Tulsa, OK. The product index file should contain the same products for all sites. The Dallas site file has been completed.
- XI. WATER CONTROL PC FIELD GROUP MEETING. The purpose of the meeting was to discuss the life of the Harris system as stated by Mr. John Parks. The expected life of the system is through 1992. Majority of the discussions centered around the pros and cons of the Harris system, i.e., if the system is small then PCs would be adequate; however, if a large system, then will need something larger. One of the concerns for the Harris is because of Harris' nonsupport for the existing systems. Some of the recommendations were to have a system of PCS or the Unix. No solutions were arrived at this meeting. The next meeting agenda will contain an item to analyze the Corps wide contract to determine its needs and also analyze its communications network.
- XII. <u>NESDIS DCS AUTOMATIC PROCESSING SYSTEM (DAPS)</u>. Mr. John Parks stated that the current status of the system is that the NEDIS has a contract to update the system. The updated system should be in place by July 1989. Enchancements to the system by the Corps are: (i) GOES demodulators have been deleted and, (ii) DOMSAT will probably be used. John asked that each District should assure that they are receiving minutes of the TWG meetings. These are important because they contain current system changes.
- XIII. <u>OTHER TOPICS</u>. Mr. Charles Sullivan reported on these topics:
- a. <u>Ground Receive Station (GRS)</u>. The back-up to the GRS should be in place as soon as possible. It should take about 3-1/2 weeks to do the software. The Fort Worth District is expected to provide a person to SWDO to complete the job.
- b. <u>Meteorologist Position in SWDO Water Management Branch</u> Mr. Sullivan informed the group as to when the person would be entering on duty and discussed some of the job duties. He asked for suggestions as to what jobs the meteorologist could do for the Districts. NEXRAD will be one of the major duties.

- c. <u>Harris Support for Total Database</u> Harris' support will be through March 1993. The cost for the maintenance is questionable at this time; however, his feelings are that we will not have to pay for the maintenance.
- XIV. <u>SUMMARY</u>. The following is a list of items discussed by the group in closing the meeting:
- Why not have the annual RCC meeting in District offices? The Albuquerque District is recommended for the next year's meeting place. Some of the advantages of having the meeting in the District are involvement of District staff, see projects that may have interest to all, etc.
- Task group for the COOP plan should meet and make necessary revisions within the next two weeks.

### AGENDA 1988 RCC ANNUAL MEETING SOUTHWESTERN DIVISION CORPS OF ENGINEERS

### 16-17 NOV 88

1st Day 1000

- I. INTRODUCTION & REMARKS
- II. DISTRICT STATUS REPORT
- III. SOUTHWESTERN DIVISION LAB, WATER QUALITY ANALYSES
  - IV. NEXRAD UPDATE
    - V. BACK-UP PROCEDURES WATER CONTROL DATA SYSTEM
      - A. GENERAL
      - B. COOP STATUS:
        - 1. SYSTEM PLAN
          - a. DATA ACQUISITION PROCEDURES
          - b. DATA BASE AND SOFTWARE
          - c. EQUIPMENT
        - 2. LOCAL PLANS (APPENDIX TO SYSTEM PLAN)
      - C. IMPLEMENTATION AND TESTING OF COOP
  - VI. WATER CONTROL MANUALS AND SCHEDULES.
- VII. SWDO (DALLAS SITE) DATA BASE DEFICIENCY
- VIII. WATER MANAGEMENT BUDGET

### AGENDA 1988 RCC ANNUAL MEETING 16-17 NOV 88

2ND DAY

0800

- IX. DROUGHT CONTINGENCY PLAN DEVELOPMENT
- X. AFOS DATA EXCHANGE
  - A. VUENWS CURRENT CAPABILITIES, GRAPHICS
  - B. PRODUCT LIST, INDEX AT ALL SITES
- XI. WATER CONTROL PC FIELD GROUP MEETING (19-20 OCT 88)
  - A. PURPOSE
  - B. RESULTS
- XII. NESDIS DCS AUTOMATIC PROCESSING SYSTEM (DAPS)
  - A. CURRENT STATUS
  - B. ENHANCEMENTS TO GOES DCS BY CORPS
    - 1. GOES DEMODULATORS
    - 2. SATELLITE DATA DISTRIBUTION SYSTEM (DOMSAT)
  - C. DAPS PLATFORM DATA TABLE (DPT)

### XIII. OTHER TOPICS

- A. GRS TRANSFER TO USGS
- B. METEROLOGIST POSITION IN SWDO WATER MANAGEMENT BRANCH
- C. HARRIS SUPPORT FOR TOTAL DATABASE
- D. INSTALL NEW OPERATING SYSTEM ON HARRIS
  - 1. SCHEDULE
  - 2. NEED FOR COORDINATED INSTALLATION

### XIV. ADJOURN

### 1988 REC ANNUAL MEETING

### Southwestern Division U.S. Army Corps of Engineers

### 16-17 November 1988

### ATTENDANCE LIST

NAME	ORGANIZATION
Ralph Garland	CESWD- ED- WF
John R. Parks	CESWD-ED: WH
Jim Bacton	CESWIT ED HIR
Loren Pope	CESWL -ED-11
Charles Scheffler, Jr.	CESWG ED-H
Douglas Permin	CESWE-ED HIC
Elgie Henderson	CESWF-ED-HH
Cliff Victor	CESHF EF -Wik
Clinton Word	CEDWI EC HO
Ross Copley	CHSWI-ECHIR
James A. Procto	CESM -FD-HD
Arnold Escoba	CESWE-ED-FIL
Frank Janamillo	CESWAED- FH
Carroll Scoggine	CESWT-EC: H
Dick kreiner	CESWA-ED-PH
Don Gallegos	CESWA-ED PH
Charles Sulityan	CESWD-ED- WA
Faul Rodman	CESWE-ED-HH (Part-time)
Min Rokicki	OAD (Part-time)
William Tanner	CESWD ED-GL (Part-time)
Jim Medloci	CESWE-ED-H4 (Fart-time)

### MINUTES

Arkansas River Basin Coordinating Committee Meeting 1114 Commerce Street, Dallas, Texas 6 June 1988

- 1. The Arkansas River Basin Coordinating Committee meeting was held in the Southwestern Division office, Corps of Engineers, Dallas, Texas on 6 June 1988. A copy of the agenda is attached as enclosure 1. The meeting was attended by 55 people, which included 16 of 22 Committee members and 39 invited guests. A copy of the attendance list is attached as enclosure 2.
- 2. Brigadier General Robert C. Lee, Division Engineer, Southwestern Division, Corps of Engineers, and chairman of the committee, opened the meeting at 10:00 o'clock a.m., welcomed the group to the 2nd meeting of the reconstituted Arkansas River Basin Coordinating Committee, and introduced the attendees.

He briefly reviewed the background that led to the formation of the original Arkansas River Basin Coordinating Committee and the reconstitution of the present committee consisting of state and federal representatives concerned with the many uses within the basin. He pointed out that the committee serves as an advisory committee to the Corps of Engineers in the development of operating plans for the System. A copy of the opening remarks is attached as enclosure 3.

BG Lee stated that the purpose of the meeting and the report were displayed on the screen (see enclosure 4 for a copy of the screen display).

- 3. David Burrough, Chief, Planning Division, Little Rock District presented a review of the Arkansas River Basin, AR and OK, Feasibility Study, Operational Plans Review Draft Report, which is sponsored through the joint efforts of the states of Oklahoma and Arkansas and the Corps of Engineers. A copy of Mr Burrough's presentation is attached as enclosure 5.
- 4. Mr. Ross Copley, Chief, Reservoir Control Section. Tulsa District Corps of Engineers presented a review of the 1987 through spring 1988 operations in the Arkansas River Basin System above Ft. Smith Arkansas. A copy of Mr Copley's presentation is attached as enclosure 6.
- 5. Mr. Bob Schroeder, of the Reservoir Control Center, Little Rock District presented a review of the 1987 through spring 1988 operations in the Arkansas Basin below Ft. Smith, AR. A copy of Mr Schroeder's presentation is attached as enclosure 7.
- 6. Following these presentations, committee members were given the opportunity to address the group. Those committee members present made remarks appropriate to their areas of interest and

expertise. A summary of these remarks are as follows:

- a. Ed Lindsey, Southwestern Power Administration stated that he supports Plan C, with reservation and thinks the taper should stop at the top of conservation pool. He thinks the study should consider the use of noncontracted storage in non-power reservoirs first. The reallocation of uncontracted storage should also be considered. He thinks water may be needed for possible drought conditions.
- b. Chuck Thomas, Oklahoma Soil Conservation Service, stated that plan C appears to approach a reasonable balance. However, other alternatives should be pursued in the feasibility report.
- c. Bob Price, Ark Soil Conservation Service, said the use of the Arkansas River water for irrigation should be studied, and that we should look at the high salt content. He also presented a brief report on the Arkansas Valley Irrigation Project and the Plumb Bayou Watershed Irrigation Project. This report is attached as enclosure 8.
- d. Ed Thompson, Ark-Okla Port Operators Association stated that he favors Plan C.
- e. Dr. Jan Dean, Oklahoma Fish & Wildlife Commission, stated said he was representing Steve Lewis who had other commitments. He said the Operational Plans report underestimates fish & wildlife recreation losses. The methodology used was inadequate and they would like to work with us to use better methodology. There should also be more Oklahoma and U. S. Fish and Wildlife Conservation Commission input. They would like additional pool manipulations, i.e., higher for spring rises. A fishery decline during the next 2-3 years is expected due to the navigation emergency. A written report containing the official comments was submitted and is attached as enclosure 9.
- f. Joel Wentz, Kansas Water Office, stated that Kansas reservoirs have little impact on the lower river. However, they are very critical for flood control.
- g. Jim Barnett, Oklahoma Water Resources Board, said that more concerns need to be addressed in the final report, i.e., refinement of the method of estimating dredging costs, improve estimating of recreation impacts. Also a better method of estimating the archaeological impacts and shore erosion impacts is needed. A written statement was submitted and is attached as enclosure 10.
- h. Randy Young, Ark Soil & Water Conservation. Commission, stated that plan C is good to maximize benefits and maximize competing uses. The Fine Tuning Plan is a positive step and the Corps efforts to maximize coordination with the state is appreciated. He said water supply use will increase in Arkansas and more control of runoff must be exercised to benefit the basin as a whole. A written summary of comments was submitted and is

attached as enclosure 11.

- i. Harvey Bollinger, RedArk Development Authority, said the draft report is a good first step. However, he is concerned that we are emphasizing plans A, B & C. He said that we must focus on other alternatives, including modifications to improve the system. He said we must be consistent in evaluation among purposes and in applications of authority. Also the plan needs to deal with too little water, not just too much water.
- j. Glen Cheatham, Oklahoma Department of Commerce stated support of the use of Plan C until we have better plan. He supports the attempts to improve the reliability of the system and to assure that all purposes are served, not just navigation.
- k. Jim Phillips, Arkansas Waterways Commission, commended the work done and supports Plan C. He would like to see development of plans D, E, F giving 310, 320, 340, or even 365 navigation days. Perhaps this is not possible, but we should strive for that. Need to recognize that 75,000 cfs at Van Buren is to high. A flow of 65,000 cfs at Van Buren, not 75,000 cfs, is needed because the flow increases by 10,000 cfs more when it reaches the end of the system.
- l. John Fearson, Port of Catoosa, indicated that he supports plan C. He said that more navigation days are needed but recognizes the multi-purpose use of the system. The existence of the group is a good tool where all interests can be heard.
- 7. Mr. Estus Walker, Chief, Water Management Branch, Southwestern Division, Corps of Engineers, presented a brief review of the conditions which made the recent declaration of a navigation emergency necessary. A copy of Mr. Walker's presentation is attached as enclosure 12.
- 8. A copy of the Corps legal opinion furnished to GAO in response to GAO legal questions incident to the evaluation of the "Corps of Engineers Operating Plan for the Arkansas River Basin" was made available at the meeting. A copy is also attached as enclosure 13.

### 9. Conclusions.

- a. Brigadier General Lee stated that the advice of the committee is greatly appreciated and that we should move ahead from where we are to finish the feasibility study. He told the members to feel free to contact him any time.
- b. The next meeting was tentatively set for early May 1989.
- 10. Meeting Adjourned at 3:00 p.m.

### \*\* 13 Enclosures

- 1. Agenda
- 2. Attendance List
- 3. Opening Remarks BG Robert C. Lee
- 4. Meeting & Report Purpose Slides
- 5. Arkansas River Basin, AR and OK, Feasibility Study Presentation Mr. David Burrough
- 6. Tulsa District Presentation Mr. Ross Copley
- 7. Little Rock District Presentation Mr. Bob Schroeder
- 8. State of Arkansas Department of Agriculture, Activity Report Mr Bob Price, Ark SCS
- 9. Written Comments OK Department of Wildlife Conservation
- 10. " OK Water Resources Board
- 11. " AR Soil & Water Conservation Commission
- 12. Navigation Emergency Presentation Mr. Estus Walker
- 13. Corps legal opinion in response to GAO
- \*\* NOTE ENCLOSURES NOT PUBLISHED IN THIS REPORT